



FREEVAL

Evaluation of a Fire Radiative Power Product derived from
Meteosat 8/9 and Identification of Operational User Needs

Final Report

Martin G. Schultz, Project Coordinator
Martin Wooster, Project Co-coordinator

Forschungszentrum Jülich GmbH
Institut für Chemie und Dynamik der Geosphäre (ICG)
Troposphäre (ICG-2)

FREEVAL

Evaluation of a Fire Radiative Power Product derived from Meteosat 8/9 and Identification of Operational User Needs

Final Report

EUMETSAT contract EUM/CO/06/4600000277/YG
Document issued 20 March 2008

Martin G. Schultz, Project Coordinator
Martin Wooster, Project Co-coordinator

Schriften des Forschungszentrums Jülich
Reihe Energie & Umwelt / Energy & Environment Band / Volume 23
ISSN 1866-1793 ISBN 978-3-89336-549-4

Bibliographic information published by the Deutsche Nationalbibliothek.
The Deutsche Nationalbibliothek lists this publication in the Deutsche
Nationalbibliografie; detailed bibliographic data are available in the
Internet at <http://dnb.d-nb.de>.

Publisher
and Distributor: Forschungszentrum Jülich GmbH
Zentralbibliothek, Verlag
D-52425 Jülich
phone: +49 2461 61-5368 · fax: +49 2461 61-6103
e-mail: zb-publikation@fz-juelich.de
Internet: <http://www.fz-juelich.de/zb>

Cover Design: Grafische Medien, Forschungszentrum Jülich GmbH

Title image: Savanna fire at Kruger National Park, South Africa.
Reprint with permission from
J. Goldammer, Global Fire Monitoring Center, Freiburg, Germany

Printer: Grafische Medien, Forschungszentrum Jülich GmbH

Copyright: Forschungszentrum Jülich 2008

Schriften des Forschungszentrums Jülich
Reihe Energie & Umwelt / Energy & Environment Band / Volume 23

ISSN 1866-1793
ISBN 978-3-89336-549-4

The complete volume is freely available on the Internet on the Jülicher Open Access Server
(JUWEL) at <http://www.fz-juelich.de/zb/juwel>

Neither this book nor any part may be reproduced or transmitted in any form or by any means,
electronic or mechanical, including photocopying, microfilming, and recording, or by any
information storage and retrieval system, without permission in writing from the publisher.

Project team:

Martin G. Schultz, FZ Jülich, Germany (coordinator)
Martin Wooster, King's College, London, UK (co-coordinator)

Olivier Boucher, Met. Office, Exeter, UK
Marie Doutriaux-Boucher, Met Office, Exeter, UK
Claire Granier, University Paris, France
Angelika Heil, FZ Jülich, Germany
Anthony Hollingsworth[†], ECMWF, Reading, UK
Johannes W. Kaiser, ECMWF, Reading, UK
Thomas Kasikowski, Met Office, Exeter, UK
Jean-Jacques Morcrette, ECMWF, Reading, UK
Gareth Roberts, King's College, London, UK
Adrian Simmons, ECMWF, Reading, UK
Guido van der Werf, Vrije Universiteit, Amsterdam, The Netherlands

External contributions from Mikhail Sofiev, FMI are highly appreciated.

[†] Dr. Anthony Hollingsworth sadly passed away on 29 July 2007.

Table of Contents

EXECUTIVE SUMMARY.....	5
1 FREEVAL OBJECTIVES AND PROJECT STRATEGY	7
1.1 OVERALL PROJECT OBJECTIVES.....	7
1.2 IDENTIFICATION OF POTENTIAL OPERATIONAL USERS.....	10
1.2.1 Chemical Weather Forecasting/Monitoring	10
1.2.2 Validation of Prognostic Fire Models and Visibility Forecasts	10
1.2.3 Public Information and Safety Aspects	11
1.2.4 Scientific Studies.....	12
1.3 BRIEF DESCRIPTION OF THE SEVIRI INSTRUMENT AND APPLICATION TO FIRE DETECTION AND FRP CHARACTERISATION	13
1.4 THEORY OF THE FRP ALGORITHM	15
1.5 FACTORS LIMITING FRP PRODUCT ACCURACY.....	18
1.6 VALIDATION STRATEGY	20
2 FRP REQUIREMENTS DEFINITION.....	22
3 VALIDATION DATASET DESCRIPTION	25
3.1.1 The MODIS MOD14 Data Set.....	25
3.1.2 Dataset Used to Investigate Algorithm Assumptions.....	26
3.1.3 Dataset Used to Investigate Per-Fire Comparisons	26
3.1.4 Dataset Used to Investigate Effects of Spatial Resolution	27
3.1.5 Dataset Used to Investigate Effect of SEVIRI Sensor Characteristics and Level 1 to 1.5 Pre-processing Operations	28
3.1.6 Datasets Used in Impact Studies.....	28
4 SPECIFIC VALIDATION METHODOLOGY	31
4.1 ALGORITHM PERFORMANCE ANALYSIS.....	31
4.2 SEVIRI PRODUCT PERFORMANCE ANALYSIS	32
4.2.1 Per-Fire Comparisons	32
4.2.2 Effect of Spatial Resolution - Area Based Comparisons.....	32
4.2.3 Analysis of Ecosystem-specific Biases	39
4.2.4 Effects of Viewing Geometry.....	40
4.2.5 Effects of Saturation.....	40
4.2.6 Effects of SEVIRI sensor characteristics and Level 1.0 to 1.5 pre-processing operations	40
4.3 LANDSAF PRODUCT VALIDATIONS	41
4.3.1 Comparison to KCL product.....	41
4.3.2 Comparison to MODIS.....	41
4.4 VALIDATION BASED ON IMPACT STUDIES	41
4.4.1 Impacts of Temporal Resolution	41
4.4.2 Impact of FRP versus Hot Spot Detection	42
4.4.3 Impact on Estimating Fire Emissions	43
4.4.4 End-to-end Use (Greek Fires Case Study).....	43
5 VALIDATION RESULTS.....	45
5.1 RESULTS OF THE ALGORITHM PERFORMANCE ANALYSIS.....	45
5.2 RESULTS OF THE SEVIRI PRODUCT PERFORMANCE ANALYSIS	54
5.2.1 Per-Fire Comparisons	54
5.2.2 Effect of Spatial Resolution – Area Based Comparisons	59
5.2.3 Analysis of Ecosystem-specific Biases	71
5.2.4 Effects of Viewing Geometry.....	72
5.2.5 Effects of Saturation.....	73
5.2.6 Effect of SEVIRI Processing Chain.....	74
5.3 RESULTS OF LAND SAF PRODUCT VALIDATIONS	81
5.3.1 Comparison to KCL product.....	81
5.3.2 Comparison to MODIS	82

FREEVAL Final Report

5.4	RESULTS OF VALIDATION BASED ON THE IMPACT STUDIES	85
5.4.1	<i>Impacts of Temporal Resolution - Study of Sensitivity to Temporal Resolution of Emissions:</i> <i>Global Carbon Dioxide Modelling of 2004</i>	85
5.4.2	<i>Impact of FRP versus Hot Spot Detection</i>	91
5.4.3	<i>Impact on Estimating Fire Emissions</i>	94
5.4.4	<i>End-to-end Use Case Study: Modelling the Greece Fire Plumes of August 2007</i>	96
6	CONCLUSIONS	103
6.1	PRODUCT VALIDATION SUMMARY	103
6.2	DEMONSTRATED USEFULNESS OF PRODUCT	104
6.3	DEFINITION OF ACCURACY REQUIREMENTS	105
6.4	RECOMMENDATIONS FOR FUTURE DEVELOPMENTS	106
6.4.1	<i>Short-term Recommendations</i>	106
6.4.2	<i>Mid-term Recommendations</i>	107
6.4.3	<i>Long-term Recommendations</i>	108
A 1	ABBREVIATIONS	110
A 2	REFERENCES	111
A 3	THE PROJECT CONSORTIUM	114
A 4	REPRINT OF J.W. KAISER, M. SUTTIE, J. FLEMMING, J.-J. MORCRETTE, O. BOUCHER AND M.G. SCHULTZ: GLOBAL REAL-TIME FIRE EMISSION ESTIMATES BASED ON SPACE-BORNE FIRE RADIATIVE POWER OBSERVATIONS, PROCEEDINGS OF THE INTERNATIONAL RADIATION SYMPOSIUM, SAN DIEGO, CA, USA, AUGUST 2008.	133

Executive Summary

The FREEVAL project answered EUMETSAT invitation to tender (ITT) No 06/794 Evaluation of a Fire Radiative Power Product derived from Meteosat-8/9 and Identification of Operational User Needs. The core work of this project was to evaluate the efficacy of a retrieval algorithm used to identify actively burning fires and estimate their fire radiative power from SEVIRI observations of fire-affected regions, and determine the effectiveness of the retrieved observations. This algorithm was developed by M. Wooster and his colleagues at King's College London (KCL), and had been selected by EUMETSAT for implementation prior to the start of FREEVAL. During FREEVAL, EUMETSAT implemented the algorithm in a prototype operational processing chain, aided by advice from KCL and with some algorithm changes being necessary in that environment. The assessment of algorithm retrieval accuracy covered several aspects and was tailored to provide sufficient information so that an operational readiness report (ORR) can be issued and the data product can be generated with full specifications.

The validation of the SEVIRI fire radiative power (FRP) product considered three main aspects:

- 1) theoretical performance of the FRP algorithm,
- 2) accuracy and performance limitations due to the SEVIRI instrument and to the level 1.5 data characteristics from which all SEVIRI geophysical products are currently derived,
- 3) performance of the specific FRP algorithm implementation at the Land Surface Analysis Satellite Applications Facility (Land-SAF).

Validation was performed through radiative transfer modelling, through product analysis and cross-comparison at the pixel, fire, and grid-cell (e.g. $1^\circ \times 1^\circ$) and regional basis, including comparisons with independent data products. In many cases, data from the EOS Terra and Aqua Moderate Resolution Imaging Spectroradiometer (MODIS) was used as the comparison dataset, since FRP can also be derived from the measurements of this sensor, but the analysis also included data from other sensors and platforms.

Due to the foreseen delay in substantial data products being available from the prototype operational processing chain implemented at EUMETSAT and the LandSAF, it was necessary to make use of different FRP dataset versions with largely similar but not identical characteristics during the FREEVAL study. Hence, much of the fundamental validation work was carried out with a full one year duration (Feb 2004 – Jan 2005) FRP dataset produced by running the first operational (non-commissioning phase) Meteosat-8 SEVIRI data through an improved version of the original fire detection and FRP algorithm developed at KCL in the Interactive Data Language environment (Wooster et al., 2003, 2005; Roberts et al., 2005, 2008). In parallel with this activity, a version of this improved algorithm was being implemented in C++ at EUMETSAT as the prototype processing chain, and was later ported to the Land SAF processing facility at the IM in Lisbon. Minor modifications were required to adjust the KCL code to the intricacies of the operational environment, and the details of this implementation are described in the algorithm theoretical basis document (Govaerts et al., 2007). Data from the Land SAF processing chain was made available later during the FREEVAL study, and the performance of this Land SAF product is here compared to that produced by the KCL processing chain. Some perturbations to performance are also expected due to unresolved differences between the calibration of the Meteosat-8 and

Meteosat-9 imaging radiometers, particularly at higher signals such as are obtained over fires in the 3.9 μm spectral band.

A second important aspect of the FREEVAL project was the identification of potential users of the FRP product and the specification of user needs, which were then gauged against the product characteristics. The main users, who were identified prior to the project and were actively engaged in FREEVAL with discussions and sensitivity modelling studies, were national and European weather centres (UK Met Office and ECMWF). These centres are developing a range of applications requiring knowledge of atmospheric composition and emissions, including those from open vegetation burning. They expressed a strong need for an accurate and rapidly available data product helping them to quantify trace compound emissions from fires with good spatial and temporal resolution. The conclusions of this report reflect the consortium's view as to how well the SEVIRI FRP product can match user requirements. We also provide some recommendations how future developments could further enhance the existing capabilities for global and regional earth observation and monitoring of emissions from such fires.

In summary, the FREEVAL project found that the SEVIRI FRP product offers great potential to improve current knowledge on the occurrence and strength of open vegetation burning in Africa and Southern Europe, and that it also provides some data relevant to fires in south America but at reduced usefulness due to the extreme scan angles and incomplete coverage when viewing that location. These FRP data will undoubtedly become an important component in operational applications aimed at monitoring atmospheric composition if the data are generated operationally (i.e. continuously) and with little time delay (i.e. in near realtime). Limitations of the product are mainly due to the SEVIRI sensor characteristics, thus reflecting the fact that this instrument had not been designed for fire detection or fire characterisation.

1 FREEVAL Objectives and Project Strategy

1.1 Overall Project Objectives

Open vegetation fires are an important disturbance agent of the terrestrial biosphere, and represent a ubiquitous, highly variable emission source for many key greenhouse gases, air pollutants, and aerosols. Even though natural fires (ignited by lightning or volcanoes) have occurred throughout Earth's vegetated history, today the vast majority are initiated by humans. Fire is commonly used for land clearance and management, pest control and soil fertilization. Fires are most frequent in tropical and subtropical regions, with Africa usually regarded the continent with the most wide-spread fire occurrence. Emissions from vegetation fires are increasingly recognized as an important parameter in atmospheric modeling, and their accurate description is a fundamental pre-requisite for the installation of operational services to monitor and predict atmospheric composition and the long-range transport of air pollutants, and for the monitoring of compliance with international treaties on greenhouse gas and air pollutant emission ceilings.

The observation of open fires from space has greatly advanced our understanding of the global dimension of this phenomenon and of the spatial and temporal patterns of fire occurrence. Nevertheless, it has proven very difficult to use the remote sensing of active fires or the mapping of burned areas for accurate, temporally and spatially consistent estimates of emissions from these fires, and to provide these data in timeframes useful for atmospheric forecasting. This has to do on the one hand with great uncertainties in the estimates of fuel load and combustion behaviour (which have typically been required to convert observations of active fires or burned area into emission fluxes), and on the other hand with the non-ideal nature of the available EO systems for this application (e.g. limited imaging frequency and inappropriate sensor characteristics). The lack of a near realtime data delivery of fire products from such systems has also hampered such efforts.

Fire observation has rarely been a primary mission objective for the design of satellite instruments. As a consequence, almost all sensors that can be used for fire detection and fire characterisation suffer from instrument saturation effects, relatively limited spatial and/or temporal resolution, and other limiting factors. Specifically, the temporal sampling from low earth orbit instruments is often inadequate for capturing the high temporal variability of fire occurrence and fire strength, and for fully resolving the fire diurnal cycle (which is known to be extreme in some areas). The data delivery of 'fire products' from such systems has in the main not been viewed as an 'operational' near-real time service, but rather a service to the science community, but the former is required if the data are to support timely applications such as those involving forecasting of trace gas/aerosol concentrations, air quality and visibility.

Active fire data provided by the SEVIRI instrument on board Meteosat 8/9 promised significant advancements in the current state-of-the-art of fire monitoring and emission quantification systems in two ways:

Firstly, its main observable, the Fire Radiative Power (FRP) of each detected active fire pixel, is expected to be directly related to the rate of combustion of biomass and thus the release of smoke emissions from the identified fires (Wooster et al., 2005). The FRP provides information on the measured radiant heat output of detected fires (in units of megawatts). Its integration over the lifetime of a fire, the fire radiative energy (FRE), should therefore be directly proportional to the accumulated emissions released by the fire. This has been verified

in a number of small-scale field experiments, but needs further proof on regional to continental scales. Quantifying emissions based on FRE eliminates the need to separately assess burned area, fuel loads, and combustion rates as is done currently in most emissions assessment methods, and therefore removes a whole series of uncertainties due to our often rather limited knowledge of these variables.

Secondly, since SEVIRI is employed on a geostationary platform, it can sample a large footprint with high (15 min) frequency, and can therefore deliver important information on the temporal variability of fires. A limitation is that the relatively coarse spatial resolution of the measurements (3 km sampling distance at the sub-satellite point) lowers the detection probability of the smaller/less intense fires, and such fires therefore remain unaccounted for (i.e. undetected) in the raw output product. By definition each such fire may each be releasing relatively small amounts of pollutants, but the total number of these smaller fires may make their cumulative emissions significant, and so statistical adjustment of the product to deal with this bias may be warranted.

The EUMETSAT ITT 06/794 requested bidding proposals to evaluate the information content of the FRP product generated from SEVIRI data via an assessment of its accuracy and usefulness for operational applications. The FREEVAL proposal (SEVIRI Fire Radiative Energy/Power Product Validation) was then selected and funded to accomplish the work described in this report. The consortium of the present proposal is formed of six organizations with expertise across the range of science areas required for effective response to this ITT and with the expertise in operational atmospheric forecasting and reanalysis systems that are anticipated as the primary application area to be supported by the FRP product. The consortium is led by Dr. Martin Schultz, who combines major expertise in global atmospheric modelling with expertise in fire emissions modelling and the co-ordination of complex research programmes. The team effort contains a sizeable contribution from the main developer of the FRP approach selected by EUMETSAT to be implemented for this product, Prof. Martin Wooster from King's College London (KCL), together with Dr Gareth Roberts (also of KCL) who designed and coded much of the original SEVIRI fire detection algorithm implemented at KCL and also selected for implementation by EUMETSAT. The other partners are well-known experts in various fields related to earth system modelling, satellite retrievals and emission monitoring. Several of the partners play an important role in the ongoing developments of Earth system monitoring services of the sort that could greatly benefit from an operational FRP product. For a description of the consortium including their CVs see Annex 3.

The scope of Land Surface Analysis Satellite Applications Facility (LSASAF or Land SAF <https://landsaf.meteo.pt/>) is to increase benefit from EUMETSAT Satellites (MSG and EPS) data related to a) land, b) land-atmosphere interactions and c) biospheric applications. The Land SAF system is part of the EUMETSAT ground segment of operational product generation which is taking place in Lisbon at IM. In particular, the Land SAF has been designated to process the SEVIRI FRP product if and when it will become operational. The FREEVAL project makes a major contribution to the Operation Readiness Report (ORR) for this product.

The objectives of the FREEVAL project were to:

- (i) evaluate the accuracy of the FRP-product, both in terms of the algorithm's theoretical ability and its actual performance assessed via comparisons between the FRP product and independent data sources,
- (ii) investigate, trigger and promote applications that could potentially utilize an operationally disseminated FRP product, e.g. monitoring and forecast systems, and evaluate the impact of utilizing the FRP product in these systems,
- (iii) make recommendations as to possible future improvements to be made to the FRP product to best meet the requirements of the optimum applications identified in (ii).

In order to realise these objectives, a series of different analyses had to be performed. The general strategy of the validation is explained in section 1.6. Detailed descriptions of the reference datasets, the validation methodology and validation results are provided in sections 3, 4 and 5, respectively. The validation efforts reported on here also include tests of the implementation of the SEVIRI FRP product for fire emissions and atmospheric transport modelling (case studies). The FREEVAL team provided substantial input to the product specifications of the FRP pixel and gridded products to be provided operationally by the Land SAF. In addition, the consortium contributed substantially to the FRP product user manual (PUM FRP).

The work in the FREEVAL project went significantly beyond the literal text of the ITT, because key potential operational users of the FRP product were actively engaged in the product testing. Operational requirements from a number of potential users were collected and evaluated. Case studies were conducted in the framework of prototype systems for operational 'real-time' Earth system monitoring and medium term forecasting which are currently being developed at the (UK) Met Office and by the European integrated project "Global and regional Earth-system Monitoring using Satellite and in-situ data" (GEMS) co-ordinated by the European Centre for Medium-range Weather Forecasts (ECMWF). Emission fields for atmospheric trace compounds were generated from the prototype FRP product, and dedicated global modelling studies were performed in order to test the impact of the product in comparison to those of existing fire emission inventories. These case studies included an assessment of the additional value of the frequent temporal sampling available from SEVIRI via its geostationary orbit. Independent validation of model results was achieved with *in-situ* and remote sensing observations of aerosol optical depths.

Finally, we make recommendations for how the FRP product can be improved in terms of (i) accuracy and error estimation, for example via corrections for identified biases (e.g. non-detection of smaller fires) and via provision of improved uncertainty estimates, and (ii) product characteristics relevant to operational ingestion and assimilation (e.g. data format, spatial and temporal integration period). We shall also list the consortium's view on the "optimum" characteristics for a fire-monitoring component in future earth observation systems designed to support such operational forecast applications.

1.2 Identification of Potential Operational Users

In the context of this project we define operational use predominantly as short-term “chemical weather” forecasts and reanalysis simulations of greenhouse gases, aerosols, and reactive gas-phase compounds, all of which are significantly affected by emissions to the atmosphere from open vegetation fires. In light of the ongoing urgent and high-profile development of such services, and given the relatively coarse spatial resolution of the SEVIRI FRP product, these seem certainly the most promising applications in the near future and our consortium included international experts in this field who are responsible for the European development of such services. Other potential applications could include early detection of new fires (for fire fighting and management purposes), the monitoring of land-use change by fire, and assessment of climate impacts on fire activity. FREEVAL established a list of potential applications and contacted a number of key potential users to inform them about the availability of an FRP product from SEVIRI and sample their specific requirements. An evaluation of the product with respect to these ‘secondary’ applications will require another dedicated study.

1.2.1 Chemical Weather Forecasting/Monitoring

Besides the large European efforts in the GEMS project, which includes global trace compound forecasts and analyses at ECMWF as well as a suite of regional-scale European air quality models, there are other similar activities in the United States (Navy Research Laboratories, Monterey, CA; NOAA), Canada (Environment Canada) and in Brazil (INPE-CPTEC). Principal investigators from these initiatives were contacted and expressed their interest in the SEVIRI FRP methodology and in the data product so produced. Due to the similar nature of these systems we expect that they will have very similar requirements as the GEMS system.

GEMS is expected to develop into the core service component of the GMES Atmospheric Service, and several project members already made a commitment to make use of the SEVIRI FRP product in their respective modelling efforts on greenhouse gases, reactive gases, aerosols and regional air quality, respectively. Some further development of the GEMS models is needed before the product can be used as a regular and primary input data set for fire emissions. These developments have been written into the work plan of the GEMS successor project Monitoring of Atmospheric Composition and Climate (MACC). Initial use of the near-real-time SEVIRI FRP product is envisioned for the summer of 2008.

1.2.2 Validation of Prognostic Fire Models and Visibility Forecasts

There are two potential applications of SEVIRI FRP data that were further explored during FREEVAL at the Met Office in Exeter, UK. Firstly, the FRP product can be extended to estimate CO₂ emission released by fires. This, in turn, can be compared to the output of on-line and off-line interactive fire models. Such a procedure allows a useful verification of current fire models. An example of such a comparison is shown in Figure 1.1.




Figure 1.1: Example of a comparison of the correlation of monthly burned area derived from the fire model Had_FIRE (using HadCM3 or ERA 40 climate data) with burned area derived from the GFED (Guido van der Werf et al. 2006) and from SEVIRI (FREEVAL).

A temporal resolution of 3 hours is sufficient for this purpose and would allow evaluation of the diurnal cycle of fire emissions, which is known to exhibit large variations in such areas as the African savannah. A spatial resolution of $1^{\circ} \times 1^{\circ}$ would match current GCM grid-size. In the case of such model modification/validation applications, there is no need to obtain FRP data in real or near-real time.

A further application of the FRP product lies with visibility forecasts. There is a small but increasing interest from various stakeholders in NRT forecast of atmospheric visibility in different regions of the world. The decrease in visibility associated with open fires requires an accurate source term for the emission of particulate matter from fires. The FRP product can be extended to provide estimates of particulate matter (PM) emissions, with emission factors depending on the type of ecosystem, and possibly the size of the fire. Temporal resolution of 1 to 3 hours and spatial resolution of about 10 km would be sufficient given the current resolution of models used for visibility forecasting at the regional scale.

In conclusion the FRP product will prove very useful at the Met Office as the importance of visibility forecasts and fire modelling grows. The operational provision of the FRP product is therefore strongly encouraged.

1.2.3 Public Information and Safety Aspects

South Africa operates a public fire information system reporting on the nightly weather forecast and on the web (<http://safnet.co.za/>). This is presently based mainly on MODIS active fire observations, though locally generated active fire detections from SEVIRI are available in addition, and the system could well benefit from the inclusion of operationally produced SEVIRI FRP data. Another application is the internal fire early warning system used by ESCOM (South African power company), which uses the locally-produced SEVIRI active fire information to determine when and where fires are burning close to electrical power lines. If they are deemed to pose a threat to power safety the line can be shut down before a 'flashover' (essentially a spark induced by the heated air and flames above a fire)

can occur. At the present time locally derived MODIS and SEVIRI active fire location data are used for this application, and discussions with ESCOM resulted in the quote that the SEVIRI data were actually the most useful for the purpose due to its capability to detect rapidly changing fires, and the possibility for near realtime data transmission. Whilst MODIS can detect smaller fires, its usefulness is limited by the far less frequent nature of the observations. The potential value of additional FRP information to this application was determined using SEVIRI-derived FRP data for 2004 for fires that were identified as being close (within 10 km on the SEVIRI observational grid) to a power line.

Figure 1.2 confirms that fires that resulted in flashovers have, on average, an FRP that is higher than those that do not, and that the difference is statistically significant. This implies that the operational provision of SEVIRI FRP data might lead to an improved warning system at ESCOM and potentially other electric power companies in Africa.




Figure 1.2: Differences in FRP for fires related to flashover events and those that pass within 10 km of the transmission line but which do not result in a flashover.

1.2.4 Scientific Studies

Several members of the atmospheric science community have expressed great interest in SEVIRI FRP data, because of its potential to improve accurate quantification of trace compound emissions from fires and to study fire behaviour and climatology in Africa and southern Europe. Through the combined use of multiple remote sensing products, a more accurate and reliable quantification of fire emissions should become possible. As stated previously, the presently employed method for estimating fire emissions as input to atmospheric modelling studies relies on knowledge of the pre-burn fuel load and the combustion completeness. The SEVIRI FRP product can provide an independent validation for this approach. Figure 1.3 shows an example of such a comparison, where the SEVIRI time-integrated FRP data of a series of fires located in southern African grasslands and woodlands has been converted to a measure of fuel consumption via the method of Wooster et al. (2005). This is then compared to the pre-burn available fuel estimates, which have been derived from the burn scar area (as measured by manual mapping from MODIS level 1b 250 m spatial resolution NIR spectral reflectance imagery) and time integrated estimates of net primary production (NPP) made over the area of each burn scar during the prior growing season. The NPP data were obtained from the “geosuccess” portal, and are derived from use of SPOT-VGT spectral reflectance measures and a light use efficiency plant growth model (www.geosuccess.net/geosuccess/relay.do?dispatch=NPP_info). The ratio of the actual estimated fuel consumption to the available fuel consumption provides an estimate of the

proportion of fuel combusted (i.e. the “combustion completeness”) for this particular land cover type and time of year. As can be seen from Figure 1.3, the estimate of combusted biomass derived from SEVIRI is correctly below the estimate of available biomass for all fires examined.




Figure 1.3: Estimates of SEVIRI FRP-derived biomass combustion as compared to the pre-burn fuel load for eighteen fires in southern African grasslands and woodlands. The latter was calculated from SPOT-VGT derived NPP data and burned area measures taken from MODIS. The ratio of the two provides and estimates of the proportion of available fuel combusted.

1.3 Brief description of the SEVIRI instrument and application to fire detection and FRP characterisation

The following paragraph is adapted from Schmid (1999):

The Spinning Enhanced Visible and Infrared Imager (SEVIRI) on the Meteosat Second Generation (MSG) geostationary satellites Meteosat-8 and 9 is a 50 cm diameter aperture, line by line scanning radiometer, which provides image data in four Visible and Near InfraRed (VNIR) channels and eight InfraRed (IR) channels. The VNIR channels include the High-Resolution Visible (HRV) channel, which contains 9 broadband detection elements to scan the Earth with a 1 km sampling distance at SSP. All the other channels (including the IR channels) are designed with 3 narrow band detection elements per channel, to scan the Earth with a 3 km sampling distance. The full Earth disc image is obtained after 1250 scan line steps (south – north direction) of 9 km SSP per line step. The satellite spin of 100 rpm allows to complete (east – west direction) a full image in about 12.5 min. A flip-flop mechanism is activated to put the on-board black body in the optical path for the instrument calibration. The black body is removed after about 2 seconds from the calibration position. After that, the scan mirror moves back to its initial position. The Earth observation is resumed (after retrace during ~2 min) leading to an overall repeat cycle of maximum 15 minutes.

The instrument functional architecture is based on four main assemblies:

- the Telescope and Scan Assembly (TSA) including the Calibration Unit and the Refocusing Mechanism,
- the Focal Plane & Cooler Assembly (FPCA),
- the Electrical Unit Assembly (EUA) consisting of the Functional Control Unit (FCU),
- the Detection Electronics (DE) including the Main Detection Unit (MDU), the Preamplifier Unit (PU) and the Detectors.

The SEVIRI channels that are most relevant for fire detection and determination of FRP are:

- IR3.9 (nominal central wavelength at 3.92 μm , nominal spectral band 3.48-4.36 μm)
- IR10.8 (nominal central wavelength at 10.8 μm , nominal spectral band 9.8-11.8 μm)

Other spectral channels are used in the cloud detection process (since cloudy pixels are screened out prior to application of the fire detection algorithm), and in the procedures used to reject “false alarms” such as those due to the occurrence of sun-glint (specular-reflectance). The procedure used to generate the SEVIRI FRP product can be considered to consist of the following key stages:

- masking out of pixels unsuitable for further analysis [i.e. cloud-contaminated pixels, large areas of open water].
- detection of potential fire pixels [i.e. pixels whose spectral characteristics identify them as potentially containing actively burning fires].
- identification of true fire pixels [i.e. filtering of the potential fire pixel set using a series of spectral, spatial and contextural thresholding tests to leave only those pixels confirmed as containing actively burning fires].
- calculation of the fire radiative power for each true fire pixel.

The initial implementation of the geostationary fire detection algorithm was made at King’s College London using commissioning phase SEVIRI data, and was coded in the Interactive Data Language (IDL) environment (Roberts et al., 2005). At the start of the FREEVAL activity this algorithm was in the process of being significantly improved, and it is this improved implementation that forms the basis of the approach to be used in the proposed operational production of FRP data from SEVIRI, as outlined in the FRP Product Algorithm Theoretical Basis Document (Govaerts et al., 2007). Details of this fire detection algorithm are provided there in full, and are also included in a forthcoming paper (Roberts and Wooster, 2008) and so will not be repeated here.

After the fire detection process, each pixel has its FRP estimated, as a function of the pixels MIR spectral radiance increase above the background non-fire signal. The theory behind this approach to FRP estimation can be found in Wooster et al. (2003; 2005), and Section 1.4 of this document.

At the start of FREEVAL a prototype FRP product operational processing chain was being implemented at EUMETSAT in C++, using the KCL IDL code as the basis but with minor

modifications to deal with the operational environment. The details of this implementation are fully described in Govaerts et al. (2007), and this is the code that is intended to run at the LandSAF processing facility at the IM in Lisbon and which will generate the operational FRP product. However, since at the start of FREEVAL products from this processing chain were unavailable, it was necessary to make use of FRP datasets from the KCL processing chain in many of the components of the study. Hence, much of the fundamental validation work described herein was carried out with dataset covering a full one-year duration (Feb 2004 – Jan 2005) that was produced at KCL by running the first year of operational (non-commissioning phase) Meteosat-8 SEVIRI data through the available IDL-coded processing chain. This product is here referred to as the *KCL FRP dataset*, and is supplemented by Meteosat-9 derived FRP data from July and August 2007 produced by the same system. Data from the EUMETSAT/LandSAF processing chain was made available later during the FREEVAL study, produced solely from Meteosat-9 SEVIRI data of 2007, and the performance of this *LandSAF FRP* product is here compared to that produced by the KCL processing chain to ensure that it has similar product accuracy characteristics. Some perturbations to performance are expected due to the aforementioned (small) differences in the KCL and EUMETSAT/LandSAF processing chains, and due to unresolved differences between the calibration of the Meteosat-8 and Meteosat-9 imaging radiometers, particularly at higher signals such as are obtained over fires in the MIR channel (Lattanzio and Govaerts, 2006).

1.4 Theory of the FRP algorithm

The MIR radiance method of FRP estimation was first presented in Wooster et al. (2003) and is based on simple approximations to the physical laws governing the emission of thermal radiation from fires. The MIR radiance method exhibits two potential advantages over dual-wavelength methods such as those originally presented in Dozier (1981). Firstly it relies only on quantification of the fire pixel in a single spectral channel, removing problems related to interchannel spatial mis-registration that potentially impact such dual spectral band approaches (Shephard and Kennelly, 2003), and secondly it relies only on quantification of the fire signal in the MIR spectral band only, where spectral radiative emission from wildfires is maximised and thus where the signal increase of the fire pixel over the ambient background window signal is at its greatest (i.e. the S/N is optimised). For these reasons, the method used to derive FRP in the official MODIS fire products also uses measurements in the MIR spectral band (Kaufman *et al.*, 1998a), though in that case expressed in terms of brightness temperatures rather than radiances. The MIR radiance method of FRP derivation is defined by:

$$FRP_{MIR} = \left(\frac{\sigma \varepsilon_f}{a \varepsilon_{f,MIR}} \right) L_{f,MIR} \quad [Wm^{-2}]$$

Equation 1.1

where σ is the Stefan-Boltzmann constant ($5.67 \times 10^{-8} \text{ W m}^{-2} \text{ K}^{-4}$), ε_f is the emissivity of the fire over all wavelengths, and $\varepsilon_{f,MIR}$ is the emissivity over the MIR spectral band. In the

absence of data to the contrary gray body behaviours is assumed ($\varepsilon_f = \varepsilon_{f,MIR}$), and this is understood to be a realistic approximation for vegetation fires (Langaas, 1995)

a ($\text{W m}^{-2} \text{sr}^{-1} \mu\text{m}^{-1} \text{K}^{-4}$) is a constant determined from the empirical best-fit relationship between the fourth power of the blackbody emitter temperature, T and the emitted spectral radiance, $B(\lambda_{MIR}, T)$, in the MIR spectral band [i.e. $B(\lambda_{MIR}, T) = aT^4$], made over the range of emitter temperatures appropriate to actively burning fires. Since the Stefan-Boltzman Law states that the true fire radiative power emitted over all wavelengths is also a function of the fourth power of the emitter temperature, then the FRP can be estimated as a linear function of the fires MIR emitted spectral radiance, as expressed in Equation 1.1.

In Equation 1.1, $L_{f,MIR}$ ($\text{Wm}^{-2} \text{sr}^{-1} \mu\text{m}^{-1}$) represents the MIR spectral radiance emittance of the fire. However, under the circumstances pertaining to the observation of sub-pixel sized fires by a system such as SEVIRI, the fire is not fully resolved by the imaging system and the at-sensor received signal L_{MIR} is in fact the summation the following terms; emitted fire thermal radiance, solar and atmospheric downwelling irradiance reflected from the fire, emitted thermal radiance from the non-fire background, solar and atmospheric downwelling irradiance reflected from the non-fire background, and upwelling atmospheric thermal radiation:

$$\begin{aligned} L_{MIR} = & \tau_{MIR} p_f \varepsilon_{f,MIR} B(\lambda_{MIR}, T_f) + \tau_{MIR} p_f (1 - \varepsilon_{f,MIR}) (\tau_{d,MIR} I_{sun,MIR} \cos \phi + I_{atm,MIR}) / \pi \\ & + \tau_{MIR} (1 - p_f) \varepsilon_{b,MIR} B(\lambda_{MIR}, T_b) + \tau_{MIR} (1 - p_f) (1 - \varepsilon_{b,MIR}) (\tau_{d,MIR} I_{sun,MIR} \cos \phi + I_{atm,MIR}) / \pi \\ & + L_{atm,MIR} \end{aligned}$$

Equation 1.2

where τ_{MIR} is the upward atmospheric transmission in the sensors MIR spectral band, ϕ is the solar zenith angle, $\tau_{d,MIR}$ is the downward atmospheric transmission in the sensors MIR spectral band at angle ϕ , $I_{sun,MIR}$ is the extraterrestrial solar irradiance in the sensors MIR spectral band, $I_{atm,MIR}$ is the diffuse downwelling atmospheric irradiance in the MIR spectral band, and $L_{atm,MIR}$ is the upwelling atmospheric spectral radiance in the MIR spectral band, the other symbols (T , ε , p) have their previously defined meanings, with subscript f corresponding to their value at the fire and b at the non-fire background.

Similarly for a neighbouring non-fire ‘background’ pixel:

$$L_{b,MIR} = \tau_{MIR} \varepsilon_{b,MIR} B(\lambda_{MIR}, T_b) + \tau_{MIR} (1 - \varepsilon_{b,MIR}) (\tau_{d,MIR} I_{sun,MIR} \cos \phi + I_{atm,MIR}) / \pi + L_{atm,MIR}$$

Equation 1.3

The fire emitted spectral radiance in the MIR spectral band, $L_{f,MIR}$, required for input into Equation 1.1 is in fact the $p_f \varepsilon_{f,MIR} B(\lambda_{MIR}, T_f)$ term on the right hand side of Equation 1.2, and its value can be obtained numerically by combining Equation 1.2 and Equation 1.3:

$$\begin{aligned} L_{MIR} = & \tau_{MIR} p_f \varepsilon_{f,MIR} B(\lambda_{MIR}, T_f) + L_{atm,MIR} + (1 - p_f) (L_{b,MIR} - L_{atm,MIR}) \\ & + \tau_{MIR} p_f (1 - \varepsilon_{f,MIR}) (\tau_{d,MIR} I_{sun,MIR} \cos \phi + I_{atm,MIR}) / \pi \end{aligned}$$

Equation 1.4

and re-arranging:

$$p_f \varepsilon_{MIR} B(\lambda_{MIR}, T_f) = \frac{1}{\tau_{MIR}} \left(L_{MIR} - (1 - p_f) L_{b,MIR} + p_f L_{atm,MIR} \right) - p_f (1 - \varepsilon_f) (\tau_{d,MIR} I_{sun,MIR} \cos \phi + I_{atm,MIR}) / \pi$$

Equation 1.5

Equation 1.5 represents the true value of $p_f \varepsilon_{MIR} B(\lambda_{MIR}, T_f)$ for use as $L_{f,MIR}$ in Equation 1.1. Multiplying the output of Equation 1.1 by the sensor pixel area then provides an estimate of the fire radiative power in Watts (generally expressed in MW due to the large fire radiative power values observed from open wildfires), based only on the MIR spectral signal.

However, certain of the parameters in Equation 1.5 cannot be determined, for example the fire fractional area, p_f , whilst others, for example the atmospheric parameters are likely to be imperfectly known. By neglecting the (relatively) unimportant terms, Equation 1.5 can be greatly simplified and then parameterised using even coarse resolution satellite data, in order to provide an estimate of $L_{f,MIR}$ for input into Equation 1.1.

The first assumption is that the atmospheric term $p_f L_{atm,MIR}$ on the right hand side of Equation 1.5 will always be small compared to at least one of the first two terms and is therefore negligible. Next, the requirement to know the fire fractional area is removed by assuming that $(1 - p_f) L_{b,MIR} \approx L_{b,MIR}$, which is considered workable when p_f is sufficiently small, and as p_f increases the error this assumption introduces is still negligible since in that case the spectral radiance of the fire pixel will be increasingly dominated by emittance from the (increasingly large) fire rather than from the much cooler ambient temperature background (since $B(\lambda_{MIR}, T_f)$ can be four orders of magnitude larger than $B(\lambda_{MIR}, T_b)$ at MIR wavelengths). The final term in Equation 1.5, corresponding to the solar and downwelling atmospheric radiation that are reflected from the fire, is assumed negligible for the same reason.

Via these simplifications the fire-emitted spectral radiance ($L_{f,MIR}$) for input into Equation 1.1 can be estimated from the difference between the MIR spectral radiance of the active fire pixel (L_{MIR}) and that of the surrounding non-fire ‘background’ ($L_{b,MIR}$) calculated as the mean signal of the ‘background window pixels, and adjusted for the MIR atmospheric transmission:

$$L_{f,MIR} = p_f \varepsilon_{f,MIR} B(\lambda_{MIR}, T_f) = \frac{1}{\tau_{MIR}} (L_{MIR} - L_{b,MIR})$$

Equation 1.6

The impact of the assumptions made during the derivation and application of the above equation used to estimate $L_{f,MIR}$, the assumptions made during the derivation of Equation 1.1, will control the theoretical accuracy of the FRP algorithm.

1.5 Factors Limiting FRP Product Accuracy

Although SEVIRI has been designed for operational weather forecasting and not specifically for fire detection, its MIR channel (thermal band centred at $3.9\ \mu\text{m}$) shows great potential for fire detection and the measurement of fire radiative power (FRP) using Equation 1.1 and Equation 1.5, as demonstrated in Figure 1.4. However, the MIR channel of the SEVIRI sensor has a saturation level of $\sim 335\ \text{K}$, and as a result a certain proportion of the particularly large and/or high intensity fires are expected to cause saturation of the measurements in this spectral band. Whilst this will not impact detection of such fire pixels (indeed their large signal will very likely make them amongst the most detectable such events), it will lead to an impact on the accuracy of the FRP measurements of such fires since their MIR spectral radiance will be underestimated.

A further factor influencing FRP product accuracy is the relatively coarse spatial resolution of the SEVIRI MIR channel, which also varies with viewing geometry. The sub-satellite pixel size is $4.8 \times 4.8\ \text{km}^2$ (FWHM), and these $23\ \text{km}^2$ pixels are oversampled by a factor 1.6 in the x and y directions leading to a sub-satellite pixel sampling distance of $3 \times 3\ \text{km}^2$. Pixels close to the disk edge (for example those over Madagascar and South America) reach areas of $\sim 90\ \text{km}^2$. The relatively large pixel size limits the detectability of small/low intensity fires having a low FRP, and may lead to a misinterpretation of fire clusters as individual large fire events. The increasing pixel size away from the sub-satellite point is expected to increase the significance of these events relative to smaller fires.

Finally, the on-board processing of SEVIRI data and its conversion to the level 1.5 radiance product from which all geophysical datasets including the FRP product are derived (termed here the level 1 to level 1.5 processing) introduces perturbations to the measurements made in each spectral band. This will include the introduction of interpolation errors due to the geolocation and projection onto the nominal geostationary projection centered at $(0^\circ; 0^\circ)$ (see EUMETSAT Technical Document EUM/MSG/ICD/105, 2007).




Figure 1.4: Imagery of southern Africa on 4 September 2003, in which numerous active fires are burning. (a)-(d) are derived from SEVIRI data covering a 1200 km wide region, collected at 12:12 UTC. (a) 3.9 μm , (b) 10.8 μm , (c) 3.9 μm - 10.8 μm brightness temperature difference, and (d) mask of confirmed active fire pixels. (e) and (f) show, respectively, a SEVIRI and MODIS MIR image subset centred on the Okavango delta region of Botswana, captured at 11:57 UTC and 12:05 UTC respectively.

1.6 Validation Strategy

Considering the potential aspects theoretically limiting the accuracy and performance of the SEVIRI FRP algorithm and outlined in sections 1.4 and 1.5, and the availability of FRP products produced via the KCL and EUMETSAT/LandSAF data processing chains, the strategy adopted to validate the SEVIRI FRP product was to individually assess the following aspects:

- (1) the theoretical and actual performance of the SEVIRI fire detection and FRP algorithm; assessed using model simulations and analysis of the KCL FRP product and matching MODIS-derived FRP data.
- (2) the accuracy and performance limitations introduced due to the SEVIRI instrument characteristics and level 1.0 to 1.5 data pre processing procedures; assessed using model simulations and analysis of matching SEVIRI level 1.0 and 1.5 data and data from SEVIRI 'special' mode operations
- (3) the performance of the specific algorithm implementation at the Land Surface Analysis Satellite Applications Facility [Land-SAF]; assessed using the LandSAF FRP product and comparisons to the KCL FRP product and to matching MODIS-derived FRP data.

The validation strategy approach comprises both theoretical modelling, including simulations of the spectral energy emissions of fires of different sizes/temperatures and calculations of the atmospheric effects on such signals with the MODTRAN radiative transfer code (Berk et al., 1999), and comparisons to independent observations of the same parameter (i.e. per-fire FRP and per-area FRP) made with the MODIS sensor onboard the polar-orbiting EOS Terra and Aqua satellites. The data sets used in these comparisons are described in section 3.

Under (1) the underlying assumptions of the FRP algorithm are considered via an analysis of the numerical approximations made during its derivation, and the main error sources impacting the product are considered. In addition, a sensitivity analysis was performed including the effect of SEVIRI MIR channel saturation and background thermal 'clutter' (referring to the fact that the background temperature signal upon which the fire signal is superimposed is unlikely to be uniform).

Findings from the simulation are compared to the actual retrieved range of fire characteristics present in the FRP data to determine the consistency of the product in relation to the theoretical performance and determine whether the current error estimations are appropriate. The impact of the SEVIRI 3.9 μm channel saturation was considered in terms of the percentage of observations where saturation has an impact, and its temporal distribution.

The products' error of fire detection omission, commission and FRP accuracy is assessed via comparison of the KCL FRP product to near simultaneous MODIS observations (both at a per-fire level, as well as over fixed grid-cells and regions of the MODIS swath for regional-scale comparisons). This analysis includes an assessment of the fire detection capabilities of SEVIRI in various vegetation cover classes. MODIS was selected as the reference data set because of its relatively finer spatial resolution (1 km at the sub satellite point) and its sufficient data coverage (up to 4-times daily observations over Africa). Daytime and nighttime MODIS to SEVIRI FRP comparisons have been conducted, across the fire-affected regions of the SEVIRI disk. Furthermore, derivative secondary datasets, which are themselves derived from observations made by MODIS are also used. One of these is the

Global Fire Emissions Database (GFED) (van der Werf et al. 2006), whose fire emissions calculations are based upon the previously mentioned burned area $\times$ fuel load $\times$ combustion completeness relationship. In version 2 of the GFED database, burned area is actually calibrated from cumulative counts of MODIS hotspots (i.e. active fire detections) and a previously derived relationship between this variable and actual area burned in the causal fire (van der Werf et al. 2006).

Under (2) the impact of the observational and data pre-processing procedures used to generate the SEVIRI level 1.5 data product, which is the input to all versions of the FRP processing chain, was assessed via simulation modelling of the SEVIRI observations process when viewing active fires, by comparisons of level 1.0 and 1.5 data recorded under standard conditions, and via analysis of co-incident Meteosat 8 and 9 SEVIRI data when the Meteosat 8 instrument was operated in a number of non-standard modes (including a low gain mode to reduce or negate the influence of sensor saturation).

Under (3), the fire detection and FRP product output from the recently implemented LandSAF data processing chain were validated. This chain will ultimately be used to produce the operational SEVIRI FRP product foreseen to be produced from mid-2008 onwards (see <http://landsaf.meteo.pt/algorithms.jsp?seltab=8>). The aim of the LandSAF product validation is to demonstrate that the LandSAF operational products have the same or similar accuracy to those produced by the original IDL code used at KCL. Since the EUMETSAT-derived C++ code operating at the LandSAF is essentially an implementation of the original KCL algorithm written in IDL, with some small modifications necessary for its implementation in an operational environment, it should be expected that the performance of the two products is similar.

Finally, the content, efficacy and value of the spatio-temporal patterns and magnitude of burning provided by the information contained within the SEVIRI FRP product have been assessed via an 'impact analysis' study. This was undertaken via inclusion of the data product as an emissions source term in a series of specific impact studies, with comparison of the results to those found when using alternative fuel consumption databases (e.g. GFED version 2, van der Werf et al., 2006) as the source term. In these impact studies, the results of atmospheric modelling applications using SEVIRI FRP information to estimate fire emission fluxes were evaluated with independent data sources measuring the atmospheric composition and its changes due to vegetation fires. The strategic approach comprises the following steps: The FRP product from the KCL chain was formatted and distributed to the users ECMWF and Met Office. Emission factors were used to convert the FRP data to emissions estimates. Due to the need for global emission data sets, SEVIRI FRP derived emissions were superimposed on an existing global data set based on MODIS fire counts (GFEDv2). Model runs with and without blending of the FRP-derived emissions, were conducted in order to assess the adjustments to the model outputs provided by the FRP products inclusion. Comparisons to *in situ* and/or remotely sensed observations of atmospheric constituents (mainly aerosols) perturbed by major biomass burning events allowed for an assessment of the impact of the FRP data product on the model results. Consideration was given to whether adjustments to the FRP product spatio-temporal characteristics or error specifications are required to provide an optimum emissions data source for ingestion into these currently operating simulation models.

2 FRP Requirements Definition

The requirements of operational and scientific users viz the FRP product can be categorized as follows:

- accuracy: what are the acceptable errors of omission and commission and what is the required accuracy of the derived FRP?
- resolution: is the relatively coarse spatial resolution of the SEVIRI MIR channel adequate for fire detection?
- measurement frequency: is the time interval of 15 minutes between SEVIRI scenes adequate to capture fire variability?
- data delivery and formats: how fast do users need the data and in which format should the data be provided?

Active fire products are by necessity subject to errors of omission and commission since at their heart is an anomaly detection procedure working on thresholding of image radiance and brightness temperature signals (Figure 1.4). This anomaly detection procedure will not successfully capture all pixels containing active fires, and will indeed very likely report some pixels where the supposed ‘anomaly’ is not caused by fire. Generally speaking, if an active fire product is made less sensitive in order to reduce false alarms (i.e. errors of commission) then its errors of omission will very likely increase, so there is a balance to be struck. Giglio et al. (2003b) report the errors of commission of the widely used TRMM VIRS active fire product as, on average, $\sim 10\%$ for a spatial resolution that provides 4 km^2 pixels at nadir. The fire detection false alarm rate present in the SEVIRI FRP product should ideally be no higher than this, but the errors of omission are expected to be larger than for TRMM VIRS due to SEVIRI’s lower spatial resolution. It is difficult to formulate precise requirements for omission and commission errors, because the impact of such errors will depend on the application and its degree of aggregation and processing of the individual SEVIRI slot-level data products, and because the product errors are not independent of each other and one needs to find a balance between these errors so as to maximize the product usefulness. As a general rule, the level of fire detection omission for SEVIRI should be such that the fire pixels that it does successfully detect are responsible for the majority (i.e. $> 50\%$) of the FRP actually being emitted at the time of observation (this can be verified via simultaneous use of a higher spatial resolution sensor, such as MODIS). Furthermore, the size spectrum of detected fires should ideally be unbiased (beyond a set lower FRP threshold) such that extrapolation of frequency – magnitude relations (Roberts et al., 2003) can in theory be applied to estimate the frequency of ‘missing’ (undetected) low FRP fire pixels that are below the detection threshold.

In terms of the accuracy of the FRP observations made for the detected fire pixels, it is worth considering the theoretical optimum performance that can be achieved. The relatively high spatial resolution (370 m) BIRD sensor, that was designed specifically for active fire observations, and which was used by Wooster et al (2003) in the derivation of the MIR FRP algorithm, is reportedly able to measure the FRP of around 75% of detected active fire pixels to within $\pm 30\%$, assuming perfect knowledge of the atmospheric transmissivity (Zhuckov et al., 2005). It can be expected that SEVIRI with its coarser resolution and lower saturation temperature will yield somewhat larger errors than this. Since the accuracy is largely limited by the measurement of the background radiance that has to be determined from neighbouring pixels, it contains a random error term, which will decrease in relative magnitude when several fires are aggregated as in a gridded FRP product. Furthermore, as noted above, there

are ways to improve estimates of total FRP within a grid cell if a correction for small fires escaping detection is applied (e.g. based on extrapolation of frequency magnitude statistics).

Finally, for the purpose of estimating combustion totals from SEVIRI data, one needs to consider that these are to be estimated as the time-integrated values of FRP, which will tend to reduce the impact of random error on each individual FRP observation. Specifically, it should be recognised that many applications are focused not on the use of per-slot FRP measures of individual fires or fire pixels, but on spatial and temporal aggregations of such measures so as to derive estimates of the overall amount of a chemical species emitted over a particular area and time (e.g. a 1 degree resolution spatial grid, over a 1 hr period) and as such the influence of random errors in FRP characterisation will be reduced in these applications via this spatial and temporal aggregation.

The spatial resolution requirements of the FRP product can be summarized as follows: for early detection and fire warning systems, it must be as high as possible – ideally, the fire position should be discernible within a few hundred metres. Nevertheless, even a coarser resolution product can be of use for these applications, in particular when it is delivered rapidly and with temporal sampling frequencies of less than 1 hour. Inclusion of fire data for emission estimates in global and regional modelling applications generally poses less stringent resolution requirements, although some regional models are run on grid scales of 5 km × 5 km or less.

Since fire characteristics are extremely variable, a high temporal sampling frequency is desirable, and it is clear that a geostationary platform offers great advantage in this respect. Due to the fact that in the past data with less than daily coverage has hardly been available, and even these data proved highly useful in the various applications of fire satellite observations, it may be premature to define strict thresholds for the temporal sampling frequency requirements. From the feedback we gathered from various users it certainly seems as if the 15-minute sampling frequency provided by SEVIRI is adequate, though for “emergency response” type applications the delay between the collection of the level 1.5 source data and receipt of the locational information on new actively burning fires should be kept to an absolute minimum.

Atmospheric composition forecasts and event warning applications require a timely delivery of fire data products, ideally within less than 15 minutes after sampling. Other applications, notably for model validation and carbon budget studies, have much less stringent or no specific timeliness requirements. It should be noted that there is presently hardly any fire data set covering Africa and Europe that is delivered operationally and in near realtime. Therefore, even if the 15-minute requirement cannot be strictly met, a regular near-realtime data product from SEVIRI would improve the status quo and would be welcomed by all users. Data formats don’t seem to be a major issue, but some users expressed wishes concerning the use of specific dissemination channels so that their access is guaranteed.

The following Table summarizes the temporal, spatial and accuracy requirements that were expressed by various user communities. Note that in particular the spatial resolution requirements refer to the resolution used in the various applications. Fire detection and derivation of FRP generally require data with finer resolution than what the applications will use.

User community	User requirement				
	temporal resolution	spatial resolution	timeliness	accuracy	Notes
GEMS ¹	15-60 min (3 hours)	25-50 km for global system, 5-50 km for regional air quality models	15-30 min after image acquisition (less than 6 hours)	25-50% error, aggregated within model grid box after correction for missing small fires	Access at ECMWF; includes reprocessing of past periods
CPTEC-INPE	1-2 hours (3 hours)	pixel - 50 km	30 min	as above	Access from Brazil; ftp access requested
Visibility forecast	1-3 hours	10 km	3-6h	<100% error	
Carbon budget study	daily integrals	1 deg	1 month	25-50% error, aggregated within model grid box after correction for missing small fires	Reprocessing of past SEVIRI observations
fire climate model development	3 hours	1degree	1 month	25-50% error, aggregated within model grid box after correction for missing small fires	Reprocessing of past SEVIRI observations
SA FIS	15 min	Pixel	asap (e.g. 15 min of end of slot)	Errors of omission and commission as low as possible, FRP uncritical	
Emergency response	15 min	Pixel	asap (e.g. 15 min of end of slot)	Errors of omission and commission as low as possible, FRP uncritical	

asap= as soon as possible

¹ this includes the GEMS follow-up project MACC and ultimately the GMES Atmospheric Service
Table 2-1: User requirements for operational use of the SEVIRI FRP product. Unless otherwise stated, the requirements should be seen as target requirements. Where a range is given, the lower value represents the optimal value and the upper value the target requirement. In cases where a clear threshold requirement can be identified, this is listed in paranthesis.

3 Validation Dataset Description

The independent validation data came mainly from the MODIS active fire products, and specifically the fire detections recorded in the MOD14/MYD14 product (Justice et al., 2002; Giglio et al., 2003) collected by the MODIS sensors onboard the EOS Terra and Aqua satellites. Various study periods have been selected as described below. SEVIRI data was acquired from MSG-8 and MSG-9 and processed either at KCL, EUMETSAT or the Land SAF data processing centre. Radiative transfer modelling at KCL was performed using MODTRAN v4 (Berk et al., 1999). Other datasets used in the validation were the Global Land Cover Map 2000 (GLC2000; Mayaux *et al.*, 2004) to prescribe landcover type. Validation of emission estimates and performance analysis in impact studies was done using the the Global Fire Emission Database (GFED) version 2 and the prototype version 3 (van der Werf et al., 2006), and using the modelling systems at ECMWF (GEMS), the UK Met Office, and the Finnish Meteorological Institute (SILAM). The following sub sections describe these data sets in more detail and discuss some dataset features that are relevant for the SEVIRI FRP validation procedure.

3.1.1 The MODIS MOD14 Data Set

The MOD14 product is a level 2 data product for thermal anomalies/fire derived from the Moderate Resolution Imaging Spectroradiometer (MODIS) instruments on EOS-Terra and EOS-Aqua (Justice et al., 2002; Giglio et al., 2003). A dataset description can be found on <http://edcdaac.usgs.gov/modis/mod14.asp>. For our analysis we used ver4 of the MOD14 product, and the fire detection abilities of these data in southern Africa have been independently assessed by Morissette et al (2005) against high spatial resolution data from the 15 m – 90 m spatial resolution ASTER imaging radiometer which also flies on EOS Terra. Results from that study demonstrate the strong performance of the MODIS MOD14 fire detection algorithm, since when even when only relatively few 30 m spatial resolution ASTER-derived active fire pixels are present within the MODIS 1 km pixel recorded at the same moment, the MODIS active fire detection algorithm provides a high probability of detection [provided the ASTER fire pixels are distributed in a relatively spatially contiguous manner within the MODIS pixel, as measured here by Moran's I (Moran, 1950)]. When larger numbers of ASTER fire pixels are present within a MODIS pixel (e.g. > 100) the MOD14 product shows strong performance whatever the actual fire pixel spatial distribution at the scale of the ASTER observations.

The MOD14 product contains both a fire pixel mask, but also a near-complete record of the spectral characteristics of both the fire pixel and its neighbouring background pixels. It also contains an FRP record, though this is produced using a different algorithm to that implemented with SEVIRI and which takes no account of the spatially varying pixel size across the MODIS swath (in fact the MODIS algorithm reports FRP in units of W/m^2). For this reason, during the comparisons made herein, the FRP for each MODIS fire pixel detected by the MOD14 product was computed based on the same equation as for SEVIRI (Equation 1.1), as described in Wooster et al. (2005). Prior to comparisons to SEVIRI, the MODIS-derived FRP data were post-processed to remove the influence of duplicate fire detections in the original MOD14 mask due to the so-called MODIS 'bow-tie' effect that significantly affects far off-nadir views (see below explanation). The ability of MODIS to measure FRP to a set accuracy and precision has not yet been fully verified due to the difficulties of finding

an independent data source covering different land cover and fire regimes. However, testing against BIRD high spatial resolution FRP data derived on a per-fire basis for forest fires in Australia indicated, on average, that the MODIS FRP measure was within 25% of the near-contemporaneously recorded BIRD FRP measure (Wooster et al., 2003). The main reason for the differences were identified as (i) the fact that the MODIS fire detection algorithm failed to identify some parts of the individual fronts of each fire that BIRD successfully managed to detect by virtue of its higher spatial resolution, and (ii) the small time delay, of the order to minutes, between the MODIS and BIRD observations of each fire.




Figure 3.1: *Estimated detection probabilities of a 1 km MODIS active fire pixel, calculated as a function of the number of 30 m ASTER active fire pixels it contains, and the spatial distribution of those ASTER active fire pixels (as expressed by Moran's I). Taken from Morisette et al. (2005).*

3.1.2 Dataset Used to Investigate Algorithm Assumptions

Numerical simulations using calculations of the spectral radiant energy emissions resulting from bodies of different temperatures, and with atmospheric components of the signal calculated using MODTRAN v4, were used as the primary data to investigate the algorithm assumptions, following in part the methodology adopted previously by Wooster et al. (2005) but expanding this to provide an uncertainty estimate for each per-pixel FRP record. Additional data used to parameterise these numerical simulations consisted of radiances recorded in the SEVIRI level 1.5 data product, atmospheric transmissivity values calculated via radiative transfer modelling made at EUMETSAT, and example per-pixel FRP products processed with the KCL and Land SAF data processing chains.

3.1.3 Dataset Used to Investigate Per-Fire Comparisons

For the purpose of the per-fire intercomparisons, all the MODIS active fire pixel detections from over 800 individual MODIS active fire products were used. The data were MOD14 (EOS Terra) and MYD14 (EOS Aqua) Level 2 Active Fire Products (Giglio et al., 2003) covering Africa for the matching period of 2004-05 and were obtained through the EOS Data

Gateway at the Land Processes Distributed Active Archive Center (LP DAAC). This represents all the active fire pixel detections made by MODIS over Africa in February, May and August 2004, during which time continental-scale fire activity shifted southwards from Senegal and Ethiopia (February) to southern Africa (August). Matching SEVIRI data processed through the KCL data processing chain were selected as those taken within ± 6 minutes of the MODIS overpass, and all such matchups were used in the comparison process.

As mentioned above, prior to the inter-comparison, MOD14 fire detections were post-processed to remove the influence of the ‘bow-tie’ effect, an artifact of the MODIS design that results in off-nadir areas being imaged more than once in successive scans (Wolfe et al., 2002). Double-counted, off-nadir fire pixels were identified using their recorded latitudes and longitudes, and the duplicates removed. The FRP for each remaining fire pixel was then calculated using the MIR radiance method of Wooster et al. (2003), applying the MIR radiance method algorithm coefficients presented in Wooster et al. (2005) for use with MODIS data and taking account of the changing MODIS pixel area across the swath.

3.1.4 Dataset Used to Investigate Effects of Spatial Resolution

SEVIRI data obtained from EUMETSAT between February 1st, 2004 and January 31st, 2005 from MSG-8 were used to investigate this issue. With the exception of a few, spurious failures in data acquisition, all images of the full Earth disk at 15-minute temporal resolution were processed over this one-year period. As stated previously, the algorithm used was the KCL geostationary fire detection and characterisation algorithm defined in Robert and Wooster (2008). This algorithm forms the bases (with only minimal changes) of the operational FRP algorithm defined in the ATBD (Govaerts et al., 2007). Only the continent of Africa, including Madagascar, was processed since the algorithm has been optimised for this area, and the vast majority (> 95%) of the biomass burning covered by the imagery was located on the African continent. The active fire detection algorithm uses i.) a novel high spatial resolution cloud mask derived from thresholding of the HRV channel data to supplement the cloud processing scheme of the Meteorological Product Extraction Facility (MPEF) at EUMETSAT (Lutz et al 2003), ii.) a preliminary detection stage with liberal thresholds to identify the maximum number of potential fire pixels, iii.) multiple subsequent stages to minimize false detections due to large uniform areas of warm ground, and sun glint from water bodies or undetected clouds, iv.) a stage to reject potential fire pixels based upon their proximity to a cloud or water body, and v.) a stage to statistically compare the elevated thermal signal of a potential fire pixel relative to the surrounding background.

On average four MODIS swaths per day subtended some portion of the African continent, depending on the exact ground tracks of the polar orbiting, sun-synchronous AQUA and TERRA satellites that carry the MODIS instrument. The fire detections made by MODIS and contained within the aforementioned MOD14/MYD14 active fire products obtained for the same one year time period (February 1st, 2004 and January 31st, 2005) from the LP DAAC were used to identify fire pixels, and for each active fire pixel FRP was calculated via the MIR radiance method, taking account of the MODIS pixel area variation across the swath as described above and in Wooster et al. (2005).

3.1.5 Dataset Used to Investigate Effect of SEVIRI Sensor Characteristics and Level 1 to 1.5 Pre-processing Operations

A key dataset used here was that from a dedicated SEVIRI Fire Radiative Power (FRP) test (so-called SEVIRI ‘special operations mode’) conducted to collect data for an evaluation of the errors inherent in the FRP product due to the SEVIRI standard configuration. In order to do this the following configuration changes were made to Meteosat-8, and co-incident Meteosat-8 and 9 data collected over the duration of the test period (3- 7 September 2007):

- a. Change to SEVIRI Rapid Scan (5 minute temporal resolution) for a latitude range covering 0° to 30° S
- b. Change the digital filter coefficients to a top hat function instead of the standard finite impulse response filter
- c. Reduce the gain for the 3.9 μm channel to allow measurement up to pixel brightness temperatures of ~ 375 K without sensor saturation.

In addition to exploitation of the data from the above SEVIRI ‘special operations mode’ experiment, the dataset used for this study consisted of a small set of co-incident level 1.0 and 1.5 SEVIRI data obtained over Africa for large fires recorded by Meteosat-9, together with a BIRD Hotspot Recognition Sensor image of southern Africa recorded in 2003 and which contained a series of active fire observations that provided data from which model simulations were derived. Characteristics of the BIRD HSRS imager can be found in Wooster et al. (2003) and Zhuckov et al (2005), with the most relevant aspects to this study being the provision of non-saturated MIR channel data at fairly high spatial resolution (370 m pixel size) over even the most intensely burning fires.

3.1.6 Datasets Used in Impact Studies

3.1.6.1 Global Fire Emissions Database (GFED)

The SEVIRI-FRP derived fire emission estimates for Africa are compared to the published inventory of the Global Fire Emissions Database (GFED) version 2 (van der Werf et al., 2006). The GFED dataset was compiled using fire satellite data from different sources and the Carnegie-Ames-Stanford Approach (CASA) biogeochemical model. Burned area measures for 2001-2004 were derived from the aforementioned MOD14/MYD14 MODIS active fire (‘hot spot’) data which were calibrated using MODIS 500m burned area estimates for selected regions (Giglio et al., 2006). ATSR (Along Track Scanning Radiometer) and VIRS (Visible and Infrared Scanner) satellite data were used to extend the burned area time series back to 1997 based on simple linear regression between the time periods when both products overlapped (Arino et al., 1999; Giglio et al., 2003; Van der Werf et al., 2006). Fuel loads and net flux from terrestrial ecosystems were estimated as the balance between net primary production, heterotrophic respiration, and biomass burning, using time varying inputs of precipitation, temperature, solar radiation, and satellite-derived fractional absorbed photosynthetically active radiation.

The current version, GFED version 2, is freely available for download from <http://www.geo.vu.nl/users/gwerf/GFED/index.html>. The dataset consists of $1^\circ \times 1^\circ$ gridded monthly burned area, fuel loads, combustion completeness, and fire emissions (Carbon, carbon dioxide (CO_2), carbon monoxide (CO), methane (CH_4), non-methane hydrocarbons (NMHC), hydrogen (H_2), oxides of nitrogen (NO_x), nitrous oxide (N_2O), particulate matter smaller than $2.5 \mu\text{m}$ diameter ($\text{PM}_{2.5}$), total particulate matter (TPM), total carbon (TC),

organic carbon (OC), black carbon (BC)). Emission estimates for the 2001 – 2006 period are also available with an 8-day time step.

For the comparison with SEVIRI-based biomass burning estimates, data from the preliminary ver3 GFED database are also included, because processing newly available burned area data has revealed relatively large changes in Africa [with less burned area (compared to version 2) for northern Africa and more in southern Africa]. For the comparisons presented in section 5.4.3, the GFED version 2 emission estimates were therefore scaled with the ratio between burned area from version 2 and 3 in order to produce a prototype GFED ver3 emissions estimate. The final version 3 will include other important changes, so that the GFED ver3 emissions presented here should be considered a preliminary data set only.

3.1.6.2 Global GEMS model

The Global and regional Earth-system Monitoring using Satellite and in-situ data (GEMS) project is combining the manifold expertise in atmospheric composition research and numerical weather prediction of thirty-two European institutes to build a comprehensive monitoring and forecasting system for greenhouse gases, reactive gases, aerosol, and regional air quality (Hollingsworth et al., 2008). The project is funded by the European Commission as part of the Global Monitoring of Environment and Security (GMES) framework.

As part of the GEMS project, prognostic representations of aerosols and greenhouse gases are being developed in the ECMWF Integrated Forecast System (IFS), in both its analysis and forecast modules. An experimental version of the global forecast model now accounts for five tropospheric aerosol types (i.e. sea-salt, desert dust, organic matter, black carbon and a sulphate related variable), carbon dioxide and methane. The sources for all species are located at the surface. The species are advected and included explicitly in the vertical diffusion and mass-flux convection schemes. The greenhouse gases have sinks at the surface only, while the aerosols undergo sedimentation and dry and wet deposition by large-scale and convective precipitation (Morcrette et al., 2008). Feedbacks of the aerosol and greenhouse gas fields on other atmospheric variables are not included in the current model version. Biomass burning emits carbon dioxide, methane, organic matter, black carbon, and sulphate and some of its precursors. The global GEMS system currently accounts for these emissions using the aforementioned retrospective inventory GFED ver2, that has a temporal resolution of 8 days (van der Werf et al., 2006). However, this approach is only a temporary solution. In the operational phase, more and better fire observations need to be acquired in near realtime and assimilated to obtain accurate atmospheric composition estimates (Kaiser et al. 2006). For the impact studies described in this report (section 5.4.4) the SEVIRI FRP product was used to provide a greatly improved temporal resolution over the observed areas, and GFED ver2 provided the source terms outside of the SEVIRI-observed regions of Africa and Southern Europe. The latest information on the GEMS system can be found on the project home pages at http://www.ecmwf.int/research/EU_projects/GEMS/index.jsp.

3.1.6.3 SILAM Dispersion Model and Fire Assimilation System at FMI

The Finnish Meteorological Institute (FMI) is producing regional PM_{2.5} aerosol concentration forecasts with the SILAM dispersion model driven by emissions calculated with the FMI Fire Assimilation System (FAS). The FMI FAS is based on fire observation products over Northern Europe from the MODIS instrument. It uses the products of either temperature

anomaly (TA) [K] or fire radiative power (FRP) [W], both with a temporal resolution of one day. Calibration of both FAS versions was started from literature data, e.g. Ichoku and Kaufman (2005). Then the emission factors were fine-tuned using a model-based approach. Namely, FMI took a few fire cases, primarily in 2006, estimated their emissions of PM_{2.5}, ran the SILAM dispersion model and compared total column loads and near-surface concentrations with available observations. The systematic deviation was eliminated via adjustment of the emission factor. More information on SILAM can be found at <http://silam.fmi.fi>.

3.1.6.4 *MOPITT Atmospheric Carbon Monoxide Concentration Data*

Carbon Monoxide column concentrations, and vertical profiles, are provided by the Measurements of Pollution in the Troposphere (MOPITT) instrument on EOS Terra (http://terra.nasa.gov/About/MOPITT/about_mopitt.html). MOPITT is an 8-channel nadir infrared instrument with a 22 km pixel spatial resolution designed to detect trace gas signals of carbon monoxide (CO) and methane (CH₄) in the troposphere. Via the application of different weighting functions, CO vertical profiles can be retrieved for independent levels within the atmosphere.

For the impact study presented in section 5.4.3, MOPITT level 3 (ver 3) data derived via averaging the daily level 2 product into a global 1°×1° dataset and obtained from the NASA Langley DAAC (http://eosweb.larc.nasa.gov/PRODOCS/mopitt/table_mopitt.html) were used. The MOPITT level 3 data contain retrieved CO profiles for seven pressure levels, day / night total column CO concentration and various quality indicators. Following the filtering approach implemented by Hyer *et al.* (2007), the ‘percent *a priori*’ quality indicator is used to filter out retrievals which were composed of greater than 40% of *a priori* profile. In addition to this, only daytime cloud free (as determined from the MOPITT cloud mask) land pixels are used in the analysis.

4 Specific Validation Methodology

4.1 Algorithm Performance Analysis

As explained in Section 1.4, the following assumptions are made in the FRP algorithm derivation and application of the approach in the SEVIRI FRP product

- i. Over the temperature range relevant to active fires, Planck's radiation law is well approximated by a fourth order power law in the 3.4–4.2 μm interval (as implied in the derivation of the scaling factor a of Equation 1.1, shown in Section 1.4.).
- ii. The approximations made during the derivation of the equation to estimate the fires contribution to the fire pixels MIR spectral radiant emission (Equation 1.6) are valid.
- iii. The background MIR radiance signal of the fire pixel can be appropriately estimated from analysis of the neighbouring non-fire, non-cloudy pixel group. At present the mean spectra radiance of this pixel group is used.
- iv. The effects of aerosols and trace gases (beyond those in the ambient atmosphere) are not taken into account, and the atmospheric transmissivity assumed in the application of the algorithm is a reasonable estimate of the true atmospheric transmission in the 3.4 – 4.2 μm interval.

In addition, it is assumed that the fire (and background) thermal emission is isotropic and that the fire behaves as a grey body. These assumptions (or indeed, quite commonly the even more stringent assumption that the fire is a blackbody) are made in all existing applications deriving fire radiative power, and cannot be easily checked without detailed field experiments that have not been carried out. They will therefore not be addressed here.

The investigation of the theoretical FRP algorithm performance analysis was based around an analysis of these assumptions and a sensitivity study of the FRP algorithm. The effect of assumption (i) above (the fourth order power law approximation) was analysed by first comparing FRP derived using Equation 1.1 to that derived from the true Stefan Boltzmann Law. The effect assumption (ii) was investigated using a radiative transfer modelling study simulating the radiances measured over sub-pixel sized fires observed from space, and then using these within Equation 1.1 to estimate the fires FRP using the equations applied during the SEVIRI FRP processing chain. These estimates were then compared to the true fire FRP calculated using the Stefan Boltzmann Law. Finally, the impact of uncertainty in the background radiance field, and in the atmospheric parameters (assumptions iii and iv), was considered using a sensitivity study that perturbed these values prior to incorporation into within FRP algorithm. The appropriate range of atmospheric transmissivity in the 3.4 – 4.2 μm interval (that covered by the SEVIRI MIR spectral band) was taken from the ATBD (Govaerts et al., 2007) and from subsequent updates provided by EUMETSAT, and was assumed to vary over the range 0.61 – 0.7 [mid-range value of 0.66]. Expected uncertainties in the MIR background window pixel signal, and the difference between this and fire pixel background, were taken from SEVIRI level 1.5 data and LandSAF FRP products covering the southern African region.

4.2 SEVIRI Product Performance Analysis

4.2.1 Per-Fire Comparisons

Assessment at the scale of individual fires was performed via a comparison to the aforementioned MODIS active fire observations identified by the MOD14 and MYD14 MODIS level 2 fire products. MODIS is the sensor for which the measurement of fire radiative power was first proposed as a means of classifying a fire's emission source strength (Kaufman *et al.*, 1998).

The analysis was conducted at the scale of individual fires (i.e. clusters of separately identified fire pixels) using data from eight MODIS MOD14/MYD14 products (6 day and 2 night) from February and August 2004, together with fire detections extracted from the SEVIRI-derived KCL FRP dataset within 6 minutes of the MODIS acquisition time. The MIR radiance method algorithm (Equation 1.1) was used to derive the FRP measure of each fire pixel detected by the sensors. The approach followed that first used by Wooster *et al.* (2003) and Roberts *et al.* (2005), clustering groups of spatially contiguous fire pixels in the primary dataset into single 'fires' whose total FRP for that imaging slot was then derived, and using the latitude and longitude range of that fire pixel cluster (expanded by the equivalent of two SEVIRI pixels to account for any geo-locational offsets) to check for the presence of the same fire pixel cluster in the reference dataset.

In most cases a fire would be expected to be represented by more fire pixels in the MODIS dataset than in the SEVIRI dataset, due to the higher spatial resolution of the MODIS observations. Comparison of fire detections made by MODIS and SEVIRI allowed for an assessment of the errors of commission (false alarms) and omission (missed fires). When both datasets successfully recorded the presence of the same fire, the total FRP of the fire as recorded by both sensors was compared to assess the ability of SEVIRI to characterise the full FRP of each fire detected.

4.2.2 Effect of Spatial Resolution - Area Based Comparisons

SEVIRI has a nominal sampling distance at the sub-satellite point of 3 km, and a spatial resolution of 4.8 km, the values increasing with distance away from the sub-satellite point. This spatial resolution is relatively coarse compared to most other imaging radiometers currently used for active fire detection and characterisation, most notably the polar-orbiting MODIS sensor which as mentioned previously has a nominal 1 km × 1 km spatial resolution at the sub-satellite point (increasing to $\sim 2 \times 10$ km at the swath edge). Detectability of a fire within a cloud-free pixel depends primarily on the MIR spectral radiance signal increase of the 'fire pixel' above that of the surrounding (background) non-fire pixels and/or above the signal of the same pixel in another spectral channel less affected by the presence of sub-pixel fires (e.g. a longer wavelength TIR channel). These signal increases ultimately depend on (i) the fire's effective emitter temperature, and (ii) the effective proportion of the pixel covered by this elevated emitter temperature. These two properties also determine the fire's FRP through the Stefan-Boltzmann Law, and so for any particular fire detection algorithm criteria (e.g. a required MIR brightness temperature increase of the fire pixel above that of the ambient background) the corresponding minimum-detectable fire can be calculated in terms of its FRP.

Figure 4.1 shows this calculation for the SEVIRI sub-satellite point over a temperature range wider than that which is assumed valid for open vegetation fires ($\sim 650 - 1300$ K). It indicates that SEVIRI should be able to confidently detect actively burning fires whose FRP reaches a minimum of around 100 MW, and in certain cases maybe able to detect fires whose FRP is even lower than this, down to around 50 MW. Conversely, the calculation also suggests that SEVIRI will saturate over fire pixels whose FRP is greater than around 900-1000 MW.




Figure 4.1: Estimated FRP range detectable for various fire temperatures using SEVIRI at the sub-satellite point. Minimum detectable FRP is shown by the vertical line extending below the bar (fire pixel MIR brightness temperature raised 3 K above the background temperature). The lower limit of the black bar indicates the minimum detectable FRP when this threshold is raised to 6 K. The per-pixel FRP that saturates the sensor is shown by the upper limit of the black bar. FRP is calculated in each case by parameterising the Stefan-Boltzmann Law with the relevant fire temperature and area, and is relatively consistent across the assumed fire temperature range since these parameters are inversely related for a particular fire pixel brightness temperature. Calculations were performed using the MODTRAN radiative transfer code (Berk et al., 1999) and assume a mid-latitude summer atmosphere (rural aerosol, 23 km visibility), with a fixed surface reflectance (0.15) and emissivity (0.85) and a daytime solar zenith angle of 20° . Results differ between day and night due to differing assumed ambient background temperatures (day: 300 K, night: 285 K) and the lack of a solar reflected radiation contribution in the latter case.

The calculations presented in Figure 4.1 do not take into account any impact of the finite impulse response (FIR) filter applied in the production of the Level 1.5 SEVIRI data, nor the true SEVIRI pixel oversampling (by a factor 1.6) which is taken account of during the FRP algorithm application via a reduction in assumed SEVIRI pixel area by the appropriate oversampling factor in the x and y directions (Govaerts et al., 2007). Taking these factors into account would lead to minimum FRPs returned by the fire detection algorithm when applied to real SEVIRI Level 1.5 data of the order of ~ 40 MW (and at the extreme ~ 20 MW) at the sub-satellite point, whilst maximum retrieved FRP would be expected to be of the order of 400 MW. These values will increase linearly with pixel area away from the sub-satellite point, and Figure 4.1 indicates that FRP retrievals from real SEVIRI data shows a statistical distribution consistent with this modelling. In Figure 4.2, the small number of fires pixels

having FRP > 400 MW are the result of fire detections at pixels well away from the sub-satellite point, and thus which are able to record FRP values higher than is possible at that location.




Figure 4.2: Frequency-magnitude of per-pixel FRP derived from SEVIRI active fire detections, binned into 10 MW intervals. Data are all SEVIRI fire pixel detections made across Africa using the KCL algorithm over the periods February, May, and August 2004. Only SEVIRI images matching the MODIS overpass time and swath were used to produce this plot, since the same data are used later to compare to MODIS. The vertical dotted line indicates the 40-50 MW threshold, indicated by modelling as the approximate minimum fire FRP that can be confidently detected by SEVIRI. Here the frequency of fire pixels with an FRP lower than this is significantly reduced, and thus these data are in accordance with that prediction.

In contrast to SEVIRI, the much higher spatial resolution MODIS sensor can detect fire pixels whose FRP values are as low as 7 - 10 MW. From this analysis, it is very clear that SEVIRI will fail to detect some fire pixels that MODIS can detect.

Whilst such low FRP fire pixels are each themselves responsible for only a small amount of the total emitted FRP of an area, Figure 4.2 confirms that the statistical distribution of per-pixel FRP is skewed towards low FRP fire pixels. For this reason, the overall FRP underestimation resulting from SEVIRI's inability to detect the lowest FRP fire pixels can be substantial.

The degree of regional-scale underestimation inherent in the SEVIRI data products is, however, slightly more complex than can be gauged by simply applying a minimum FRP detection threshold to a set of MODIS-derived FRP data in order to determine which fires SEVIRI would detect and which it would not. This is because individual MODIS-detected fire pixels, that each may have a lower FRP than the SEVIRI FRP detection threshold, may still in fact have their FRP characterised by SEVIRI if they are arranged spatially such that a sufficient number of them contribute to the signal of one SEVIRI pixel (and thus result in a per-pixel FRP measure higher than the SEVIRI minimum FRP detection threshold). For this reason, the best way of gauging the impact of the effect of SEVIRI's lower spatial resolution on regionally aggregated FRP measures is to directly compare simultaneously-derived

MODIS and SEVIRI active fire detections and FRP retrievals, with the assumption that the MODIS-derived record represents the true representation of the regionally-aggregated FRP from all fires burning in the area.

It was expected that the degree of underestimation inherent in the SEVIRI-derived FRP measures might vary in space and time, due for example to changes in the FRP frequency-magnitude relationship over burning season (e.g. from early to late dry season). For this reason, the magnitude of the FRP underestimation inherent in the regional-scale SEVIRI-derived FRP measures was investigated spatially over the entire continent of Africa for the period Feb 2004 - Jan 2005, using the KCL derived FRP dataset and a matching MODIS-derived dataset extracted from the year-long MOD14/MYD14 archive of the same area. This investigation has particular relevance to the proposed production of a SEVIRI-derived FRP gridded product at 0.5 or 1.0 degree grid resolution and which is proposed to best represent the mean FRP emitted by all fires in each cell averaged over one hour intervals (Govaerts et al., 2007). In this dataset, the SEVIRI-derived FRP signals within each grid cell would ideally be adjusted to the value that MODIS would have seen had it been the observing instrument (remembering that the advantage of actually using SEVIRI rather than MODIS is that it provides data at a very much higher temporal resolution than MODIS, and which is in theory available in near-real time for use in the derivation of short- to medium-term atmospheric forecasts). For this reason, potential methods to adjust the proposed SEVIRI-derived FRP gridded product for the expected effects of FRP underestimation were also implemented, and their efficacy assessed via testing with an independent MODIS- and SEVIRI-derived FRP match up dataset collected in August 2007.

4.2.2.1 Basic Approach

Regional scale FRP comparisons were first conducted by comparing the cumulative (aggregated) within-scene FRP observed near simultaneously by SEVIRI and by MODIS over the area equivalent to the full MODIS swath and latitudinal image extent, together with visual examinations of the active fire pixel detections made across key-fire affected regions of Africa. This analysis used data from three separate months of 2004 where fires were predominately located in North Africa (February), Central Africa (May) and Southern Africa (August). As will be shown in section 5.2.2, this analysis established a substantial difference between the MODIS and SEVIRI area based FRP measures in all regions, and one that varied in time/space, and so confirmed the need for a more complete investigation covering the full year of continent-wide data.

This longer-term investigation again used a ‘validation dataset’ consisting of active fire detections made only with near-simultaneous SEVIRI and MODIS fire pixel and FRP observations collected over the same geographic extent. Fire pixels reported by the MOD14 and MYD13 MODIS products were temporally subset to within ± 6 minutes of a SEVIRI scan, and this time were also spatially subset to include only those detected within the center two-thirds of the MODIS swath, specifically between columns 225 and 1129, in order to reduce any effect introduced by the very large MODIS pixel areas that are found towards the edges of the MODIS swath. As previously mentioned, at these locations the MODIS “bowtie effect” (Wolfe, 2002) is known to (i) induce multiple, overlapping detections for a single fire occurrence, (ii) reduce the absolute number of detections at extreme view angles since an elevated thermal signal is required to overcome the increased ground sampling area, and (iii) as a consequence of (ii), produce fire pixels with mean FRP values significantly greater than those interior to the swath. Conversely, fire pixels detected by SEVIRI were temporally subset to only those within ± 6 minutes of a MODIS overpass, and also spatially subset to a

convex hull encompassing the MODIS-detected fire pixels within the centre 2/3rds of the MODIS swath. Given that SEVIRI is less responsive than MODIS to the lower FRP fire pixels that sometimes exist along a fires' perimeter, the potential number and intensity of SEVIRI fire pixels lying outside a convex hull of MODIS fire pixels was considered negligible.

If there were insufficient MODIS fire pixels to perform a convex hull operation (e.g., if there only existed one or two MODIS fire pixels in a scene) then a 2 km square buffer around the identified MODIS fire pixels was used instead of the convex hull. The procedure for subsetting all SEVIRI and MODIS data to concurrent and collocated fire pixels essentially imposed the temporal resolution and spatial coverage of MODIS onto the SEVIRI temporal cycle and spatial extent -- as is demonstrated in Figure 4.3. For brevity, this temporal and spatial subset of the combined SEVIRI and MODIS fire products across Africa in 2004/05 is hereafter referred to as the "training dataset."




Figure 4.3: Temporal profile of FRP measured by SEVIRI and MODIS over two consecutive days. The full SEVIRI dataset (—●—) contains fire pixels at continental coverage and 15-minute temporal resolution. Observations in the training dataset for SEVIRI (□) and MODIS (○) are composed of concurrent and collocated fire pixels within the center 2/3rds of a MODIS swath.

4.2.2.2 Detailed Sensor-to-Sensor Comparisons of Fire Activity Over the Annual Cycle

Sensor-to-sensor comparisons were performed by calculating the SEVIRI to MODIS ratios of both total fire pixel counts, ϕ_{count} , and total FRP, ϕ_{FRP} . Within the training dataset, the yearly ratios of total fire count and total FRP were calculated simply by summing the number of individual fire pixels and their respective FRP, then dividing the SEVIRI totals by the MODIS totals. This provided the base information of the extent to which SEVIRI underestimates fire pixel count and FRP with respect to MODIS, and how this varies seasonally.

To assess the effects of temporally aggregating the fire pixels, ϕ_{count} and ϕ_{FRP} were calculated in discrete, non-overlapping intervals of one-day, one-week, and four-weeks beginning from the time of the first observation. Widening the temporal window essentially expanded the number of samples available to calculate ϕ_{count} and ϕ_{FRP} . Ratios of fire pixel counts and FRP were assigned timestamps corresponding to the centre of each temporal window such that:

$$\phi_{FRP}(t + \frac{\Delta t}{2}) = \frac{\sum_{i_{SEVIRI}=1}^{n_{\Delta t}} FRP_{i_{SEVIRI}}}{\sum_{i_{MODIS}=1}^{n_{\Delta t}} FRP_{i_{MODIS}}}$$

Equation 4.1

where t is the serial time at the beginning of the day, week or four-week interval, Δt is the duration of the interval, i_{SEVIRI} and i_{MODIS} are indices of the fire pixels detected by each sensor, $n_{\Delta t}$ is the total number of fire pixels detected by each sensor within the respective interval, and FRP is the fire radiative power associated with each fire pixel. The ratio of fire pixel counts, ϕ_{count} , is simply the values of $n_{\Delta t}$ for SEVIRI divided by that for MODIS.

Since fire activity varies with the season, as well as with ecoregion and land use, the patterns of ϕ_{count} and ϕ_{FRP} were also mapped spatially. For comparison, the full continent of Africa was gridded at 5.0°, 1.0° and 0.25° grid cell resolutions. Spatially explicit yearly ratios of count and FRP were calculated by summing all concurrent and collocated fire pixels detected in a single grid cell throughout the year, and again then dividing the SEVIRI totals by the MODIS totals within each grid cell.

4.2.2.3 Potential Adjustment of SEVIRI Gridded FRP Data for the Effect of Undetected Fires

Statistical distributions of FRP measured by SEVIRI suffer from left-hand truncation due to the inability of the sensor and active fire detection algorithms to reliably distinguish low FRP fires, an effect illustrated in Figure 4.3 above. Figure 4.4 shows the effect of this truncation on the FRP frequency-magnitude distributions obtained from the matched SEVIRI and MODIS training dataset, and it can be seen that the distribution here is in agreement with that of full SEVIRI data set displayed in Figure 4.2. It also confirms that for MODIS, the minimum FRP detection threshold for reliably detected fire pixels is $\sim 7 - 10$ MW. Right hand truncation of the distributions is also seen, and this is due to the effects of sensor saturation occurring at a lower FRP for SEVIRI than for MODIS due to the low gain, high saturation temperature of the MODIS MIR channel (Kaufman et al., 1998).




Figure 4.4: Frequency-magnitude distributions for all contemporaneous SEVIRI and MODIS fire pixels detected across Africa in Feb 2004-Jan 2005 (i.e. the training dataset discussed herein).

To account for the artefacts illustrated in the above frequency magnitude plot, two simple methodologies were tested for adjusting the full SEVIRI dataset at 15-minute temporal resolution and continental coverage. Both methods relied on the relationships developed within the one-year training dataset. The first approach simply interpolated the temporal profile of ratios calculated within the training dataset described previously, initially on a non-spatial basis by combining data from the whole continent together for each temporal window considered. As will be justified in the results, instead of incrementing the temporal window by a discrete week, however, a rolling weekly window was incremented by a single day over the year to provide 365 weekly ratios at daily temporal resolution:

$$\phi_{FRP}\left(t + \frac{\Delta t}{2}\right) = \frac{\sum_{i_{SEVIRI}=1}^{n_M} FRP_{i_{SEVIRI}}}{\sum_{i_{MODIS}=1}^{n_M} FRP_{i_{MODIS}}}$$

Equation 4.2

where t is the serial time at the beginning of each day, Δt is a constant interval of one week, and $n_{\Delta t}$ is the total number of fire pixels detected by each sensor within the week.

The rolling weekly ratios calculated for each day had the following characteristics: i) ratios were assigned timestamps at the middle of the rolling weekly window, i.e., at 12:00 on the 4th day of the week, ii) ratios on sequential days shared fire pixels that were detected over six of the previous seven days used to construct the ratios, and iii) only the ratios between days 4 and 362 were considered valid since the weekly window was moving into and out of the training dataset at these times respectively. Ultimately the values for ϕ_{count} and ϕ_{FRP} at each of the 96 daily SEVIRI timeslots were derived by linearly interpolating between the ratios obtained from Equation 4.2.

Adjusting SEVIRI's response to fire activity in the manner described above assumes that the sensor-to-sensor ratios in the training dataset are valid outside the MODIS ground coverage over which they were originally developed, and that the temporal trend of the ratios in the training dataset was valid for SEVIRI observations occurring between the MODIS overpass

times. Furthermore this technique is not spatially explicit, since adjustments are performed at the continental scale using all fire pixels detected by SEVIRI at each timeslot.

The second method to adjust SEVIRI measurements was designed to incorporate both the temporal and spatial variability of ϕ_{count} and ϕ_{FRP} . To do so, the continent of Africa was gridded into 5° resolution cells for each calendar month, with a total of 16×16 grids covering the continent (a domain of $80^\circ \times 80^\circ$, with identical boundaries as the grids defined in the previous section). All fire pixels detected by SEVIRI and MODIS within the training dataset were summed in each grid cell for each calendar month, and spatially explicit monthly ratios calculated by dividing the SEVIRI totals by the MODIS totals. Where and when in the 2004/05 training dataset that SEVIRI detected fire pixels but MODIS did not, or MODIS detected fire pixels but SEVIRI did not, the yearly ratios of ϕ_{count} and ϕ_{FRP} were stored in the monthly grid product by default. Justifications for the use of a 5° grid cell resolution and a monthly temporal window are presented in the results section.

For validation of the approach, the set of 12 monthly spatially explicit ratios were first applied to the full 2004/05 SEVIRI active fire dataset at 15-minute temporal resolution and continental coverage. For each of the 96 SEVIRI timeslots per day, the number of fire pixels and FRP detected by SEVIRI in each 5° grid cell were summed and divided by ϕ_{count} and ϕ_{FRP} that were stored in the respective monthly grid product. As a pseudo-validation exercise, the adjusted FRP_{SEVIRI} at each timeslot was then spatially integrated (i.e., summed over the continent) and compared to the adjusted SEVIRI measure obtained through the linear interpolation of the rolling weekly ratios. A comparison of the two techniques can at best be considered as semi-independent validation of the monthly grid product via comparison to the continent-wide adjustment procedure.

A full independent validation was conducted by using concurrent and collocated fire pixels detected by both sensors across Africa in a period completely outside of that used to determine the gridded ratio product – in this case August 2007. The subsetting procedure for the MODIS and SEVIRI fire detections in August 2007 was identical to that used to create the training dataset in 2004/05. Hereafter the concurrent and collocated fire pixels detected by SEVIRI and MODIS in August 2007 is referred to as the “validation dataset.” For each MODIS overpass concurrent with a SEVIRI scan, the number of fire pixels and FRP detected by SEVIRI in each 5° grid cell were summed and divided by the spatially explicit monthly ratios of ϕ_{count} and ϕ_{FRP} stored in the August 2004 grid product. Subsequent comparisons between the adjusted SEVIRI and the measured MODIS values in August 2007 were performed on a per overpass basis (i.e., spatially integrated basis) and on a per grid cell basis.

As a last step, an evaluation was conducted to assess the utility of the 5° grid-cell ratios when applied at 1° and 0.25° grid cell resolution. As described above, for each MODIS overpass concurrent with a SEVIRI scan, the number of fire pixels and FRP measured by SEVIRI in each 1° , or 0.25° , grid cell were summed, however in this case the spatially explicit monthly ratios ϕ_{count} and ϕ_{FRP} were applied depending upon which 5° grid cell the 1° or 0.25° grid cell resided. The adjusted SEVIRI data are, in theory, representative of what MODIS would have recorded had it viewed the full grid cell at the time of the SEVIRI observation, and these ‘simulated MODIS’ results were compared to the actual MODIS observations in both a spatially integrated and a spatially explicit basis.

4.2.3 Analysis of Ecosystem-specific Biases

In this study component, the ratio of fire detections between SEVIRI and MODIS was studied with a view to an analysis of any bias that resulted from fires burning in different

landcover types. As an example, it might be possible that SEVIRI detects a greater proportion of the MODIS-detected fires in grasslands than in forests due to the fires in forests being dominated by lower FRP events. For this study, fire detections from the KCL SEVIRI FRP product for the time period February 2004 to January 2005 were grouped according to the land cover type classification of the Global Land Cover (GLC) 2000 product (Mayaux *et al.*, 2004). MODIS fire detections from the corresponding MOD14 and MYD14 datasets were used for the comparison datasets. The relative frequency of fire occurrence in the various land cover classes was analyzed in order to find out if the detection algorithm or the pixel resolution of the SEVIRI data was leading to ecosystem specific biases.

4.2.4 Effects of Viewing Geometry

As noted above, the SEVIRI pixel size increases with distance from the sub-satellite point. This will lead to larger FRP values required to detect a fire (and also the ability to record larger FRP values before the pixel reaches saturation). The impact will be masked to some degree by the fact that different landcover classes will likely be characterised by different FRP characteristics (see above), and that landcover is not uniform as you move away from the sub-satellite point. The most extreme effects of viewing geometry related issues will be seen towards the edge of the scan, and this issue was therefore investigated via an analysis to determine whether the SEVIRI FRP/MODIS FRP ratio is lower over such areas (e.g. Madagascar and South America) than at regions closer to the sub-satellite point.

4.2.5 Effects of Saturation

Saturation of the SEVIRI pixels (nominally for brightness temperatures above 335 K) will not impact on the ability of the FRP algorithm to detect fires, but it will lead to an underestimation of the true fire radiative power. The impact of this was gauged by firstly determining the typical degree of saturation seen in standard SEVIRI level 1.5 data, and secondly by exploiting data from the SEVIRI 'special operations' mode experiment whereby the Meteosat-8 SEVIRI was operated in the low-gain setting. In this mode the sensor was able to record without the effects of sensor saturation, and the resulting 'true' FRP record was compared to that in which the FRP of pixels whose MIR brightness temperature was above the normal 335 K maximum was set to what it would have been had saturation in fact occurred at that temperature.

4.2.6 Effects of SEVIRI sensor characteristics and Level 1.0 to 1.5 pre-processing operations

The methodology adopted was two fold, firstly a direct comparison of SEVIRI level 1.0 and level 1.5 data of large fires, in order to assess the impact of the level 1.0 to 1.5 pre-processing procedures. Secondly, simulation of the SEVIRI observation process, using modelled fires and background conditions taken from the aforementioned BIRD HSRS imagery (in order to obtain realistic measures of ambient background brightness temperature variability around fires). The modelling including simulation of the SEVIRI point spread function (PSF) and the impact of the Finite Impulse Response (FIR) filter, which is applied to the recorded signals onboard the MSG satellite. The impact of the PSF and FIR filter are present even within Level 1.0 data, but the level 1.5 data have additional features induced via the spatial regridding and interpolation algorithms used in the EUMETSAT data processing chain (algorithms are fully detailed in the Image Processing Facility Algorithm Documentation; Eumetsat, 2003).

4.3 LandSAF Product Validations

The key purpose here was to determine whether the Landsaf FRP product had similar accuracy characteristics to the KCL FRP product, which had formed the dataset used for the majority of the other accuracy evaluation tests.

4.3.1 Comparison to KCL product

This work examined the errors of omission and commission of the LandSAF FRP product with respect to the KCL FRP product, only over Africa since the KCL FRP product is only available for this continent. Data from 1 – 5 August 2007 (415 separate SEVIRI imaging slots) from both processing chains were compared over the LandSAF southern Africa region, with errors of omission, commission and per-fire FRP levels of agreement quantified. This allowed determination of whether the Land SAF products have the same or similar accuracies as the original KCL FRP product. The August 2007 LandSAF FRP product dataset showed insufficient fire detections in the north Africa region to warrant a detailed comparison, and data from a different period (e.g. February) should be obtained for this purpose during any future work.

4.3.2 Comparison to MODIS

Here the errors of omission, commission and per-fire FRP levels of agreement were quantified for the LandSAF FRP product, using as the comparison dataset the MOD14/MYD14 MODIS data. The methodology used was that previously adopted for the same analysis undertaken for the KCL FRP product, outlined in Section 4.2.1. The areas covered by this analysis were the southern African and South American LandSAF regions.

4.4 Validation Based on Impact Studies

4.4.1 Impacts of Temporal Resolution

In order to assess the impact of representing or neglecting the temporal variability of fire emission on time scales of hours and days, model simulations of atmospheric carbon dioxide concentrations (CO₂) using a preliminary version of the GEMS CO₂ model were carried out. Atmospheric CO₂ has been selected for the study because it has a long atmospheric lifetime and does not possess atmospheric sources and sinks. Therefore, it can be regarded as a passive tracer with a long lifetime, and its fields display the interactions of the different emission data with the atmospheric transport most clearly. Even though the variations of the CO₂ field induced by fire emissions appear relatively small, they are significant for the source/sink inversions, which are the ultimate goal of atmospheric CO₂ monitoring.

The GEMS CO₂ model is a global atmospheric transport model which predicts 3D global distributions of CO₂. In the current setup of the model, CO₂ is treated as passive tracer and transport by advection, turbulence and convection are resolved (see also section 3.1.6.2). The current GEMS system (Hollingsworth et al. 2008) uses fire emissions from the GFEDv2 inventory (van der Werf et al. 2006) with 8 day time resolution (see Section 3.1.6.1). Atmospheric CO₂ fields modelled with these emissions are compared to fields modelled with emissions with 1 hour and 1 day time resolution.

The CO₂ emission data with different time resolutions were created by modulating the GFEDv2 8 daily emissions with the higher frequency temporal patterns observed by SEVIRI. Thus the impact of the temporal resolutions is separated from the one due to different total

emission amounts. The following steps are performed to make consistent emissions with 8d, 1d, and 1h resolution:

1. convert GFEDv2_8days dimensions to $[\text{kg}/\text{m}^2/\text{s}]$
2. obtain gridded ($1^\circ \times 1^\circ$) SEVIRI FRP data set corrected for partial cloud cover, atmospheric transmission, and missed small fires. This product has been generated by KCL. File name:
FRPcloudweighted1deg_1degree_ATMOS_MISSEDFIRES CORRECTED
3. fill FRP data gaps
 - a. missing 1 hour frames replaced with previous frames
 - b. missing grid cell values (-1) replaced with zero
4. average FRP over 8 day periods of GFEDv2_8days
5. add 1 W to eliminate division by zero errors
6. compute conversion factor = GFEDv2 emission / SEVIRI FRP, for each 8 day period and $1^\circ \times 1^\circ$ pixel over Africa
7. compute SEVIRI emission = SEVIRI FRP times conversion factor, for each 1 hour and $1^\circ \times 1^\circ$ pixel over Africa
8. pad with GFEDv2_8days for global coverage
9. average over 1 day and 8 days
10. convert 8. and 9. to GRIB with $1^\circ \times 1^\circ$ grid
11. convert 10. to GRIB with reduced Gaussian resolution T159

Four model runs have been performed, based on the different fire emission input data sets. The simulations are not constraint by any CO_2 observations. Key properties of the model setup are listed in Table 4.1.

Table 4-1: CO_2 model run setup

modelled period	2 February – 24 December 2004			
horizontal resolution	T159 (~ 125 km)			
number of vertical levels	60			
meteorology	nudged to operational analysis at 00 and 12 UTC			
Fire emission level	Lowest model level			
fire emission time resolution	no fires	8 days (8d)	1 day (1d)	1 hour (1h)

4.4.2 Impact of FRP versus Hot Spot Detection

Mikhail Sofiev at FMI has kindly given FREEVAL access to his analyses of the $\text{PM}_{2.5}$ fire emission fields generated with the FMI Fire Assimilation System (FAS) from MODIS TA and FRP observations and of the SILAM dispersion model forecasts of $\text{PM}_{2.5}$ based on the FAS emissions, see section 3.1.6.3.

One line of analysis compares the emission fields obtained from the two MODIS products and averaged over several months. Since both are obtained with empirical emission factors, the comparison is mostly sensitive to the different geographical distributions of fire emissions

obtained by using either a qualitative hot spot product, i.e. TA, or the quantitative FRP information.

The second line of analysis compares modelled atmospheric PM_{2.5} fields, based on the two different fire observation products, with satellite-based and in-situ observations of the actual atmospheric aerosol fields. Thus an end-to-end assessment of the two approaches can be made.

4.4.3 Impact on Estimating Fire Emissions

The quality of SEVIRI FRP-derived fire emissions was assessed by comparison to the published estimates contained in the Global Fire Emissions Database (GFED) version 2 (van der Werf et al. 2006). Because of the spatially limited coverage of the SEVIRI retrievals, the comparison is restricted to the African continent. For the analysis, the continent is subdivided into two study regions, namely Africa north of the equator and Africa south of the equator. The analysis covers the period February 2004 to January 2005 and uses monthly estimates of carbon emissions. The focus of the comparison is on how well SEVIRI FRP derived carbon emissions for the two sub-regions agree with the GFED estimates in terms of seasonal pattern and total amounts.

The GFED inventory for years after 2001 is based on MODIS active fire detections which were scaled to a limited number of MODIS burned area observations and then multiplied by available fuel loads and combustion efficiencies derived from the CASA vegetation model. While MODIS has a higher likelihood of fire detection in an individual scene compared to SEVIRI, there are far less scenes available per day and these do not capture the time window of maximum daily fire activity (the two daytime overpasses of MODIS Aqua and MODIS Terra occur at 10:30 and 14:30 local time, respectively). As a consequence SEVIRI actually detects a larger absolute number of fires per day than MODIS and one has to rely on the scaling procedure for MODIS to provide a complete estimate of fire affected area and burned material. Therefore, the comparison of SEVIRI FRP to GFED emissions should be regarded as a comparison between two independent data sets rather than a validation using a reference data set. Nevertheless, this comparison is important, because GFED has become a de-facto standard in atmospheric composition modelling.

Another, more qualitative validation of the seasonality of emissions derived from SEVIRI FRP uses MOPITT CO profiles for comparison. The analysis covers the same period as the analysis mentioned above (February 2004 to January 2005). For the analysis, monthly variations in SEVIRI FRP in southern hemispheric Africa are directly compared to mean monthly MOPITT CO profiles for the same region. CO is a tracer for biomass burning and the satellite-derived CO profiles provide an estimate of the seasonality and the amount of burning. Because of being different quantities, the direct comparison of FRP with measured CO profiles provides no quantitative comparison. However, because estimated CO emissions are considered to be largely proportional to the FRP (assuming that at least on a regional scale fires always represent a mix between flaming and smoldering conditions with roughly constant proportion), the comparison provides qualitative information on whether the seasonal pattern of FRP-derived CO emissions will match with observations.

4.4.4 End-to-end Use (Greek Fires Case Study)

In late August 2007, huge fires burnt in Greece. The FRP derived emissions and the simulated and observed plumes of these fires were used to test and demonstrate the feasibility and potential of fire plume modelling and, ultimately, forecasting by combining SEVIRI FRP with the GEMS system for aerosol monitoring.

The current version of the global aerosol model developed in GEMS (Morcrette et al. 2008) is driven with the GFEDv2 inventory. For this study, aerosol emissions derived from the SEVIRI FRP product by KCL have been superimposed on this data set and the modelled smoke plumes are compared to MODIS observations. In contrast to the tests on the impact of temporal resolution (see section 4.4.1) where only the time information of SEVIRI was used, here the FRP product was used quantitatively with its correction to account for small fires. The simulation also covers a smoke plume that is transported from Algeria to Italy and is compared to ground-based AERONET observations at Lecce University. The individual data processing steps were:

1. convert SEVIRI 3.9 μm channel to FRP [MW]
2. grid FRP to 0.1x0.1 deg grid
3. average over 1 hour
4. correct for fires below detection limit (no correction for partial cloud cover was needed, since Greece was cloud-free at the time of the fires)
5. convert
 - to Dry Matter combustion rate [kg/s] (factor 0.368 kg/s/MW)
 - to BC, OM, and SO₄ emission rate [kg/s] with emission factors based on a combination of Andreae and Merlet (2001) and Ichoku and Kaufman (2005)
6. interpolate to the grid cells corresponding to model resolution T799 (triangular truncation at wavenumber 799), which is the resolution of the operational deterministic ECMWF weather forecast and also representative for current regional air quality monitoring systems. (~25km)
7. run the GEMS aerosol model with fire emissions in lowest layer for 1 August – 6 September 2004. Compared to the standard GEMS model the resolution has been increased.

5 Validation Results

5.1 Results of the Algorithm Performance Analysis

Figure 5.1 shows the impact of assumption (i), the fourth order power law approximation to Planck's Radiation Law, by comparing the FRP derived via the MIR radiance method (FRP_{MIR}) to that derived via the Stefan-Boltzmann Law (FRP_{TRUE}), in the case that the fire is fully resolved by the sensor (i.e. there is no 'background' non-fire component to the signal). The difference between these two measures, denoted by their ratio (R), is due only to the uncertainty introduced by the Planck Function approximation, and is shown here to be relatively constant (i.e. R constrained between 0.88 and 1.12) over a significant part of the emitter temperature range considered (i.e. $> \sim 665$ K and < 1365 K).




Figure 5.1: Ratio (R) between the Fire Radiative Power estimate derived from MIR radiance method (FRP_{MIR}), and the true FRP derived from the Stefan-Boltzmann Law (FRP_{TRUE}). Calculations here assume pixels fully filled by fire. Horizontal dashed lines denote the limits where FRP_{MIR} is within a factor of 0.88 and 1.12 of FRP_{TRUE} , whilst vertical lines denote the corresponding temperature range (665 - 1365 K).

An example of the emitter temperature distribution retrieved over a real wildfire is shown in Figure 5.2, indicating that in excess of 95% of the fire pixels have emitter temperatures in the 665 – 1365 K range, where R is constrained between 0.88 to 1.12. Thus the underlying FRP uncertainty induced by use of the MIR radiance method is governed by this uncertainty, but the advantage is that by using this method we do not have to resolve the fire temperature distribution and can thus use the method on highly sub-pixel sized events, providing of course that we can assume that their temperatures lie within the above range. This range is expected to cover the vast majority of fire events, and is broadly consistent with that specified in, for example, Ohlemiller (1995) and Riggan et al. (2004) for actively burning fires and in the assumptions made during derivation of the MODIS fire detection and fire characterisation approach (Kaufman et al., 1998).




Figure 5.2: Fire emitter temperatures retrieved from analysis of Airborne Visible Infrared Imaging Spectrometer (AVIRIS) hyperspectral data of the 2003 Simi Fire in Southern California, USA by Dennison *et al.* (2006). The method used a spectral library of emitted hyperspectral radiance endmembers corresponding to a fire temperature range of 500-1500 K, along with reflected solar radiance endmembers, both based on simulations using the MODTRAN radiative transfer model. These endmembers were used to determine the true subpixel fire emitter temperature within each active fire pixel identified with AVIRIS. Error bars indicate the median range of emitter temperatures modeled within 5% of the RMSE for the indicated emitter temperature.

At the scale of satellite observations, e.g. the nominal 4.8 x 4.8 km pixel sizes supplied by SEVIRI, real fires consist of a wide mixture of temperature components within each ‘fire pixel’ rather than single temperature emitters – as can be seen from the temperature distributions seen in the 50 m spatial resolution AVIRIS data shown above. As a result, the ratio (R) of FRP_{MIR}/FRP_{TRUE} for the mixed temperature fires contained in such large pixels may likely move away from the extremes shown in Figure 5.1 due to FRP underestimation inherent towards the lower (< 750 K) and upper (> 1200 K) fire temperature limits being counteracted by FRP overestimation from the mid-range (750 – 1200 K) emitters. However, since the actual fire temperature distribution within a SEVIRI pixel is by definition unknown, the theoretical accuracy limits of 0.88 to 1.12 are maintained. Note that in the case of Figure 5.2, most fire pixels have temperatures between 800 and 1050 K, and in this range FRP estimated by the MIR radiance method positively biased ($R > 1.0$), but when the full fire temperature distribution is considered the overestimation will be by a factor less than the maximum of 1.12.

The assumptions (ii) used to derive Equation 1.6 from Equation 1.5 were assessed for their impact on FRP retrieval accuracy via the aforementioned radiative transfer modelling of sub-pixel sized active fire observations. They were found to introduce no error significantly above the $\pm 12\%$ introduced by the fourth order approximation to Planck’s Radiation Law (whose magnitude was already demonstrated in Figure 5.1).

Assumptions (iii) and (iv) regard uncertainties in the atmospheric parameter of the FRP equation (τ_{MIR} , the MIR atmospheric transmission) and in $L_{b,MIR}$ (the background radiance of the fire pixel, estimated from the background window pixels). Combining Equation 1.1 and an error of $\pm L_{berror,MIR}$ in the assumed background radiance we state:

$$FRP_{MIR} = \frac{1}{\tau_{MIR}} \left(\frac{\sigma}{a} \right) (L_{MIR} - L_{b,MIR}) \pm \frac{1}{\tau_{MIR}} \left(\frac{\sigma}{a} \right) L_{berror,MIR} \quad [Wm^{-2}]$$

Equation 5.1

The first term on the rhs of Equation 5.1 represents the fire FRP, which has the potential *multiplicative* error sources due to the uncertainties related to the power law approximation (a factor of 0.88 to 1.12 as shown in Figure 5.1) and the assumed atmospheric transmission, which can act either in the same direction as the error introduced by the power law approximation (and thus magnify it) or can act in the opposite direction (and thus counteract it). The second term on the rhs represents the error in FRP introduced by the inability to estimate $L_{b,MIR}$ perfectly from the background window pixels, and this is an *additive* error source. As can be seen from Equation 5.1, this value is multiplied by the inverse of the assumed atmospheric transmission. Only in cases where the fires actual FRP (term 1 of Equation 5.1) is relatively small but the uncertainty in the background (term 2 of Equation 5.1) is relatively large will the error in background characterisation have a major impact. Conversely however, the magnitude of the multiplicative error on term 1 of Equation 6.1 will grow with the fires FRP, and so it can remain significant for all classes of fire FRP.

The magnitude of these error sources is illustrated using a modelling exercise based on sets of true fire parameters (effective fire temperature and sub-pixel proportion; which together determine the fires FRP), the radiative transfer modeling to simulate SEVIRI spectral radiance observations of the ‘fire’ and ‘background window’ pixels, and the equations used to derive an estimate of the fire FRP from these observations. This system was perturbed by parameter alterations, notably to the assumed values of MIR atmospheric transmission and differences between the background pixel radiance and the true background radiance of the fire pixel itself (i.e. $L_{berror,MIR}$ is non-zero in Equation 5.1).

Results for three different effective fire emitter temperatures (650, 850 and 1000 K) and considering only a range of errors in the background characterisation, and not in assumed τ_{MIR} , are shown in Figure 5.3. For each fire temperature, the results converge at the $L_{berror,MIR} = 0$ point, with the magnitude of the error simply being that induced by the fourth order power law approximation to the Planck’s Radiation Law at that temperature (assumption (i)). As $L_{berror,MIR}$ increases away from zero, the additive error component shown in Equation 5.1 becomes non-zero and the same $L_{berror,MIR}$ perturbation induces a larger percentage error in FRP for low FRP (i.e. lower temperature and/or lower sub-pixel fractional area) fires than for large FRP fires. Giglio and Kendall (2001) in a somewhat similar exercise considered perturbations in the background radiance of $\pm 0.02 \text{ Wm}^{-2}\text{sr}^{-1}\mu\text{m}^{-1}$, but here we consider perturbations up to of $\pm 0.1 \text{ Wm}^{-2}\text{sr}^{-1}\mu\text{m}^{-1}$ since this level of background window radiance variability is seen in the SEVIRI FRP data, though values around $\pm 0.03 \text{ Wm}^{-2}\text{sr}^{-1}\mu\text{m}^{-1}$ are more common. Only in situations where the fires are, in any case, very unlikely to be detectable do $L_{berror,MIR}$ perturbations of $\pm 0.03 \text{ Wm}^{-2}\text{sr}^{-1}\mu\text{m}^{-1}$ have a strong influence on FRP_{MIR} . For fires having FRPs greater than the minimum values confidently detectable by SEVIRI, perturbations of this sort add significantly less than 10% error to that already existing from the Planck function approximation, irrespective of the actual fire temperature or sub-pixel size.




Figure 5.3: Departure of estimated FRP from true FRP for blackbody fires of temperature 650, 800 and 1000 K and fractional areas 0.1 to 0.0001 (denoted by the labels) as a function of the level of disagreement between the assumed background radiance signal and its true value (i.e. the value expressed by $L_{berror,MIR}$ in Equation 5.1). Values of other fixed parameters such as downwelling and upwelling atmospheric radiances and the atmospheric transmissivity have the values taken previously in the similar modelling study conducted by Wooster et al. (2005). Results are calculated here using the full parameterisation of Equation 1.5 and Equation 1.1 to take into account all error sources. Dotted lines indicate situations where the fire is too cool and/or small to be robustly detectable (i.e. MIR brightness temperature is raised by less than 6 K over that of surrounding non-fire pixels). At $L_{berror,MIR} = 0$ results for each fire temperature converge, confirming the insensitivity of the error to fire fractional area under this condition and thus the appropriateness of the assumptions made in deriving Equation 1.6 from Equation 1.5.

Figure 5.4 indicates the additional sensitivity of the FRP retrievals to the estimate of MIR atmospheric transmission, and how this interacts with $L_{berror,MIR}$ assessed in the previous Figure. Using an 800 K fire as an example, the effect of an error of $\pm 15\%$ in the assumed value of τ_{MIR} is assessed. Assuming observations at the sub-satellite point, this equates approximately to an assumed minimum atmospheric transmission in the MIR spectral band ($\tau_{MIR} = 0.61$) when the transmission is actually at a maximum ($\tau_{MIR} = 0.7$), and visa versa. For such a fire, Figure 5.4b confirms that perfect knowledge of both τ_{MIR} and $L_{b,MIR}$ allows the maximum error in FRP to remain lower than $+10\%$ for all fire fractional areas and thus all

FRP values. A 15% overestimate in τ_{MIR} results in an FRP underestimate of $\sim 10\%$ (Figure 5.4a), whilst a 15% underestimate in τ_{MIR} increases the magnitude of the FRP overestimate derived via the MIR radiance method, to $\sim 25\%$ for all detectable fires Figure 5.4c).




Figure 5.4: As Figure 5.3. but now expressing the departure of the estimated FRP from the true FRP for blackbody fires of temperature 800 K and fractional areas 0.1 to 0.0001 (denoted by the labels) as a function of the level of disagreement between the assumed background radiance signal and its true value (i.e. the value expressed by $L_{berror,MIR}$ in Equation 5.1) and for different errors in the assumed MIR atmospheric transmission. Values of other fixed parameters such as downwelling and upwelling atmospheric radiances and the atmospheric transmissivity have the values taken previously in the similar modelling study conducted by Wooster et al. (2005). A 15% overestimate in assumed MIR atmospheric transmission is assumed in (a), perfect knowledge in (b), and a 15% underestimate in (c). Dotted lines indicate situations where the fire has too low and FRP to be robustly detectable (i.e. the MIR brightness temperature is raised by less than 6 K over that of surrounding non-fire pixels). At $L_{berror,MIR} = 0$ results for each fire temperature converge, indicating the insensitivity of the error to fire fractional area under this condition.

In terms of reported error for each FRP estimate, currently what is provided in the LandSAF FRP product is a measure of the additive error component (term 2 of Equation 5.1), calculated as the following [though from the ATBD it may not, apparently, currently be adjusted for the atmospheric transmission]:

$$FRP_{error_additive} = \pm \frac{A_s}{\tau_{assumed,MIR}} \left(\frac{\sigma}{a} \right) \sigma_{\tilde{T}_b} \quad [W]$$

Equation 5.2

where $\tau_{assumed, MIR}$ is the assumed MIR atmospheric transmission, A_s is the pixel sample area, and σ_{τ_b} is the estimates of uncertainty in the background radiance of the fire pixel, estimated from the background window standard deviation.

Additional uncertainty comes from the multiplicative error term, which can be calculated from:

$$FRP_{error_multiplicative} = \left(FRP_{measured} \pm FRP_{error_additive} \right) \left(\frac{1}{R} \frac{\tau_{assumed, MIR}}{\tau_{actual, MIR}} - 1 \right) \quad [W]$$

Equation 5.3

Where $FRP_{measured}$ is the reported FRP in the product, $FRP_{error_additive}$ is the additive error calculated from Equation 5.2, R is the ratio uncertainty resulting from the fourth order approximation to the Planck function shown in Figure 5.1 and $\tau_{assumed, MIR}$ and $\tau_{actual, MIR}$ are the assumed and actual MIR atmospheric transmission respectively. In most cases the actual values of R and $\tau_{actual, MIR}$ will be unknown, though their potential range is known and reported in the ATBD (Govaerts et al., 2007). Hence, using these values the appropriate range of potential multiplicative error can also be calculated for any FRP estimate reported in the product. The extreme values of the sum of the additive and multiplicative error components can then be taken as the estimate of overall uncertainty on FRP, which can be used to place uncertainty bounds on $FRP_{measured}$.

A mean background window radiance standard deviation of $\sim 0.03 \text{ Wm}^{-2}\text{sr}^{-1}\mu\text{m}^{-1}$ was determined from the LandSAF FRP products of southern Africa, with maximum values three times this. Independent testing of the levels of background window variability found at non-fire pixels (where the true ‘background’ temperature of the central pixel in the background window pixel grid is known) indicated that the standard deviation of background window radiances was mostly larger than the actual radiance difference between the central pixel of the background window and the mean radiance of the surrounding pixels, with Figure 5.5 showing an example of this at two different landcover classes (grassland and forest). This was found true for background windows of 5×5 , 7×7 or 10×10 pixels in size. Therefore, the background window radiance standard deviation measure currently used to estimate the additive error component of the FRP uncertainty budget is an appropriate, if perhaps somewhat conservative, measure.




Figure 5.5: The central pixel brightness temperature of a 5×5 pixel window plotted over the full 24 hr cycle for a southern Africa closed grassland site (top) and a deciduous forest site (bottom), as identified by the GLC2000 landcover database. Also shown are the difference between this pixels brightness temperature and the mean of the remaining background window pixels, and $\pm$ one standard deviation of the background window pixels. This latter figure is seen to mostly be larger than the actual difference between the central pixel and the mean of the background window pixels.

The total FRP uncertainty, estimated as the maximum range of the sum of the additive and multiplicative error components discussed above and presented in Equation 5.2 and Equation 5.3, was estimated for the full range of per-pixel FRP potentially measurable from SEVIRI. The calculations assumed both a ‘worst case’ (Case 1) additive error budget scenario where $\sigma_{\bar{I}_b}$ is equivalent to the aforementioned maximum background variation, and the ‘mean’ case (Case 2) where $\sigma_{\bar{I}_b}$ is equivalent to the aforementioned mean variation. In both cases it was

assumed that little information was available to estimate the true atmospheric transmission in the MIR spectral band, so $\tau_{assumed, MIR}$ was taken as the mid-range value of 0.66 calculated for a SEVIRI view zenith angle of 30 degrees and a water vapour content of 30 kg/m² [and thus is essentially a ‘default’ value in the middle of the actual potential range] and values of $\tau_{actual, MIR}$ were taken up to the possible extremes of 0.61 to 0.7 for that view zenith angle. In this way the multiplicative error budget represented here is the maximum uncertainty likely to be present, and could be reduced should it be possible to provide values of $\tau_{assumed, MIR}$ that are known to be closer to $\tau_{actual, MIR}$ than this (e.g. from modelled atmospheric water vapour distributions across the SEVIRI field of view obtained with a meteorological forecast model).

Figure 5.6 shows the results from the uncertainty model produced with such assumptions. In Case 1 the additive error resulting from the large background radiance uncertainty equates to an FRP uncertainty of 34 MW at the 30 degree VZA (where pixels are 15% larger than at the sub-satellite point), which represents a substantial fraction of the measured FRP for fire pixels not too far above the minimum that are detectable with SEVIRI. (e.g. $FRP_{measured}$ in the 50 – 100 MW range). In Case 2 the additive error resulting from the lower background radiance variability equates to a more manageable FRP uncertainty of 10 MW. In both Cases, it is apparent that the multiplicative error dominates the total uncertainty budget for most of the potential range of measured FRP, and only at the lower end of the potentially measurable FRP scale does the additive error make a major contribution. It should be noted, however, that this is particularly relevant as the majority of detected fires in Africa are characterised by low FRP values.




Figure 5.6: The x-axis reports the recorded FRP estimated by SEVIRI, whilst the y-axis reports the potential range of true FRP that could have given rise to that SEVIRI-derived FRP estimate. Results are shown over the 50 – 750 MW range, taking account of the additive error only (at left), and then both the total (additive plus multiplicative) error (at right). Case 1 assumes ‘maximum uncertainty’ errors in the radiance estimate of the fire pixel background (as deduced from the standard deviation of the background window radiances), whereas Case 2 assumes the mean uncertainty in this parameter. The maximum uncertainty in MIR atmospheric transmissivity is assumed in both cases, and both also take into account the full range of uncertainties in the fourth order approximation to the Planck Function (see text for details). In this way the multiplicative error component expressed here is the maximum expected for SEVIRI.

The calculations above assume the maximum uncertainty in atmospheric transmissivity. In all likelihood this will be reduced during the product development, for example by making use of model output for parameterise the atmospheric water vapour content and thus provide an estimate of $\tau_{\text{assumed, MIR}}$ that better approximates $\tau_{\text{actual, MIR}}$. Where atmospheric transmissivity is known with negligible uncertainty, the error budget reduces to the additive error component from the background window radiance variability, and the uncertainty due to the fourth order power law approximation to the Planck function. Assuming this, and using the relation presented in Equation 5.3 together with the observed FRP measures and additive error components deduced from 2000 fire pixel observations made across the southern African region on 2 June 2004 at the peak fire time slot (13:12 GMT). Figure 5.7 shows the distribution of FRP uncertainty. Half of the observations have a total FRP uncertainty less than $\pm 40\%$, and the mean uncertainty is also very close to this (i.e. uncertainties are normally

distributed). On average the per-pixel FRP uncertainty due to the additive error component is 30%, and the remaining uncertainty comes from the Planck function approximation. If SEVIRI were to have a higher spatial resolution, the magnitude of the uncertainty for a particular FRP fire would reduce, since the spectral radiance contribution of that fire to the overall pixel radiance would be increase, though a higher spatial resolution system would also be able to detect fires having low FRP so the overall uncertainty distribution may not be significantly affected.




Figure 5.7: % uncertainty in FRP for 2000 observed fire pixels across southern Africa. The MIR atmospheric transmissivity of 0.66 was assumed to be known perfectly, and the additive error component was calculated from the background pixel window standard deviation. The multiplicative error component came from the fourth order power law approximation only.

5.2 Results of the SEVIRI Product Performance Analysis

5.2.1 Per-Fire Comparisons

5.2.1.1 Errors of Omission and Commission

The analysis of errors of omission confirms that, though SEVIRI successfully detects very many fires each month, when MODIS and SEVIRI image the same area at the same time SEVIRI fails to detect many fires that MODIS does detect. Figure 5.8(a and b) demonstrate the effect over Central African Republic, where when using the SEVIRI observations that match to MODIS overpasses, SEVIRI detects only the larger of the MODIS detected fires. However, comparison of Figure 5.8a and 5.6c indicates that when all SEVIRI observations over the course of the 15-day study period are used, the spatio-temporal pattern of the SEVIRI-detected fires is very similar to those detected by MODIS – so most fires detected by MODIS are in fact detected by SEVIRI at some point in their lifetime. Thus by using all SEVIRI observations the spatial pattern and total number of individual fire events observed

over any particular period is reproduced rather well. However, the fact that the signal of many of these fires goes undetected by SEVIRI at the time of the MODIS overpass [Figure 5.8a and b] indicates the likelihood that, at any particular individual SEVIRI time slot, the instrument will only be detecting a fraction of the FRP that MODIS would have detected had it observed the area at the same moment. Thus, the total FRP derived from SEVIRI for a region at any given time will also be low biased when compared to MODIS.




Figure 5.8: Effect of the inability of SEVIRI to detect low FRP fire pixels that MODIS can detect, illustrated by SEVIRI and MODIS fire detections collected over Central African Republic and surroundings in February 1-14 2004. Fire pixel detections are coloured by day of detection. When only using data from the SEVIRI imaging slots that were co-incident with a MODIS overpass, comparison of (b) with (a) confirms that SEVIRI misses a large number of (low FRP) fire pixels. However, it should also be noted that when using all SEVIRI imaging slots, SEVIRI appears to agree well in comparison to MODIS in terms of identifying the spatial distribution fire-affected areas, and in fact can detect a larger number of fires overall. The conclusion is that whilst many fires have an insufficiently high FRP to be detected by SEVIRI if we limit the SEVIRI observations to just those at the MODIS overpass time, most fires appear to become sufficiently large and intense at some point in their lifecycle that they will be successfully detected by SEVIRI.

Full results from the analysis of omission and commission, indicate that in February 2004, 54% of all MODIS-detected fire pixels over Africa (a total of 140,000 pixels) had no corresponding SEVIRI fire pixel. However, it should be remembered when interpreting these results that a large number of these MODIS pixels likely formed clusters such that several MODIS fire pixels correspond to only one 'missing' SEVIRI pixel. For May 2004 the equivalent results were 101,000 missed MODIS fire pixels (57%), and for August 198,000 fire pixels (57%). Corresponding errors of commission (false detections) by SEVIRI were rather small, at 6% (February), 8% (May) and 6% (August), a level comparable to the ~ 10% rate quoted for the TRMM active fire product (Giglio et al., 2003a). The FRP of these false detections accounts for 3% (February), 6% (May) and 3% (August) of that months cumulative FRP total for the continent, indicating that the falsely detected fires have typically low FRP values.

In addition to its FRP, each detected fire pixel in the LandSAF and KCL FRP products has a confidence parameter attached, calculated as a function of the fires spectral signal above the background, its spatial location relative to clouds and water bodies, and series of other parameters detailed in Govaerts et al., 2007. The statistical distribution of this fire pixel confidence parameter for the erroneously detected fire pixels identified in the February, May and August 2004 datasets discussed above is plotted in Figure 5.9 and compared to the confidence parameter of the set of correctly identified fire pixels. The similar degrees of

commission error seen in each of the three months is reflected in the similar frequency distribution of the confidence parameter, though May has a distribution peaking towards a slightly lower confidence value, which reflects its slightly higher error of commission. The confidence values of the correct fire detections have a peak correctly shifted towards higher confidence values when compared to that of the false detections. However, it is not the case therefore that all fire pixels below a certain confidence limit can be automatically assumed to be false detections, since Figure 5.9 indicates that even some of the correctly identified fire pixels have confidence values lower than 0.5 for example. Such fire pixels are those most likely to be at the limit of detectability in terms of their spectral radiance signal above the background, and which maybe close to regions where false alarms are likely to be increased.




Figure 5.9: Frequency distribution of SEVIRI fire pixel detection confidence for all falsely detected fire pixels in February, May and August 2004, as compared to that of all fire pixels.

In fact, the majority of the false alarm fire pixels still have a confidence value exceeding 0.5, and this is mostly a result of the MIR brightness temperature limits used to define strong confidence and weak confidence fire pixels (Govaerts et al., 2007), and the fact that the detection algorithm is designed only to confirm potential fire pixels as true fire pixels when there is a reasonable level of certainty that this is correct (i.e. to minimize errors of commission as far as possible; which has shown to be the case since levels of commission are < 10% even though low FRP fires at the very limit of detectability are in fact regularly distinguished by the algorithm). A similar effect relating to relatively high confidence values for false alarm fire pixels has been noted in the MODIS fire products (Giglio et al., 2005). Of course, a small fraction of the identified false alarm detections by SEVIRI maybe due to MODIS incorrectly missing a fire. Morisette et al. (2005) indicate the strong performance of the MODIS fire detection product (using the version 4 algorithm), but Figure 6.3 illustrates two examples where we have found MODIS fire detection errors occur in comparison with a successful SEVIRI detection. Figure 5.10 (a-b) illustrates a case where SEVIRI detects three fires, whilst for some reason the MODIS MOD14 product only detects one fire. Figure 5.10 (c-d) highlights a further example where a MODIS pixel that clearly does contain an active fire is classified as a water pixel by the landcover map used in the MODIS fire detection procedure, and is therefore not passed through to the fire detection algorithm. This may possibly be a seasonal water body that in the dry season is the site of many fires.




Figure 5.10: Two examples where MODIS fire detection appears less sensitive than that of SEVIRI. (A) and (B) show, respectively, matching SEVIRI and MODIS night-time MIR channel images where fires are visible. White circles indicate the detected fires for each dataset. Of these, MODIS detects only one but SEVIRI all three. (C) and (D) again show, respectively, SEVIRI and MODIS MIR channel imagery which indicate the presence of a fire, which SEVIRI successfully detects. MODIS, however, fails to detect this fire, which appears to be due to the landcover of these pixels being (incorrectly) classed as water in the landcover map used by the MODIS fire detection algorithm. Although these results indicate that some errors of omission do exist in the MOD14 fire detections with respect to SEVIRI, these are likely to be the exception rather than the norm since validation of the MOD 14 product using matching ASTER data indicates strong overall performance in this environment (Morissette et al., 2005).

5.2.1.2 Sensor-to Sensor Per-Fire FRP Comparison

Figure 5.11 presents the results of the per-fire FRP comparison between fires that were successfully detected by SEVIRI and by MODIS, remembering that a fire maybe represented by different numbers of spatially contiguous fire pixels in the data of each sensor (an indeed is very likely to be, due to the sensors differing spatial resolutions). The per-fire FRP data generally show a strong level of agreement, with low bias but significant scatter. The observed scatter results from a number of key causes, (i) uncertainty in the ambient background characterization results of each sensor (Wooster et al., 2005); (ii) the small but potentially significant (≤ 6 minutes) time difference between corresponding MODIS and SEVIRI observations of the same fire, (iii) variation in retrieved FRP related to the sub-pixel location of the fire with respect to the sensor IFOV and point spread function, and (iv) the fact that ‘fire pixels’ have to have a significantly higher minimum FRP to be detected by SEVIRI than by MODIS, but more of the overall radiance contribution from a fire maybe contained within a SEVIRI pixel than a MODIS pixel, and so on a case-by-case basis, certain

of the individual pixels making up a fire may remain undetected by SEVIRI but detected by MODIS, or visa versa.

Figure 5.11 indicates that the level of per-fire FRP agreement is lower for fires with a MODIS-derived FRP exceeding 3000 MW, which correspond to unusually large and/or intensely burning fires that are most likely subject to the effects of SEVIRI MIR detector saturation (Roberts et al., 2005), and which is analysed in Section 5.2.5. Fortunately, the incidence of such fires is rather low, so the effect of SEVIRI pixel saturation is limited when considering all fires made over larger regions, and certainly is much less important than the fact that SEVIRI misses many of the lower FRP fire pixels that MODIS can detect.




Figure 5.11: A comparison of per-fire FRP derived from SEVIRI and MODIS observations of 289 fires observed near-simultaneously by each sensor in February, May and August 2004. Fires are designated as contiguous clusters of active fire pixels. Correlation between the two datasets is quite strong ($r^2 = 0.62$, $p < 0.0001$) but there is clear evidence that SEVIRI overestimates FRP for fires where the MODIS-derived FRP is $< \sim 40$ MW, and underestimates FRP for fires where the MODIS-derived FRP is $> \sim 3000$ MW. Discounting these 17 cases increases the strength of the correlation significantly ($r^2 = 0.87$, $p < 0.0001$).

A further effect that mostly impacts retrievals over high-FRP fires is that the SCE cloud mask sometimes flags the thick smoke from particularly large fires as cloud. In the MIR it is possible to detect fire pixels through such smoke, but because the site of the fire pixel is flagged as cloud in the cloud mask, it will remain undetected. Visual inspection of a number of large fires indicates such occurrences are rare, but do occur and contribute to the increased FRP underestimation over the highest FRP fires.

The agreement between the MODIS- and SEVIRI-derived per-fire FRP is also considerably worsened for fire fires detected by SEVIRI where the MODIS-derived FRP was less than 40 MW. Such fires correspond to a SEVIRI MIR brightness temperature increase of only a few Kelvin above the background ($\sim 2 - 3$ K, depending on the ambient temperature and levels of incoming solar radiation), thus indicating that they are at the very limit of the detectability envelope seen in Figure 4.1 and are also most subject to the additive errors introduced by uncertainty in the ambient background characterisation. Considering all 289 matchups presented in Figure 5.11, 76% of the MODIS and SEVIRI FRP values agree to within 33%, a

proportion that increases to 79% when considering those fires whose FRP as derived from MODIS fell within the $40 \text{ MW} < \text{FRP} < 3000 \text{ MW}$ limit. Within this limit the data show minimum bias with respect to MODIS (only 3.7 MW between the SEVIRI- and MODIS-derived per-pixel FRP measures).

5.2.2 Effect of Spatial Resolution – Area Based Comparisons

5.2.2.1 Basic Results

Figure 5.12 presents the results of the regional-scale cumulative FRP comparisons, with each point representing the total FRP observed by MODIS and SEVIRI at the time of a MODIS overpass and within the area covered by the entire MODIS swath. This area-based cumulative FRP is clearly underestimated by SEVIRI with respect to MODIS (i.e. the gradient of the lines of best fit are < 1.0), and this underestimation is due to SEVIRI's inability to detect the lowest FRP fire pixels, many of which MODIS can detect due to its significantly higher spatial resolution as already demonstrated.




Figure 5.12: Relationship between regional-scale inter-scene FRP derived from all spatially matched, contemporaneous SEVIRI and MODIS observations for, from top left clockwise, February, May, and August 2004. Data are taken from across the African continent in each case, but fires are concentrated in north, central and southern Africa respectively. The data were taken from the entire MODIS swath, between nadir and 55° scan angle, and the area of the relevant contemporaneous SEVIRI image was

spatially subset to reflect the same geographic coverage. The OLS linear best-fit passing through the origin is shown (bold line), along with the 95% confidence intervals on the mean (dotted line) and on the prediction of y from x (outermost lines). In each case SEVIRI generally underestimates regional-scale FRP, primarily due to the non-detection of the lowest FRP fire pixels, many of which MODIS can detect.

Since the proportion of low-to-high FRP fire pixels varies between each MODIS image (depending presumably on time of acquisition and its interplay with the fire diurnal cycle, and location of acquisition and its interplay with landcover/landuse) the level of agreement between the cumulative inter-scene FRP recorded by SEVIRI and MODIS also varies, resulting in a significant scatter (as indicated by $r^2 < 1.0$). Nevertheless, the relationship between SEVIRI- and MODIS-derived FRP is quite strong in each case, and the relatively high degree of similarity in the results from the different months and areas (e.g. in terms of the slope of the OLS line of best fit, the rmse and r^2 coefficient) indicates a degree of consistency in the fire regime and algorithm performance across Africa as a whole. The total FRP measures obtained by accumulating data from the entire month of matched SEVIRI and whole-swath MODIS imagery indicates a SEVIRI-to-MODIS monthly cumulative FRP ratio of 0.57 (Feb), 0.60 (May) and 0.55 (Aug), again indicating a high degree of consistency between months.

Looking in detail at Figure 5.12, it is apparent that in some cases SEVIRI underestimates regional FRP by more than 50% compared to MODIS. The most significant cases turn out to be a consequence of small, scattered clouds and the fact that the cloud mask used in the production of the MOD14 fire product is of a higher spatial resolution than that of SEVIRI, and also appears less conservative in that it sometimes fails to mask smaller clouds and cloud edges (Giglio *et al.*, 2003a). This typically results in a greater proportion of pixels being flagged as cloud contaminated by SEVIRI than by MODIS, and also allows MODIS to correctly identify active fire pixels occurring between closely spaced clouds in a higher proportion of cases. In the remaining examples, thin clouds and/or heavy aerosols covered large areas, and the Stage 2 SEVIRI MIR/RED radiance ratio test detailed in ATBD caused a number of low FRP fire pixels to remain undetected in these cases.

5.2.2.2 Detailed Sensor-to-Sensor Comparisons of Fire Activity Over the Annual Cycle

Of all SEVIRI scans and MODIS overpasses in the year between February 2004 and January 2005 there were 2239 timeslots in which both sensors concurrently (± 6 minutes) observed a portion of Africa. No fire pixel in the training dataset exists between 0300 and 0630 GMT nor between 1500 and 1900 GMT, due to the absence of a MODIS overpass. Daytime detections accounted for 95% of the total fire counts and 96% of the total FRP within in the training dataset for both MODIS and SEVIRI. Overall SEVIRI detected 20% of the total yearly fire pixel count, and measured 50% of the total yearly FRP compared to MODIS.

Ratios of fire pixel count and FRP were most variable at the instantaneous scale and ranged from 0.0 to 1.27 and from 0.0 to 4.86, respectively ('observation ratios' ϕ_{count} and ϕ_{FRP} in Figure 5.13). This variability in ϕ_{count} and ϕ_{FRP} between consecutive MODIS observations is attributed to the following: i) the dynamic nature and diurnal cycle of fire behaviour, ii) the timing and ground track of the MODIS overpass, iii) the different measured frequency-magnitude distributions associated with fire activity, and iv) the occasionally limited sample of fire pixels used to calculate ϕ_{count} and ϕ_{FRP} . The temporal profiles already presented in 4.3 demonstrate the combined effects of the MODIS overpass time, ground track, and swath width on the diurnal cycle of measured FRP.




Figure 5.13: Temporal profiles in the ratios between SEVIRI and MODIS of fire pixel count, (ϕ_{Count}) and FRP (ϕ_{FRP}). Using fire pixels within the training dataset, the ratios are calculated within five temporal windows ranging from the instantaneous scale to one year.

Figure 5.14 shows the distribution of ϕ_{FRP} with respect to the FRP measured by SEVIRI and by MODIS. Of note are the two extreme groups of observations with ϕ_{FRP} greater than 1.0 and ϕ_{FRP} less than 0.1. Though each cluster spans three orders of magnitude, the range of FRP_{SEVIRI} with $\phi_{FRP} > 1.0$ was shifted an order of magnitude higher than the range of FRP_{SEVIRI} for which $\phi_{FRP} < 0.1$, while for the MODIS data the opposite behaviour is observed. The characteristics of these two clusters are separated as follows:

- For an identical value of scene-integrated FRP_{SEVIRI} , observations with ϕ_{FRP} less than 0.1 had a greater absolute number of MODIS detections as well as lower fire pixel count ratios. Furthermore 52% of the observations with $\phi_{FRP} < 0.1$ had frequency

magnitude distributions that were composed entirely of SEVIRI fire pixels less than 56 MW.

- The scenario at which FRP_{SEVIRI} was 4.9x greater than FRP_{MODIS} occurred at an observation with a low absolute number of MODIS detections ($n_{MODIS} = 9$), a high count ratio ($\phi_{FRP} = 0.78$), and captured a thermal distribution in which pixels greater than 56 MW accounted for 90% of FRP_{SEVIRI} .




Figure 5.14: Ratios of FRP, ϕ_{FRP} , as a function of the FRP measured by SEVIRI (left) and MODIS (right). Ratios are identical to those presented in Figure 3, and are separated by the width of the temporal window in which the fire pixels were aggregated; either on an observational ($n=2239$), daily ($n=365$), weekly ($n=52$), or monthly basis ($n=12$).

Given the variability of the instantaneous ratios in the training dataset, and the limited number of MODIS overpasses in a single day, diurnal cycles of ϕ_{count} and ϕ_{FRP} could not easily be discerned. However, seasonal patterns of ϕ_{count} and ϕ_{FRP} were discerned after accumulating fire pixels into non-overlapping intervals of one-day, one-week, and four-weeks (Figure 5.13 and Figure 5.14). The variability of the instantaneous ratios narrowed as more in-scene radiant energy was measured; and as an example ϕ_{FRP} converged from over four orders of magnitude between low and moderate measures of FRP_{SEVIRI} to values within 0.4 and 0.9 for temporally aggregated measures of FRP_{SEVIRI} greater than 1×10^5 MW (Figure 5.14a). The temporal superposition of the frequency magnitude distributions not only enhanced the thermal signal above the background, but due to the overpass times and the ground tracks of the MODIS swath, the wider temporal windows coalesced the ratios that were calculated i) at different times in the diurnal cycle of fire behaviour, and ii) at different geographic locations. Thus the extreme variability in the ratios at the instantaneous scale was moderated as the temporal window was widened, and this effect can be most clearly seen in Figure 5.13. Temporal windows above that of the individual MODIS observations include data from all four MODIS passes typically available for any particular location per day (i.e. 1:30am; 10:30am; 1:30pm and 10:30pm local equator crossing time).

Weekly and monthly ratios of ϕ_{count} and ϕ_{FRP} show vary with the total FRP detected by SEVIRI, but the relationship is imperfect (e.g. Figure 5.14a), and analysis of the seasonal trend in ratios shows that they are loosely coupled to the migration of fire activity over the continent. In Figure 5.13, the elevated ratios ($\phi_{count} > 0.2$ and $\phi_{FRP} > 0.5$) seen at the beginning of February 2005 (Day 1) and also at the end of November through December (Days 300 – 336) are associated with fire activity in the latitudinal belt between 3 and 12° N in Sierra Leone, Guinea, Ghana, and in particular in Central African Republic and Sudan. Similarly, elevated ratios of ϕ_{count} and ϕ_{FRP} in June and July (Days 125 – 175) are associated

with the latitudinal belt between 4 and 20 °S, and in particular the northern part of Angola. The depressed ratios ($\phi_{count} < 0.2$ and $\phi_{FRP} < 0.5$) correspond to the weaker fire activity during the transition between the Northern and Southern hemispheres.

Yearly ratios calculated at 5.0, 1.0 and 0.25° grid cell resolutions illustrate the spatial patterns of ϕ_{count} and ϕ_{FRP} across the African continent (Figure 5.15). Again the relationships between the absolute number of fire pixel counts and ϕ_{count} and between FRP and ϕ_{FRP} were relatively weak. As described above, the ratios at different locations were representative only of the time in which the areas burned. Grid cells at 5° resolution were large enough to span different land cover types, land use practices, and ultimately fire regimes and therefore fail in some respects to adequately capture the inherent spatial variability of the ratios. Conversely however, a higher grid cell resolution can result in noisy ratios that fail to obtain enough statistical samples to reduce the inherent scene-to-scene variability (a feature analogous to the temporal sampling issues demonstrated in Figure 5.13). Similar to the expansion of the temporal window demonstrated there, the aggregation of fire activity within relatively large 5° grid cells moderated the ratios that otherwise can be dominated by localized hotspots at sub-5° grid cell resolutions.




Figure 5.15: Yearly sum of FRP_{SEVIRI} at 1° grid cell resolution (upper left) and yearly ratios of FRP_{SEVIRI} to FRP_{MODIS} (ϕ_{FRP}) evaluated at 5.0, 1.0 and 0.25° grid cell resolutions. Open boxes with solid black outlines indicate null ratios where MODIS detected at least one fire pixel, but SEVIRI did not. .

In Figure 5.15, clear spatial patterns in ϕ_{count} and ϕ_{FRP} become visually distinguishable at the 1° grid cell resolution, as compared to the 5° resolution. Furthermore, as with the lower density of fire pixels that surround regions of high fire activity, a higher number of grid cells at this finer spatial resolution had null ratios where MODIS detected fire pixels, but SEVIRI did not (indicated by the open boxes). Of note in Figure 5.15 is that the spatial pattern of ϕ_{FRP} at 0.25° resolution becomes rather noisy, with the variability reinforced due to the smaller sample size that is influenced more by individual combustion events. At this spatial scale, the finest tested here, the small grid cell size and uncertainties in the registration of the fire pixel centres also become increasingly important. Fire pixels that in actuality represent the same fire on the ground might be successfully detected by SEVIRI and MODIS, but at this grid-cell size there is an increased chance they could be erroneously located in different (adjacent) grid cells.

5.2.2.3 *Potential Adjustment of SEVIRI Gridded FRP Data for the Effect of Undetected Fires*

Two methods were tested for adjusting the observed SEVIRI FRP measurements to what they would have been had MODIS been the observing instrument. Before this, a non-spatially explicit set of continent-wide ϕ_{FRP} ratios were constructed via temporal interpolation of the data shown in Figure 5.13.

(a) Interpolation of the Ratios within the Training Dataset

Based upon the variability of the ratios presented in Figure 5.13, an interval of one week was selected as the minimum temporal window within the training dataset at which there were sufficient number of fire pixels detected by SEVIRI and MODIS *at the overpass times and spatial coverage of MODIS* to i) overwhelm influences of detector sensitivity, algorithm performance, and random variability of fire behaviour at observations of low fire activity, ii) form well structured frequency distributions of FRP, and iii) capture continental trends in the ratios rather than location-specific patterns associated with isolated swaths. The first method for adjusting SEVIRI active fire detections yielded 365 rolling weekly ratios calculated at 1200 GMT each day (Figure 5.16). The rolling weekly ratios shared the same macroscopic trend as the 52 discrete weekly ratios, but also contained microstructure associated with significant fire events occurring at daily resolution. Ratios specifically at SEVIRI timeslots (indicated by the lines connecting the 365 rolling weekly ratios in Figure 5.16) were retrieved by simply linearly interpolating between the ratios at 1200 GMT obtained from Equation 5.2. Since this method offered no predictive capability it could not be independently validated with data collected outside the training dataset. Instead these interpolated ratios were used to evaluate the monthly grid products.




Figure 5.16: Temporal profile of the ratios between FRP_{SEVIRI} and FRP_{MODIS} , ϕ_{FRP} . The 52 discrete weekly ratios were calculated within non-overlapping temporal windows that were each 7 days wide. The 365 rolling weekly ratios were calculated within a moving weekly window such that six of the seven consecutive days overlapped. Ratios used to adjust the 2004/05 SEVIRI dataset at full temporal resolution and continental coverage were determined by linearly interpolating between the rolling weekly ratios assigned each day at 12:00 GMT.

(b) Development of the Monthly Gridded Ratio Products

Spatially explicit monthly ratios of ϕ_{count} and ϕ_{FRP} developed within the training dataset are presented in Figure 5.17 and Figure 5.18, respectively.




Figure 5.17: Monthly-gridded ratios of fire pixel counts measured between SEVIRI and MODIS (ϕ_{count}). Hollow grid cells with a black outline indicate a ratio of zero where MODIS detected fire pixels, but SEVIRI did not.




Figure 5.18: Monthly-gridded ratios of FRP measured between SEVIRI and MODIS (ϕ_{FRP}). Hollow grid cells with a black outline indicate a null ratio where MODIS detected fire pixels, but SEVIRI did not.

(c) Comparison of the temporal and spatial adjustment methods

As an evaluation exercise, the 12 monthly grid products shown in Figure 5.17 and Figure 5.18 were used to adjust the SEVIRI fire pixels counts and observed FRP at the full 15-minute temporal resolution and continental coverage between February 2004 and January 2005. Comparisons between the interpolation of the rolling weekly ratios described in (a) above, and the application of the monthly grid products described in (b) above are presented in Figure 5.19. Although the training dataset (as a subset of the full SEVIRI dataset) supplied the ratios that were both interpolated as well as stored in the monthly grid product, and so the validation cannot be considered fully independent, it is still reassuring that the results from application of both methods show relatively good agreement.




Figure 5.19: Comparisons between two of the methods used to adjust the 2004/05 SEVIRI dataset at full temporal resolution and continental coverage ($n=31616$ observations). Fire pixel counts (left) and FRP (right) were adjusted via interpolation of the rolling weekly ratios and via the monthly grid product. Both the interpolated product and the grid product were derived from concurrent and collocated fire pixels within training dataset.

A fully independent validation of the 5° grid product was performed using a separate dataset from August 2007. Each of the 102 concurrent and collocated matchup observations in August 2007 consisted of a single MODIS ground track that intercepted on average 6 grid cells with a range between one and 18 grid cells. For each concurrent and collocated observation, the FRP_{SEVIRI} in each individual 5° grid cell was summed, divided by the ϕ_{FRP} from the August 2004 grid product, then summed again over all grid cells to yield the total, adjusted FRP_{SEVIRI} on an observational basis. The adjusted FRP_{SEVIRI} was then compared to the actually measured FRP_{MODIS} . The level of agreement will depend on how similar the fire activity in August 2007 is, in terms of the ratio of small to large fires and their spatial distributions, to that seen in August 2004.

Figure 5.20a shows the results of this comparison, and the linear regression fit to the instantaneous observations in Figure 5.20a exhibits relatively good agreement ($r^2=0.83$), the slope of the OLS line of best fit exceeds unity (slope = 1.23) and indicates that using the August 2004 grid product to adjust FRP_{SEVIRI} in August 2007

ultimately overestimates FRP_{MODIS} . However, it overestimates by a smaller factor than the unadjusted SEVIRI data underestimates FRP_{MODIS} by (in that case the slope of the OLS line of best fit is 0.47) and so indicates that applying the adjustment factor (i.e. ϕ_{FRP} determined from the 2004 dataset) does improve the level of agreement between the SEVIRI and MODIS measures of FRP. Furthermore, based upon the relationship between the measured FRP_{SEVIRI} and FRP_{MODIS} at the observational scale (Figure 5.20a), it appears that a simple linear scalar would suffice to adjust SEVIRI-derived FRP to those made by MODIS.




Figure 5.20: Validation of the August 2004 grid product using fire pixels detected by SEVIRI and MODIS in August 2007. Comparisons are presented between FRP_{MODIS} and the adjusted FRP_{SEVIRI} (black circles) and the un-adjusted FRP_{SEVIRI} (hollow boxes). The linear regression fit to the 102 concurrent and collocated observations is valid regardless of the grid cell resolution at which FRP_{SEVIRI} was adjusted (a, upper left). The spatially explicit effects of applying the August 2004 monthly grid product are also presented at the native 5° grid cell resolution (b, upper right), at 1.0° grid cell resolution (c, lower left) and at 0.25° grid cell resolution (d, lower right). Three outliers (i.e., three grid cells) removed prior to fitting the linear regression at 1.0° grid cell resolution are highlighted by red circles (c, lower left).

Summing over the entire month, the total adjusted SEVIRI data for August 2007 overestimated the monthly MODIS fire counts by 18%, and overestimated the monthly MODIS FRP by 37%. Interestingly the monthly values in the training dataset

for ϕ_{count} and ϕ_{FRP} in August 2004 were 16.9% and 44.5%, whereas in August 2007 these percentages remained very similar at 16.4% and 46.0%, respectively. The consistency of these figures suggest that, in fact, differences between the predicted FRP_{MODIS} (i.e. the adjusted SEVIRI FRP observations) and the actual measurements of FRP_{MODIS} at the observational scale are very likely attributable to interannual differences in the exact spatial distribution of fires and consequently ϕ_{count} and ϕ_{FRP} , rather than to their overall magnitude (i.e. many of the fires in August 2007 were in a different grid-cell than in August 2004, and these different cells had different ϕ_{count} and ϕ_{FRP} values).

The adjusted FRP_{SEVIRI} and measured FRP_{MODIS} at 5° resolution were also compared at the grid cell level. Fire pixels detected by either SEVIRI or MODIS during the 102 individual observations in August 2007 were contained within 636 grid cells at 5° resolution (i.e., grid cells with the same extents at different time slots were considered individually). The linear regression relating the adjusted FRP_{SEVIRI} and the measured FRP_{MODIS} for each of the 636 grid cells at 5° resolution is presented in Figure 6.13b. Again the positive bias indicates that adjustments of FRP_{SEVIRI} using the August 2004 grid product served to over predict the FRP_{MODIS} actually measured in August 2007. Furthermore the correlation coefficient ($r^2 = 0.63$) supports the inference of the spatial heterogeneity of the adjustments as stated above for the observation scale. Once again the true, rather linear, relationship between the measured FRP_{SEVIRI} and FRP_{MODIS} implies that at the grid level a simple scalar would suffice to adjust one to the other.

Finally, the August 2004 grid product of ratios was applied to the instantaneous measurements of FRP_{SEVIRI} in August 2007 summed at 1° and 0.25° resolution. At the observational scale, the relationship between the adjusted FRP_{SEVIRI} and the measured FRP_{MODIS} were identical to those presented in Figure 5.20b, regardless of the grid cell spatial resolution. This is because at the observational scale all energy is accounted for regardless from which grid cell it is emitted. Interestingly, after three outliers were removed from the linear regression, the relationship between the adjusted FRP_{SEVIRI} summed at 1° resolution and the measured FRP_{MODIS} summed at 1° resolution is not too different from the grid-level relationship at 5° resolution (Figure 5.20c). Although the bias changes between scales, the nearly equivalent correlation coefficients (i.e., $r^2 = 0.63$ vs. $r^2 = 0.61$) demonstrates that these two methods of application offer similar predictive capability. These results suggest that the monthly grid products at 5° grid resolution can be applied at 1° resolution without a dramatic loss of confidence in the estimate. At 0.25° , however, the relationship between the adjusted FRP_{SEVIRI} and measured FRP_{MODIS} per grid cell disintegrates (Figure 5.20d), and we conclude that a 1° grid cell resolution is thus the highest spatial resolution appropriate for the SEVIRI gridded FRP product that will include the adjustment for smaller ‘undetected’ fires.

Also analysed was the value of deriving time-specific values of ϕ_{count} and ϕ_{FRP} from the 2004 matchup datasets appropriate for the different MODIS overpass times (Figure 5.21). Due primarily to the preponderance of low FRP fires during morning and evening overpass times when compared to daytime overpass times, the ratios of both MODIS to SEVIRI fire pixel counts and FRP are, on average, lower at these times. However, when the additional value offered by these diurnal ratios was tested

using the August 2007 validation data (via modulation of the 2004-derived grid-cell ratios by the value appropriate to the particular MODIS observation time being considered), the level of agreement between the ‘adjusted’ FRP_{SEVIRI} and ‘observed’ FRP_{MODIS} was the same as that shown in Figure 5.20c. Further work is needed to explore this issue and identify whether the fixed grid-cell method is the optimum approach for deriving such adjustments.




Figure 5.21: Diurnal pattern of ratios calculated using all concurrent and collocated fire pixels detected by SEVIRI and MODIS over Africa during 2004. Ratios are categorized into the morning and afternoon overpasses of AQUA and TERRA.

5.2.3 Analysis of Ecosystem-specific Biases

Figure 5.22 shows the land cover classification from the GLC 2000 data set and the fractions of fires detected in each land cover type for the MODIS MOD14 and SEVIRI data sets. There is generally good agreement between the two data sets with maximum differences of 4% attribution (maximum relative error of 25%). SEVIRI has a tendency to detect relatively more fires in mosaic forests and deciduous woodlands compared to MODIS, while MODIS detects more fires in shrublands and croplands. For the most part this can be explained by the different detection thresholds of the two instruments (a lower limit of 20-40 MW FRP for SEVIRI and 7-10 MW FRP for MODIS) and the sorts of fires dominating each particular landcover class. In particular, cropland fires tend to be very small (i.e. have low FRP) and are thus more likely to be missed by SEVIRI data set than by MODIS.

With the present analysis it remains unclear to what extent the (small but significant) differences in the vegetation-type specific fire detection efficiency are related to the viewing geometry of the two instruments. This could in future be tested by analyzing fires in similar vegetation classes which occur in different regions on the African continent (for example cropland fires in the Sahel zone versus those in Northern Africa or South Africa).




Figure 5.22: GLC 2000 land cover classification and relative frequency of fire detection in each land cover type for MODIS and SEVIRI data.

5.2.4 Effects of Viewing Geometry

No specific analysis was performed to investigate the effects of the viewing geometry. However, various results reported in the other sub sections point to a decreasing detection efficiency and reduced FRP accuracy for pixels far away from the sub-satellite point (see for example Figure 5.28).

5.2.5 Effects of Saturation

To quantify the extent of MIR channel sensor saturation, the KCL FRP product data of February, May and August 2004 were used. It was found that SEVIRI detected 1.3 million fire pixels in February 2004 across Africa, of which only 0.1% were saturated in the level 1.5 data. In May and August the numbers were 0.9 million (0.5% saturated) and 1.7 million (0.6% saturated) respectively, and thus saturation when taken over the entire dataset, is seen to be a relatively minor occurrence. However, on a per-fire basis saturation levels can be more than an order of magnitude greater, even potentially affecting 25% of the fire pixels recorded over very intense/large fires, and on a per-slot basis at the time of peak fire activity saturation typically affects a few percent of the detected fire pixels.

Figure 5.23 shows the results of the SEVIRI ‘special operations mode’ experiment with regard to instrument saturation. In this case the Meteosat-8 SEVIRI instrument was operated with an extended dynamic range and with a rapid 5-minute scan over southern Africa during September 2007, at the peak of the fire season in this region. The plots show a comparison of total sub-scene FRP when the instrument is operated in low gain mode (essentially without any saturation of the MIR spectral channel) as compared to the same data with the saturation effect artificially induced. Results are not currently available for data collected around the midday period, but the plot indicates that saturation is a more prevalent phenomenon at the location of peak burning than is suggested by the continent-wide data above. Towards the diurnal peak, approaching 5% of detected fire pixels are saturated, resulting in an FRP underestimation of around 10%. At night this increases up to 8% and 40% respectively, though the total sub-scene FRP at night is low so the overall effect on the cumulative time-integrated FRP (i.e. the FRE) would be minimal and the lower levels of FRP percentage underestimation present during the day cause a far greater total effect. Analysis of the individual pixel brightness temperatures confirms that under this extended dynamic range operation (max MIR channel BT = 375 K) less than 0.002% of the total fire pixels detected over the day are saturated, and thus operating SEVIRI in such a mode would effectively negate any impact of pixel saturation on the FRP results.




Figure 5.23: Data from the SEVIRI 'special operations mode' experiment conducted on 4 September 2007, when the Meteosat 8 SEVIRI instrument was put into low-gain mode. The figure compares the sub-scene cumulative FRP recorded in this 'unsaturated' mode to that which would have been recorded under normal conditions (i.e. with saturation present for pixels with a MIR BT of 335 K or greater), and the figure also shows the % of pixels that would have been saturated, and the degree of FRP underestimation caused by this saturation, also expressed as a percentage.

5.2.6 Effect of SEVIRI Processing Chain

Table 5-1 shows the impact of the level 1.0 to level 1.5 conversions on the number of saturated SEVIRI pixels. It is very clear that the smoothing employed in the spatial regridding of the level 1.0 data results in a much lower number of saturated pixels in the output level 1.5 data. As a consequence, under normal observation conditions there is likely to be more FRP underestimation present than is suggested by the number of saturated pixels present in the level 1.5 product.

Date and time	Level 1.0 3.9 BT saturation range (DN)	Level 1.5 Max 3.9 BT (Kelvin)	Level 1.0 Number of Saturated Pixels	Level 1.5 Number of Saturated Pixels
20040712081503	334.22 - 334.49 (1023)	335.56	8	4
20040712083003	334.21 - 334.49 (1023)	332.20	64	27
20040712084504	334.49 (1023)	335.56	1	1
20040712090004	334.21 - 334.49 (1023)	335.56	9	1

Table 5-1: Pixel saturation statistics for level 1.0 and level 1.5 versions of SEVIRI fire scenes.




Figure 5.24: Data from the SEVIRI 'special operations mode' experiment conducted on 4 September 2007, when the FIR filter was removed from the Meteosat 8 SEVIRI instrument but kept on the Meteosat 9 SEVIRI instrument that observed the same area almost simultaneously. The figure shows the MIR brightness temperatures recorded over the same fire by both systems, and the transect illustrates the effect of the FIR filter negative side lobes.

Data from the SEVIRI 'special operations mode' experiment is shown in Figure 5.24 with regard to the on-board application of the FIR filter. In this case the FIR filter was not applied to the Meteosat-8 data, and the improved fidelity of the observations of this fire can be clearly seen when compared to the contemporaneously recorded Meteosat-9 data upon which the FIR filter was used.

The impact of this FIR filter on the retrieved FRP observations was assessed primarily through simulations, calculated using the steps shown in Figure 5.25. An example output from the simulation of the SEVIRI observation process, which included representations of both the SEVIRI point spread function (PSF) and finite impulse

response (FIR) filter and a set fire size and temperature, is shown in Figure 5.26. A real SEVIRI active fire observation with the FIR filter employed is shown for comparison. The similarity of these two representations is apparent, particularly in terms of the increased radiance at the fire pixels themselves and the depressed radiances at the surrounding pixels due to convolution with the FIR response filter and its negative side lobes. The primary difference in the two representations is that in the model a spatially ‘flat’ background (i.e. constant brightness temperatures) are used, whereas the background in the true SEVIRI data has some variability due to ambient surface temperature variations. These depressed radiances can induce a higher brightness temperature variability in the ambient background window around fire pixels, and thus can impact the likelihood of the fire pixels actually being detected (since the algorithm scales certain of the detection criteria by a measure of the variability of signals found with the surrounding background window).




Figure 5.25: The major steps involved in simulating SEVIRI active fire observations using a spatially invariant background temperature of 300 K.




Figure 5.26: The SEVIRI point spread function (E-W) and the finite impulse response filter, together with a SEVIRI observation of an active fire modelled with these as compared to a real SEVIRI active fire observation. The effect of the negative side lobes (resulting in depressed radiances either side of the fire) induced by the FIR filter can be seen in both, and their impact is shown quantitatively by the east-west transect.

The effect of the SEVIRI observation process on the quantification of FRP was assessed using simulated SEVIRI active fire data of the sort shown Figure 5.27, calculated for differing fire size and temperature distributions (and so different FRP values). The SEVIRI PSF acts to smooth the fire radiance out over neighbouring pixels and can result in fire pixels at the edges of the fire actually contain some of the fire energy output, but with signals that do not allow them to be detected as fire pixels. This will cause underestimation of FRP compared to the raw FRP error (induced by the Planck function approximation), and the magnitude of this is shown in the “FRP without FIR” error value in Figure 5.27. In some cases its magnitude actually cancels out the effect of the Planck function approximation. The additional application of the FIR filter, expressed by the “FRP level 1 error” makes the most significant difference to the degree of error in the case where the fire forms the largest proportion of the pixel (1%), but in fact all such fires would have in reality resulted in a saturated SEVIRI pixel in any case, so the effect would have been outweighed in magnitude by the saturation impact. For non-saturated fires covering 0.1% and 0.01% of the SEVIRI pixel field of view (FOV), application of the FIR filter has less of an effect. It acts in two ways, with the positive side lobes directly giving rise to additional fire pixels and the negative side lobes having an adverse affect on the background characterisation involved in the fire detection algorithm (and thus potential leading to FRP overestimation via depression of the background temperature estimate). The lowest FRP fires shown here are those where the fire size is 0.01% of the SEVIRI FOV (rightmost plot), and for fires of this size only those with a fire-

effective temperature of ~ 800 K or higher would in fact be detectable under real conditions (i.e. with a varying ambient background temperature). Nevertheless, the Figure indicates that such low FRP but still potentially detectable fires may in theory have their FRP underestimated by up to 60% under the conditions examined here, due primarily to the effect of the sensor PSF smoothing the fire radiance out over a number of pixels, and to some of these pixels failing to be detected as fire pixels. At such low signals, the effect of the FIR filter is negligible, and thus the FRP underestimate is equal with and without the FIR filter.




Figure 5.27: The effect of the SEVIRI observation process on the retrieval of FRP for fires of different effective temperatures and pixel proportions. The errors in FRP is shown due to the fourth order approximation to the Planck function only, to the complete modelled level 1 observations process (PSF and FIR filter) and to the observations without the FIR filter.

In order to determine the effect when the ambient background temperature is allowed to vary in a realistic way, BIRD data were used to provide the MIR background radiances for the simulations, upon which the modelled fire spectral signals were superimposed. The resulting array subject to the same SEVIRI observation process as described above. Figure 5.28 shows the resulting simulated SEVIRI MIR and TIR channel data, whilst Figure 5.29 shows the degree of error for the range of fire FRP's that are detectable from SEVIRI. The use of the varying background temperature has increased the background variability measure, thus increasing certain of the fire pixel detection algorithm thresholds that are scaled by this parameter, consequently making any low signal fire pixels less likely to be detected. This has resulted in a decreased total FRP measure, since more of the true fire pixels caused by spreading out of the fires radiance into surrounding pixels due to the PSF and FIR filter convolutions remain undetected. For low FRP fires, this results in a greater level of FRP underestimation when the varying background is used, as compared to the flat (spatially invariant) background.




Figure 5.28: Simulated SEVIRI active fire TIR and MIR channel data, derived from higher spatial BIRD imagery to provide the ambient background measurements, and with a modelled fire spectral radiance signal superimposed.




Figure 5.29: Degree of underestimation induced by the SEVIRI observation process on simulated fires of the sort depicted in Figure 5.28 and which have been modelled with a varying ambient background temperature (taken from BIRD imagery) and a spatially invariant 'flat' background temperature. The error due only to the MIR radiance method alone is also shown.

Finally, Figure 5.30 shows the results of the SEVIRI ‘special operations mode’ experiment with regard to data collected simultaneously by Meteosat-8 and Meteosat-9, firstly when the former system had the FIR filter present and then when it was removed. Under standard operations, Meteosat-8 measures per-scene FRPs on average around 10% lower than those recorded by Meteosat-9. On removal of the FIR filter, this difference is increased to around 22%, due to a combination of the removal of the influence of the –ve side lobes, the fact that some fire pixels remain undetected in the non-FIR filtered data since they have lower MIR radiances (see Figure 5.24) and to the effect of the removal of the FIR filter on the extent on signal saturation.




Figure 5.30: Comparison of Meteosat-8 and Meteosat-9 per-scene FRP data recorded simultaneously over southern Africa during the Meteosat-8 ‘special operations mode’ experiment. Greater discrepancies are seen when the FIR filter is removed from the Meteosat-8 SEVIRI (Meteosat-9 had the filter always applied).

5.3 Results of Land SAF Product Validations

5.3.1 Comparison to KCL Product

In terms of active fire pixel detection for each slot of data in August 2007, on average 12.7% of the fire pixels detected by the KCL FRP product in a slot did not have a corresponding LandSAF product fire pixel, whilst in 22.7% the reverse occurs. Whilst these figures may seem high, these averages are hugely influenced by night-time observations when there are very few fire pixels. During daytime conditions, where fire pixel counts and total FRP are typically orders of magnitude greater than at night and where the non-detection or false-detection of individual fire pixels is thus far less significant, the KCL and Land SAF products agree within 0.2% and 0.3%. Therefore in general the products show very similar performance characteristics in terms of fire pixel detections at the times when there are significant numbers of fires.

Figure 5.31 shows that when both the Land SAF and KCL products detect the same fire pixels, their FRP is retrieved almost identically, with a very slight positive bias in the Land SAF product most likely due to the specific calibration methods used in each data processing chain. The level of difference is found to be similar when summing all FRP observed in each product over the complete LandSAF southern African region (the OLS line of best fit is $y = 1.006x + 1336$, $r^2 = 0.99$), and thus the LandSAF products for this region are essentially expected to have the same bulk error characteristics and accuracies as the original KCL product.




Figure 5.31: FRP comparison between the Land SAF FRP product and that generated at KCL from EUMETCAST-received SEVIRI data of the same imaging slots. The figure shows the per-pixel comparison for the Land SAF southern African region, where only data from fire pixels identified in both products are included in the match up dataset.

5.3.2 Comparison to MODIS

In August 2007 over South Africa, errors of omission in terms fire detection were 68%, i.e. 68% of MODIS-detected fire pixels had no corresponding SEVIRI fire pixel within the Land SAF product (compared to 54% in the KCL product for August 2004, see section 5.2.2.1). Again it should be remembered that a large number of these MODIS pixels would have been in clusters, such that many 'missing' MODIS fire pixels might have corresponded to only one 'extra' SEVIRI pixel. Errors of commission were low, with only 2% of the Land SAF products fire pixels having no matching MODIS pixel (compared to 6-8% in the KCL product). On a per-fire basis, there is a strong correlation between the FRP measures made by SEVIRI and by MODIS (Figure 5.32), and this is in agreement with the results of the SEVIRI to MODIS per-fire FRP comparison made with the original KCL product (Figure 6.4).

On average, over the month, in the southern African region the Land SAF algorithm for SEVIRI detects 65% of the total FRP that MODIS detects when observing the same area almost simultaneously, this underestimate being a result of the aforementioned inability of SEVIRI to detect the lowest FRP fire pixels, as outlined earlier. Figure 5.33 shows the relationship between SEVIRI- and MODIS-detected cumulative FRP on a per-MODIS scene basis, and the strong linear correlation found here attests to the similarity of the Land SAF product and the KCL FRP product whose swath-based relationship to MODIS was previously shown in Figure 5.12.




Figure 5.32: A comparison of per-fire FRP derived from SEVIRI and MODIS observations of 187 fires observed near-simultaneously by each sensor. Fires are designated as contiguous clusters of active fire pixels and SEVIRI FRP measured were taken from the Land SAF FRP per-pixel products of southern Africa collected in August 2007.




Figure 5.33: Relationship between regional-scale inter-scene FRP derived from all spatially matched, contemporaneous SEVIRI and MODIS observations for the south African region in August 2007, where the MODIS swath is taken as the observation area and the Land SAF per-pixel FRP product was used as the SEVIRI record. The OLS linear best-fit passing through the origin is shown (bold line), along with the 95% confidence intervals on the mean (dotted line) and on the prediction of y from x (outermost lines). In each case SEVIRI generally underestimates regional-scale FRP, primarily due to the non-detection of the lowest FRP fire pixels, many of which MODIS can detect.

Agreement between the area based results for the South American region is far worse than for the African regions, and within a given time-period there are also far fewer matchups due to the area viewed by SEVIRI having fewer fires than does southern Africa and to the extreme viewing angle making fire pixels harder to detect by SEVIRI. Reflecting this degraded performance compared to the southern African region, on average in the South American Land SAF region, fire pixel errors of omission were 79% with respect to MODIS (larger than the southern African case), whilst errors of commission were around the same at 2.5%. Figure 5.34 shows the level of agreement between the MODIS and SEVIRI-derived FRP measures over south America, at the level of individual fire-clusters. The agreement is seen to be far worse than that noted over South Africa seen in Figure 5.32.




Figure 5.34: A comparison of per-fire FRP derived from SEVIRI and MODIS observations of fires observed near-simultaneously by each sensor over South America. Fires are designated as contiguous clusters of active fire pixels and SEVIRI FRP measured were taken from the Land SAF FRP per-pixel products of South America collected in July 2007.




Figure 5.35: Relationship between regional-scale inter-scene FRP derived from all spatially matched, contemporaneous SEVIRI and MODIS observations for the south American region in July 2007, where the MODIS swath is taken as the observation area and the Land SAF per-pixel FRP product was used as the SEVIRI record. The OLS linear best-fit passing through the origin is shown (bold line), along with the 95% confidence intervals on the mean (dotted line) and on the prediction of y from x (outermost lines). In each case SEVIRI generally underestimates regional-scale FRP, primarily due to the non-detection of the lowest FRP fire pixels, many of which MODIS can detect.

Figure 5.35 indicates the similarly relatively poor performance of the SEVIRI-derived area FRP estimates, as compared to simultaneous observations from MODIS made across the same spatial extent. We conclude that extreme viewing angles present in SEVIRI views of South America have significantly degraded FRP product performance.

5.4 Results of Validation Based on the Impact Studies

Global atmospheric monitoring systems like the one developed in the GEMS project (Hollingsworth et al. 2008) for the forthcoming GMES Atmospheric Service (GAS) envisaged by the European Commission and ESA require information on the wildfire emissions of several species as input. Because of the high temporal variability of fire activity the emission input has to be generated from fire observations. None of the currently available fire emission products satisfies all requirements of the monitoring system, in terms of accuracy, spatial and temporal coverage and resolution, timeliness, and operational availability (Kaiser et al. 2006). The SEVIRI FRP product promises to improve the available fire emission input in several aspects:

1. improved temporal resolution, compared to products based on low Earth-orbit (LEO) observations,
2. improved accuracy, compared to hot spot products
3. operational availability with sufficient timeliness for real-time forecasting.

The impact of the first aspect has been studied using the GEMS CO₂ monitoring system (see section 5.4.1) and it was a key aspect of a high-resolution study of impacts from Greek forest fires in the summer of 2007. The impact of the, theoretically, improved accuracy of the emission estimates is tested in a study by FMI, which compares the impact of using the MODIS thermal anomaly (TA) or FRP product in the FMI Fire Assimilation System and the HIRLAM regional air quality forecasts. The overall quality of the SEVIRI FRP product is also tested by comparison to the community-standard monthly fire emission inventory GFEDv2. An end-to-end case study of aerosol plumes emanating from forest fires in Greece in August 2007 demonstrates the capabilities of the real-time monitoring based on the GEMS system and SEVIRI FRP.

5.4.1 Impacts of Temporal Resolution - Study of Sensitivity to Temporal Resolution of Emissions: Global Carbon Dioxide Modelling of 2004

Examples of the simulated CO₂ fields on 6 February 2004 are shown in Figure 5.36. They are expressed in total column (TC) CO₂, defined as the pressure-weighted vertical average mixing ratio [ppm]. The top plot shows the CO₂ field for the simulation without fire emissions and the bottom one shows the field resulting from

1-hourly emissions. Both fields exhibit the typical inter-hemispheric gradient observed in winter. The contribution of the fire emissions is evident as an enhancement over central Africa.




Figure 5.36: Total column CO₂ for simulation without (top) and with (bottom) fire emissions.

The contribution of the fire CO₂ emissions to the CO₂ field is shown directly in Figure 5.37. It is computed as the difference between modelled TC CO₂ with fire emissions at 1-hour (top) and 8-day (bottom) time resolution and a simulation without any fire emissions over Africa. Note, that the total emissions within each 8-day period is the same. Since the 8-day time resolution is the current GEMS baseline input (from the GFEDv2 inventory), the differences between the 8-day and 1-hour fire simulations describe the error that the current system suffers due to the limited temporal resolution of the fire emission input. Conversely, it can be interpreted as the positive impact that

usage of the SEVIRI FRP product will have on the CO₂ fields modelled with the GEMS system.

Neglecting the temporal variation of the fires during each 8-day period results in a visibly smoother fire contribution to the CO₂ field. Furthermore, the CO₂ “plume” is shifted southwards in the simulations using the 8-day fire product. This is consistent with relatively less fire activity during the first few days of the 8-day period starting on 2 February and more fire activity later on, combined with a general transport southwards, which is evident upon closer inspection of the simulations, but not explicitly shown in this report.




Figure 5.37: Fire emission contribution to total column CO₂ for emission with 1-hour (top) and 8-days (bottom) emission time resolution.

The impact of providing CO₂ fire emission input with the various time resolutions is shown in Figure 5.38. It is computed as difference between the fire emission contributions to the TC CO₂ field in the three simulations with fire emissions. For example, the top plot shows the difference between the contributions in the simulation using 1-hourly emissions versus the one with 8-daily emissions. The top plot can be interpreted as the error in the CO₂ field that is induced by neglecting the temporal evolution of the fire emissions during 8 day periods.

The middle and bottom plots of Figure 5.38 show the contributions of day-to-day variations and diurnal variations, respectively. They add up to the impact shown in the top plot. The strong North-South dipole over central Africa is caused by the shift in “plume” position mentioned above. It is evidently caused by the day-to-day variability of the fire activity. This also causes small effects that are propagated inter-continently within a few days (the response of less than 0.01 ppm TC CO₂ is however negligible in current CO₂ monitoring applications).

The diurnal variability of fire activity adds finer, more localised structure, as expected. The fine structure has almost the same amplitude as the broader structure induced by the day-to-day variability.

An example vertical cross section of the difference in the CO₂ mixing ratio due to neglecting all fire variability during 8-day windows is shown in Figure 5.39. The difference pattern has a complex structure that stretches across the whole troposphere, which is testament to the intimate link between emission and atmospheric transport variability. The impact is strongest in the boundary layer with values of up to more than ± 4 ppm.




Figure 5.38: Differences in fire contribution to total column CO₂ for emissions with different time resolutions: 1h - 8d (top, Figure 5.37 top - bottom), 1d - 8d (middle), 1h - 1d (bottom).

Cross section of CO₂ 20040206 1200 step 3 Expver exml




Figure 5.39: Vertical distribution of difference in fire contribution to the CO₂ mixing ratio for emissions with different time resolutions of 1-hour and 8-days.

The relative impact of 1-hour temporal resolution emissions as compared to 8-day ones is computed by normalising the observed differences by the contribution of (8-day) fire emissions to the CO₂ field. The result is shown in Figure 5.40. By neglecting the temporal variability, errors between -90% and +70% can be incurred. The difference in the CO₂ fields is also propagated onto the Atlantic, far away from the burning regions. On a hemispheric scale the impact is diluted to about 1% of its typical regional value. Due to the tracer-like properties of CO₂, these results are expected to be valid for all long-lived pollutants in the fire plumes (such as carbon monoxide, organic carbon, etc.).




Figure 5.40: Relative difference of total column CO_2 for different time resolutions. $(1\text{-hourly} - 8\text{-daily fires [ppm]}) / (1\text{-hourly} - \text{no fires} + 1 \text{ ppm})$.

Analyses of simulated aerosol fields on 6 February 2004 and of the simulated CO_2 fields near the end of the simulation period have confirmed the general findings described above (not shown).

5.4.2 Impact of FRP versus Hot Spot Detection

Figure 5.41 compares the geographical distributions of the MODIS thermal anomaly (TA) and FRP product in Northern Europe averaged over several months. The distributions of the resulting emissions of trace gases and aerosol components are proportional to the fire products. The two distributions appear, of course, quite similar. Nevertheless, they also exhibit some differences: FRP has a tendency to show more localised fires, emphasizing individual large events. This is particularly striking in areas with a low fire density like Skandinavia. However, similar differences are expected in areas with high fire intensity, when shorter time periods are analysed.




Figure 5.41: Per-pixel fire TA (left) and FRP (right) over Northern Europe observed by MODIS. The symbol size is proportional to the average value during May-August 2006.

Figure 5.42 shows examples of the modelled atmospheric $PM_{2.5}$ concentration at 20 m height based on emissions calculated from MODIS TA and FRP. Large differences appear over the Iberian Peninsula and around the Baltic Sea. The differences are solely attributed to the different relative strengths of fire emissions arising from the two different MODIS fire observation products. Even though FRP is expected to yield more realistic emission patterns, this is difficult to prove because of the sparsity of validation data. An indication is given in Figure 5.43, which reproduces a true-colour image of the fire plume over the Gulf of Finland that is also evident in the SILAM simulations. The MODIS image shows that the plume is very localised and thick. As expected from the more localised pattern of the FRP product, the atmospheric simulation based on the FRP-derived emissions seems to emphasise the strong plume more than the one based on TA-derived emissions.




Figure 5.42: Atmospheric PM_{2.5} concentrations on 7 August 2006, 6 UTC, predicted by SILAM at FMI, based on MODIS Temperature Anomaly (left) and FRP (right) fire observations.



Figure 5.43: MODIS true colour image of the fire plume in the Gulf of Finland on 7 August 2006. The red triangles denote observed fire temperature anomaly.

Mikhail Sofiev concludes from his analyses of the above kind that:

1. Total estimates (seasonal integrals, regional totals, etc.) can be easily made similar between the FRP and FTA assessments. Adjustments of scaling coefficients (quite poorly known for both) allow this. In particular, we found that coefficients for FRP from Ichoku & Kaufman (2005) are about 2 times too high (as was suspected by the authors themselves).

2. Having the same total values, we still end up with substantially different patterns coming from TA and FRP. TA is much less sensitive to the fire strength but rather to the area covered with the fires.
3. We also found that TA tends to report larger number of small fires, which sometimes seem to be evidently irrelevant (e.g. in areas covered by snow, repeatedly showing up in cities, etc) but sometimes might well be real. FRP is more conservative in number of fires but allows better classification of strong individual events.
4. We decided to run both versions for some time to collect more information regarding the similarities and differences between the emission estimates. Unequivocal conclusions on superiority of one approach are not too easy: the differences tend to sink into observational and modelling noise, so that sometimes assessments of one system clearly prevail but next day the other system might look better.
5. Technicality: reliability and availability of MODIS FRP as a near realtime product was clearly lower than that of TA during most of 2007 but now seems to be getting better.

The TA product contains the information on fire locations like a qualitative hot spot product that is based on channel saturation. Additionally, FTA contains quantitative information on fire strength, i.e. the pixel temperature anomaly [K]. Therefore, it can be expected that the differences between emission estimates based on qualitative hot spot products and FRP are generally larger than the ones found by the FMI study.

5.4.3 Impact on Estimating Fire Emissions

In this section, we show a) results of the comparison of SEVIRI-based monthly carbon emission estimates with data from the Global Fire Emissions Database (GFEDv2) and b) a qualitative comparison of the seasonal pattern of SEVIRI FRP with MOPITT CO profiles.

SEVIRI and GFED give similar results for Africa north and south of the equator, but SEVIRI tends to show slightly lower values overall (Figure 5.44). It is important to note that uncertainties are large in the GFED approach, so no quantitative assessment can be made on the SEVIRI-based emissions performance. The most relevant difference seen between SEVIRI and GFED version 2 is the timing of the emissions peak in both hemispheres, which is diagnosed about one month later in GFED than in SEVIRI. The later timing of the peak appears more consistent with observation of atmospheric trace compounds (see next section), but until now the factors causing the difference between the peak fire occurrence and maximum loading of the atmosphere have not been determined satisfactorily. Preliminary data from GFED3 indicates that GFED2 emissions may have been too high in northern hemispheric Africa, leading to a closer match between SEVIRI and GFED estimates. In southern Africa, however, GFED3 estimates will be higher than GFED2 estimates, which were already higher than SEVIRI-based estimates. The difference is mostly resulting from emission estimates in woodland areas. In principle, the SEVIRI FRP product should be

independent of vegetation type (see also section 5.2.3) so that differences in one particular ecosystem might hint to errors in the GFED system. This requires further proof, however. It is noteworthy, that due to large uncertainties in GFED based emissions, discrepancies between FRP and GFED do not necessarily point at shortcomings of the FRP method.




Figure 5.44: Comparison of monthly SEVIRI based carbon emissions with Global Fire Emissions Database (GFED) versions 2 and preliminary version 3 for Africa north of the equator (top panel) and Africa south of the equator (bottom panel).

Figure 5.45 shows the comparison of interannual variations in SEVIRI FRP with MOPITT CO profiles in the southern hemisphere. The peak CO loading derived from the MOPITT sensor occurs in September for retrievals between 700-1000 mb. Retrievals higher in the atmosphere (250 and 350 mb) indicate that the peak atmospheric CO concentration occurs later (October), though this discrepancy may lie with sensitivity of the averaging kernels at different heights to other factors (e.g. surface temperature). The temporal trajectories of the MOPITT CO concentration and total cumulative monthly FRP (proportional to total fuel burned) in the southern hemisphere are offset from one another, with peak FRP-derived biomass burning total in July and peak CO concentrations in September/October. The shapes of the distribution are, however, extremely similar.

The temporal lag is removed when examining the mean per-pixel FRP, which should be approximately proportional to the mean rate of combustion per grid cell. This suggests that there may be additional information in this parameter, which, with further refinement, might enable better parameterisation of temporal evolution of

emissions factors used to convert fuel consumption measures into emission of trace gases.




Figure 5.45: Annual variation of mean monthly MOPITT CO mixing ratios retrieved for five pressure levels over land between February 2004 and January 2005 in comparison to total FRP (left) and mean per-pixel FRP (right) for southern hemisphere Africa.

5.4.4 End-to-end Use Case Study: Modelling the Greece Fire Plumes of August 2007

This section shows the results of a case study initiated in the FREEVAL project on modelling the smoke plumes from fires occurring in the Mediterranean region in August 2007 using SEVIRI FRP derived fire aerosol emission estimates. It allows for some independent validation of the SEVIRI product and also served to identify the necessary technical processing steps and required product characteristics of the pixel and gridded SEVIRI FRP products. The study set-up is described in section 4.4.4.

Figure 5.46 shows the number of active fires detected over the Mediterranean region by MODIS and by SEVIRI on August 25, 2007, when fire activity was at a peak level. Most fires occurred on the western half of the Greece Peloponnese island. While the MODIS and the SEVIRI products match very well in terms of spatial pattern of fire activity, the SEVIRI product detects much more active fires than the MODIS product. As a result, MODIS distinctively under-represents the spatial expansion of the main clusters of fire activity on Peloponnes island compared to SEVIRI.




Figure 5.46: Active fires (hotspots) detected by MODIS (left) and by SEVIRI (right) on August 25, 2007 over the Mediterranean region.

Two snapshots of simulated optical depth of organic matter and black carbon aerosols, which dominate the smoke optical depth from fire plumes and have comparably smaller other emission sources, are plotted and compared to concurrent MODIS visual images in Figure 5.47. The plots also show the fire activity observed by SEVIRI and MODIS. The simulations qualitatively reproduce the key features of the observations, in particular the fact that the smoke plumes are separated into series of individual "puffs", which originate from the high fire activity during daytime and are separated by the low activity at night. An animation of the modelled plumes shows that the ones near the Libyan coast have been emitted on the previous day and the one in Algeria is two days old. Furthermore, on August 25, the following observations can be made:

- a very strong plume just off the Peloponnese, associated with very high FRP values (exceeding 70,000 MW)
- a westward broadening of the plume over the Mediterranean
- smaller plumes off the coasts of Albania, Southern Italy, and Sicily
- a strong plume falling on land in Libya

And for the following day:

- a very strong plume falling on land in Libya on 26 Aug, associated with the very high FRP values observed on 25 Aug
- a distinct "mirrored S" shape of the plume
- a thin, weak plume originating in Albania

Despite the striking similarities, the locations of the plume features are often slightly shifted in the simulations with respect to the MODIS images. This may be related to

the parameterisation of the smoke plume injection height (currently at the lowest model level) but needs further investigation.

The simulated optical depth of all the model aerosol species that are emitted by fire, i.e. organic matter, black carbon, and sulphate, are compared to the aerosol optical depths derived from concurrent MODIS observations on 25, 26, and 27 August in Figure 5.48 to Figure 5.50. The figures also show the corresponding scatter plots for the entire maps and specific rectangles defined covering just the Greek fire plumes.

On 25 and 26 August, the simulations and observations of the Greek fire plumes display very similar shapes, as discussed above. On 25 August, the simulated plume is much broader. This could indicate that even the operational resolution of the ECMWF model is insufficient to accurately capture the plume dispersion on such scales. Furthermore, a tendency of the model to overestimate the AOD is apparent. We estimate that this is a consequence of applying the Ichoku and Kaufman (2005) emission factors, which are reportedly too high.




Figure 5.47: Modelled organic matter plus black carbon AOD [-] (left, blue) and MODIS visual images (right) for an Aqua overpass on 25 August, 1205UTC, (top) and a Terra overpass on 26 August, 0935UTC (bottom). Overlaid with SEVIRI FRP [W/m²] interpolated to model resolution (left, orange) and MODIS hot spots in (right, red).

The AOD comparison of 26 August confirms these findings: The plume shapes are reproduced well, but the plume AOD values are mostly overestimated. Additionally, the background, which originates from different sources, is underestimated. This might be due to cloud cover effects, which are not simulated.

On 27 August, the Peloponnese was partly covered by clouds, the effects of which have been neglected in the tested SEVIRI FRP product generation. Obviously, the

shortcoming translates into a marked degeneration of the quality of the simulated aerosol field: The westward outflow from the Peloponnese is overestimated and the southward outflow in the simulation has not been detected by the observations at all.




Figure 5.48: Modelled smoke AOD [-] (left) and observed MODIS AOD [-] product (right) for Aqua overpasses on 25 August, 1205UTC (top). AOD scatter plots for the entire area and a box on the fire Greek plume (bottom).




Figure 5.49: Modelled smoke AOD [-] (left) and observed MODIS AOD [-] product (right) for Aqua overpasses on 26 August, 1110UTC (top). AOD scatter plots for the entire area and a box on the fire Greek plume (bottom).




Figure 5.50: Modelled smoke AOD [-] (left) and observed MODIS AOD [-] product (right) for Aqua overpasses on 27 August, 1155UTC (top). AOD scatter plots for the entire area and a box on the fire Greek plume (bottom).

Starting on 26 August, SEVIRI detected large fires along the Algerian coast. The resulting smoke plumes, travelling north-eastwards, are also evident in our simulation. Figure 5.51 shows an example of the fire activity and the developing smoke plume on 30 August. The AERONET station at Lecce University in Southern Italy observed an aerosol plume passing through on 30-31 August, see Figure 5.52. It is confirmed by MODIS observations. The fact that the steep rise is predominantly in the recorded fine mode AOD indicates that the aerosols may originate from fires. The simulation exhibits a mixed dust and smoke plume passing over Lecce on 30 August. The steepest rise in AOD is attributed to a rise of the smoke aerosol components, which originated from the Algerian fires. The dust component clearly has a smoother time evolution. This is another indication that the observed strong plume is dominated by smoke emitted in Algeria and transported across the Mediterranean.




Figure 5.51: Modelled organic matter plus black carbon AOD [-] (bluish) on 30 August 2007, 1430UTC, overlaid with observed SEVIRI FRP [W/m2] interpolated to model resolution (reddish). The University of Lecce AERONET station is indicated by a white circle.




Figure 5.52: Observed and modelled AOD time series over Lecce, Southern Italy. Observations by MODIS (top orange: daily average AOD) and AERONET (red: AOD, bottom orange: coarse mode AOD, yellow: fine mode AOD). Modelled AOD (dark blue) and AOD contributions by the aerosol model species (top) and modes (bottom). The mode definition of AERONET and the model are, unfortunately not identical. [graphics by L. Jones, ECMWF. MODIS data from http://gcmd.nasa.gov/records/GES_DAAC_MOVAS.html, AERONET data from <http://aeronet.gsfc.nasa.gov/>]

As a conclusion, this end-to-end study shows that retrospective aerosol fire plume modelling with the GEMS aerosol model driven by SEVIRI fire emission input works well. More comprehensive validation is needed, but

- High temporal resolution seems vital in order to reproduce the observed smoke plume structures.
- Model runs based on SEVIRI FRP data reproduce horizontal structures found in the observations.
- Emission factors found in the literature vary by a factor of five at least. An intermediate value would be most appropriate for the Greek fire case.
- Exact plume positions and absolute scaling may still be improved. This will require
 - the best possible correction for cloud cover
 - better modelling of injection heights
 - better knowledge of emission factors.

Several distinct Greek fire plumes have been simulated. They have travelled more than 1000 km in 1-2 days. Algerian fire plumes, mixed with Saharan dust, have also been simulated. They have travel to Italy, where they were apparently identified by ground-based observations.

In light of the potential use of the SEVIRI FRP data for smoke plume forecasts it can be concluded that forecasting of the transport and evolution of the fire plume is possible for 1-2 days into the future if the SEVIRI data are made available within a few hours after observation. Since the study was performed at a horizontal resolution typical for a regional air quality model, forecasts of smoke plumes in Southern Europe similar to the shown examples can be expected from the future regional air quality systems in GEMS when the SEVIRI FRP product becomes available. The global GEMS modelling system will be able to produce routine smoke and air pollution plume forecasts for Europe and Africa at a coarser resolution of ~ 125 km. This resolution will be further enhanced in the coming years.

6 Conclusions

6.1 Product Validation Summary

Within the FREEVAL project, the SEVIRI FRP product has been evaluated with respect to

- the validity of assumptions made in the algorithm derivation,
- the capability of the SEVIRI instrument to reliably detect fires and quantify FRP,
- the influence of SEVIRI data processing on the the FRP product and
- the impact of using it in potential operational applications.

The theoretical and radiative transfer modelling analysis of the algorithm performance has shown that the MIR radiance method algorithm used within the SEVIRI FRP products has an underlying accuracy of $\pm 12\%$ over the temperature range expected for active fires, and that the assumptions made when implementing this algorithm on data of highly-sub pixel sized fires (as will be the case with coarse spatial resolution satellite data such as that from SEVIRI) in theory introduce negligible other errors. In this case, if the fire pixels that comprise an individual fire can be reliably detected, show a sufficiently large MIR radiance increase above the background, and if the MIR atmospheric transmission is reliably known then the FRP can be quantified to this level of uncertainty. Differences between the original KCL algorithm and the Land SAF implementation are negligible in this respect.

In practical terms, the most limiting factor for product accuracy appears to be the current coarse pixel size, of area $\sim 23 \text{ km}^2$ at the sub-satellite point, increasing to $\sim 90 \text{ km}^2$ near the disk edge (assuming full width at half maximum sensitivity values). Numerous fire pixels with FRP values less than 40 MW escape detection by SEVIRI, and the detection and quantification of slightly larger fires (40-100 MW) will be less reliable, because the enhancement of the MIR brightness temperature due to the fire with respect to the (somewhat variable) background temperature of surrounding pixels is rather small. To some extent the impacts of the coarse spatial resolution are balanced by the extremely high temporal resolution of the geostationary observations. As was shown for fires in the Central African Republic, over the course of a day SEVIRI will capture a signal from most fire events that the much higher spatial resolution MODIS instruments on EOS Aqua and Terra can detect during their four-times per day overpasses. We assume that this is related to the ability of SEVIRI to observe the complete fire life cycle and thus capture fires when they reach their peak intensity. However, for any particular SEVIRI observation, the cumulative FRP measured at the regional (e.g. grid cell or country-scale) is likely to be an underestimate of what would have been measured by MODIS had it observed the whole area at the same moment, by on average around 50%.

Due to the higher spatial resolution observations and wide usage of the MODIS active fire products these are taken to be the reference standard against which the SEVIRI FRP product is assessed. Comparisons were performed for the period February 2004 to January 2005 and included data of August 2007. Tests were made on a per-fire basis, as well as on a regionally gridded basis. When MODIS and SEVIRI detect the same fire, in 76 % of the cases the FRP retrieved by SEVIRI is within 33 % of that reported by MODIS. Errors of omission and commission are estimated to 54% (68% for the one month of data of the Land SAF product) and 8% (2%), respectively, varying with season. Fire detection has been found to be largely independent of the dominant vegetation type in which the fire occurs, although SEVIRI shows a small tendency to detect fewest of the MODIS-detected fires in croplands (a landcover type dominated by smaller fires), and more of them in forested areas.

Since the MIR channel on SEVIRI was not designed for fire detection but rather for land surface monitoring, it saturates around 335 K, a temperature that is easily exceeded by larger fire events. The effect of this saturation is an underestimation of FRP for large fires, which can in fact contribute significantly to an underestimation of FRP in a given region. Limited experiments have indicated an FRP underestimation of ~ 10% by day due to pixel saturation and up to 40% at night, though at night there are many fewer fires and much lower regional FRP totals, so saturation of a few nighttime pixels can induce large percentage errors.

The spatial filtering and geometric interpolation performed on-board MSG as part of the level 1 to level 1.5 processing induces some additional noise in the MIR field, which further reduces the instrument's ability to detect all the fire pixels associated with an individual fire event, and to accurately quantify their FRP. The "blurring" of fire radiances related to this pre-processing can reduce level 1.5 fire pixel MIR temperatures, and as a consequence fewer pixels appear to be saturated in the level 1.5 data than were originally saturated at the instrument (level 1.0) stage. However, it is shown through theoretical modelling and targeted data analysis that the effects of the level 1 to level 1.5 processing are generally outweighed by the limitations given by the sensor resolution and the pixel saturation effects.

6.2 Demonstrated Usefulness of Product

FREEVAL has undertaken two types of activity in order to assess the potential use of the SEVIRI FRP product in (predominantly) operational applications:

- Several potential users were contacted and queried about their requirements and willingness to use an FRP product from SEVIRI and
- a number of impact studies were performed in the context of pre-operational modelling systems for monitoring of atmospheric composition.

Several users provided a strong recommendation for operational generation of FRP from the SEVIRI sensor. Although SEVIRI performs less well than for example MODIS with respect to the detection and quantification of fires on a per-observational basis, its high temporal sampling frequency and the expected availability of near-

realtime data products offers great potential to improve the prediction of smoke plumes from fire events in Southern Europe and Africa, and this has been demonstrated in the case studies described in this report. These case studies also underline the readiness of the community to make use of the product very soon after its release. Furthermore, the 15-minute sampling frequency will also be of interest for operational warning services, such as that operated by the South African power company ESCOM (see section 1.2).

Based on the product accuracy assessments, the user survey, and the impact study analyses performed in FREEVAL it was found that two products will be necessary to exploit the full potential of SEVIRI FRP data in (quasi) operational applications: (i) a pixel product containing observed FRP for each individual fire pixel together with ancillary data on the per-pixel FRP uncertainties, and (ii) a gridded product at a $1^\circ \times 1^\circ$ resolution containing area integrated FRP totals averaged over, most likely, a 1 hour time period and empirical corrections for undetected low FRP fires and partial cloudiness at the grid-cell scale.

6.3 Definition of Accuracy Requirements

The user requirements for FRP products in general were collected in Table 2-1 in section 2 of this report. Here, we assess the accuracy requirements specifically for the SEVIRI FRP product and in light of the theoretical performance that is achievable with this sensor under its standard operating conditions.

The three accuracy values tabulated below are defined as follows:

- *Threshold accuracy*: this is the accuracy limit which is needed so that the product fulfils its purpose.
- *Target accuracy*: this is the average product accuracy under the present operating conditions and with the instrument characteristics of SEVIRI. With this product quality the product will be valuable for most of the users identified above.
- *Optimal accuracy*: this is the accuracy that can be reached under optimum conditions (sub-satellite point, cloud-free scene, homogeneous background, medium sized fire).

As was demonstrated in the product validation activities, the accuracy of the SEVIRI FRP product will depend on various factors related to pixel resolution, saturation, viewing geometry and on-board and ground-based pre-processing of raw signals. Furthermore, the required level of accuracy will depend on the application, and different aspects of accuracy might be emphasized in different applications. For example, a fire warning system will be less concerned about the absolute quantitative value of FRP as long as the fire can be reliably detected rapidly (with few commission errors in particular) and there is some indication about fire severity. Chemical forecasts, and even more so reanalysis simulations, on the other hand, depend on the

reliability of area-averaged fire emissions (and thus FRP) and have less concern about the ability of the instrument to capture each and every fire.

	Pixel product	Gridded product
Threshold accuracy	N.A. ¹	Factor 3 over continental area
Target accuracy	70% of retrieved FRP within 50% of “true” values as defined by MODIS	Factor 2 at the scale of ecozones
Optimal accuracy	±15%	25% on a 5° grid

¹ successful detection of a significant fraction of fires reproducing the spatial and temporal distribution can be considered the threshold target

Table 6-1: Summary of accuracy requirements for the SEVIRI FRP pixel and gridded products.

In summary it can be said that the SEVIRI FRP product fulfils the accuracy requirements given in the table above. It will greatly improve the ability of operational atmospheric models to monitor emissions from highly variable vegetation fires and the smoke plumes emanating from them. Nevertheless, the community would be glad to see further improvements of the product and ultimately of the sensor design (see section 6.4) in order to further enhance the reliability of their applications.

6.4 Recommendations for Future Developments

6.4.1 Short-term Recommendations

Small product improvements which could be implemented until the next algorithm release include the following:

- improve the estimates of atmospheric transmittance, and its uncertainty, specifically with respect to water vapour (this is currently being explored with the help of model output from the ECMWF weather model)
- flag cloudy sea pixels as sea not cloud (the likelihood of fire occurrence over ocean pixels is zero, regardless of whether the pixel is covered by a cloud or not)
- add a gridded product at 1° × 1° degree resolution, including a method for adjustment for undetected low FRP (small) fires. The specifications for the first version of the gridded product have been developed over the course of the FREEVAL project and can soon be finalized.
- clarify the differences between fire detections and FRP observations made by Meteosat 8 and –9; assess the impact of calibration uncertainties (work on this is ongoing at EUMETSAT)
- add a static product with grid cell sizes (this simplifies interpolation of the product to various model grids in atmospheric transport models)
- improve the error calculation supplied with the reported FRP estimates, based on the latest results included in this report

6.4.2 Mid-term Recommendations

As shown in this report, important work remains to be done in order to fully evaluate all aspects of the SEVIRI FRP product and assess its quality and usefulness beyond the primary study area over the African continent. Specifically, the following issues were identified to merit further study:

- improved resolution for gridded product: The tests performed in FREEVAL considered only grid resolutions of 5°, 1° and 0.25°. It was found that the corrections applied to the 0.25° product would induce too much noise. However, an intermediate resolution of 0.5° may still provide satisfactory results, and furthermore it may be possible to develop an algorithm which applies the corrections on a coarser grid but still preserves finer scale structures in the gridded data product.
- explore a more dynamic, self-adapting methodology for adjusting the gridded product for the influence of non-detected low FRP fires, since basing all corrections on the dataset derived in 2004 has been shown to introduce errors. Approaches based on frequency magnitude statistical extrapolation are a possibility here.
- exploration of temporal signal to characterize background: one of the major error terms in the FRP product is the uncertainty of the background MIR radiance signal. The use of temporal information should be explored, for example observing a burning pixel and using the radiance estimates before it started to burn could help narrow the uncertainty here.
- extend validation fully to the disk edges (South America, Central Europe, Madagascar): so far, almost all validation activities concentrated on the African continent, where the SEVIRI pixel size is smallest and thus where the product will be most reliable. Preliminary analysis has demonstrated some skill of SEVIRI to also detect fires and derive FRP estimates in areas near the disk edges, for example in South America and Madagascar. However, the effect of missing fires will be much larger than the uncertainties stated in the accuracy table in section 6.3 above. Thus, a more thorough analysis is needed as to whether a reliable data product can be generated from processing of the outer disk areas.
- improve cloud mask and aerosol transmittance: Prior to input into the SEVIRI FRP processing chain (KCL or EUMETSAT/LandSAF version) the first operation is to mask out cloud contaminated pixels. The accuracy and impact of such masking, for example whether in some cases heavy smoke is falsely identified as cloud, needs to be fully assessed. What is ultimately required is perhaps a mask recording the transmittance of the atmosphere at MIR wavelengths (which for thick cloud will be zero, but for smoke will be > 0 but less than for clear sky)

- develop methods to use FRP for constraining injection altitude and emission factors: the burning intensity of a fire not only controls the magnitude of its trace gas and aerosol emissions, but also influences the way in which these compounds are released into the atmosphere. Hotter fires (with a larger flaming to smoldering ratio) will emit more oxidized compounds and they will generate additional updraughts that can potentially lead to a higher injection altitude of the smoke plume. Such processes occur below the grid scale of atmospheric models and therefore require a parameterisation. The SEVIRI FRP product offers an opportunity to develop and test such parameterisations, because FRP contains information on the fire intensity.
- reprocessing of complete SEVIRI data set: the atmospheric modelling community expressed a strong interest to obtain a consistent reanalysis product covering the complete time period of SEVIRI observations. This will require reprocessing of the archived SEVIRI data set.
- improved error estimate of the gridded FRP product: so far the discussion of errors was mostly limited to the “observed FRP”, i.e. the pixel product. Additional work is needed to constrain the error estimates on the bias correction terms applied in any released gridded data product.

6.4.3 Long-term Recommendations

The FREEVAL validation activities demonstrated the potential, but also the limitations of fire detection and characterisation with SEVIRI. While the SEVIRI FRP product certainly advances the state-of-the-art and will positively impact a number of operational applications in the future, its still contains rather large errors that could be much reduced if today’s technical possibilities were fully realized in the design of the next generation geostationary imaging spectro-radiometers. Once again it must be noted that SEVIRI was not designed for fire monitoring, and this has some implications on the FRP product quality. Below we list our recommendations for an optimal fire monitoring component in the future Global Earth Observation network. These are based on proven concepts and technological capabilities and should therefore be achievable within adequate budgets and at minimal technical risk.

Sensor characteristics:

Because of the high spatial variability of fires, a future fire monitoring system should include observations down to a scale of a few hundred metres (target resolution: 250 m at sub-satellite point). This will also allow characterisation of the low-FRP tail of the fire intensity distribution, and will thus allow improved adjustment of the lower spatial resolution data for the effect of undetected (low FRP) fires. Minimum requirements are two infrared channels: one in the MIR (centred around 3.9 μm ; and ideally not overlapping with the CO_2 absorption band upwards of 4 μm), and one in the TIR (centered around 8.7 μm or 10.8 μm). Gain settings should be such that the MIR channel saturates only above 650 or 700 K, and an extended dynamic range for the TIR channel should also be considered. Unless this can be provided by a co-

located instrument on the same platform, at least one additional channel in the optical part of the spectral is required for cloud masking and sun glint detection, optimally located in the NIR spectral region. On board data pre-processing of the type that is done for SEVIRI should be avoided or modified such that it does not impact the fire detection and FRP calculation. Of course, exact geo-referencing is required afterwards in order to filter pixels in non-vegetated areas etc.

Constellation:

To provide the above high spatial resolution system, a polar-orbiting system maybe required. This however, should be allied to the development of future geostationary systems having at least the same spectral characteristics as SEVIRI (though potentially with a narrower MIR channel that does not overlap with the CO₂ absorption band), but with an improved dynamic range and spatial resolution. A geostationary system with the spatial and dynamic range capabilities at least matching those of MODIS in the fire-relevant spectral channels is recommended.

As demonstrated by the SEVIRI FRP product, the possibility to monitor large continental areas with high temporal frequency is an extremely valuable asset of geostationary platforms. On the other hand, they do have their limitations over higher latitudes. These can be covered well by polar orbiting instruments. Therefore, the optimal fire monitoring system would consist of a series of fire-capable geostationary platforms with the characteristics described above, together with 2 or 3 polar orbiters offering an improved spatial resolution and coverage of high latitudes. In addition, the fine spatial resolution polar orbiting instrument would be desirable to validate and cross-calibrate the fire-monitoring network.

Annex

A 1 Abbreviations

ATBD	Algorithm Theoretical Basis Document
ECMWF	European Centre for Medium-range Weather Forecasts
EUMETSAT	European Organisation for the Exploitation of Meteorological Satellites
FRE	Fire Radiative Energy
FAS	Fire Assimilation System (at FMI)
FIR	Finitive impulse response
FMI	Finnish Meteorological Institute
HRV	High Resolution Visible
FREEVAL	FRE Evaluation
FRP	Fire Radiative Power
FTA	Fire Thermal Anomaly
GCM	Global Circulation Model
GEMS	Global and regional Earth-system (Atmosphere) Monitoring using Satellite and in-situ data (EU 6 th framework Integrated Project)
GMES	Global Monitoring for Environmental Security, European initiative for the implementation of information services dealing with environment and security
GFED	Global Fire Emissions Database (GFED) (van der Werf et al. 2006)
KCL	King's College London
NRT	Near Real Time
MIR	Middle InfraRed
MODIS	Moderate Resolution Imaging Spectroradiometer
MPEF	Meteorological Product Extraction Facility at EUMETSAT
ORR	Operation Readiness Report
SAF	Satellite Applications Facility
SEVIRI	Spinning Enhanced Visible and InfraRed Imager
TA	Thermal Anomaly [K]
TIR	Thermal InfraRed

A 2 References

- Arino, O., J.-M. Rosaz, and P. Goloub (1999) The ATSR World Fire Atlas. A synergy with 'Polder' aerosol products. *Earth Observation Quarterly*, 1-6.
- Dennison, P.E., K. Charoensiri, D.A. Roberts, S.H. Peterson, and R.O. Green (2006) Wildfire temperature and land cover modeling using hyperspectral data. *Remote Sensing of Environment*, 100, 212-222
- Dozier, J. (1981) A method for satellite identification of surface temperature fields of sub-pixel resolution, *Remote Sens. Environ.*, 11, 221–229.
- EUMETSAT (2003) Image Processing Facility Detailed Design Specification – Vol Q Algorithms, EUMETSAT EUM/MSG/SPE/198-Q, 307pp.
- Giglio, L., and J. D. Kendall (2001) Application of the Dozier retrieval to wildfire characterisation: A sensitivity analysis, *Remote Sens. Environ.*, 77, 34– 49.
- Giglio, L., G. R. van der Werf, J. T. Randerson, G. J. Collatz, and P. Kasibhatla (2006), Global estimation of burned area using MODIS active fire observations, *Atmospheric Chemistry and Physics*, 6, 957-974.
- Giglio, L., J.Descloitres, C.O.Justice, and Y.Kaufman (2003a) An enhanced contextual fire detection algorithm for MODIS. *Remote Sensing of Environment*, 87,273-282.
- Giglio, L., Kendall, J. D., and Mack, R. (2003b) A multi-year active fire dataset for the tropics derived from TRMM VIRS. *International Journal of Remote Sensing*. 24. 22. 4505-4525.
- Govaerts, Y., Wooster, M.J., Lattanzio, A. and Roberts. G. (2007), Fire Radiative Power (FRP) characterisation Algorithm Theoretical Basis Document, EUMETSAT, EUM/MET/SPE/06/0398
- Hollingsworth, a., R.J. Engelen, C. Textor, A. Benedetti, O. Boucher, F. Chevallier, A. Dethof, H. Elbern, H. Eskes, J. Flemming, C. Granier, J.W. Kaiser, J.J. Morcrette, P. Rayner, V.-H. Peuch, L. Rouil, M.G. Schultz, A.J. Simmons (2008) The Global Earth-system Monitoring using Satellite and in-situ (GEMS) Projects: Towards a monitoring and forecasting system for atmospheric composition, BAMS, in press
- Ichoku C. & Y.J. Kaufman (2005) A method to derive smoke emission rates from MODIS fire radiative energy measurements, *IEEE Transactions on Geoscience and Remote Sensing*, 43(11), 2636 - 2649
- Justice, C. O., L.Giglio, S. Korontzi, J. Owens, J. Morissette,D. Roy, D., J. Descloitres, S. Alleaume, F. Petitcolin, and Y. Kaufman(2002) The MODIS fire products, *Remote Sensing of Environment*, 83, 244-262.
- Kaiser, J.W., M.G. Schultz, J.-M. Gregoire, C. Textor, M. Sofiev, E. Bartholome, M. Leroy, R.J. Engelen, A. Hollingsworth (2006) Observation Requirements for Global Biomass Burning Emission Monitoring, *Proc. 2006 EUMETSAT Met. Sat. Conf.*
- Kaufman, Y. J., C. Justice, L. Flynn, J. Kandall, E. Prins, D. E. Ward, P. Menzel, and A. Setzer (1998) Monitoring global fires from EOSMODIS, *J. Geophys. Res.*, 103, 32,215–32,239.

- Lattanzio, A. and Govaerts, Y. (2006) Report on the comparison of the fire thermal anomaly products generated with Meteosat-8 and Meteosat-9 data, EUMETSAT EUM/MET/REP/06/0483, 11pp.
- Langaas, S. (1995) A critical review of sub-resolution fire detection techniques and principles using thermal satellite data. PhD thesis, Department of Geography, University of Oslo, Norway.
- Lutz, H.-J., Gustafsson, J. B. and Valenzuela-Leyenda, R. (2003) Scenes and cloud analysis from Meteosat Second Generation (MSG). Proceedings of the 2003 EUMETSAT Meteorological Satellite Conference. Weimar. Germany. EUMETSAT. EUM P39. 311-318.
- Moran, P.A.P. (1950), Notes on continuous stochastic phenomena. *Biometrika* 37:17-23.
- Morcrette, J.-J., L. Jones, J.W. Kaiser, A. Benedetti, O. Boucher, Toward a forecast of aerosols wit the ECMWF Integrated Forecast System (2008) ECMWF Newsletter No. 114, ECMWF, Reading, UK.
- Morisette, J. Giglio, L., Csiszar, I. and Justice, C. (2005) Validation of the MODIS active fire product over Southern Africa with ASTER data, *International Journal of Remote Sensing*, 26, 4239-4264.
- Ohlemiller, T.J. (1995) Smoldering combustion. In: Quincy, MA, DiNenno, P. J.; Beyler, C. L.; Custer, R. L. P.; Walton, W. D. (Eds.), *SFPE Handbook of Fire Protection Engineering*, 2nd edition, vol. 2, Building and Fire Research Laboratory (NIST), Gaithersburg, MD, pp.171-179.
- Riggan, P., Tissell, R., Lockwood, R., Brass, J., Pereira, J., Miranda, H., Campos, T., Higgins, R. (2004) Remote measurement of energy and carbon flux from wildfires in Brazil. *Ecological Applications*, 14, 855-872.
- Roberts, G. and Wooster, M.J. (2008) Geostationary Fire Detection and Fire Characterization over Africa, *IEEE Transactions on Geoscience and Remote Sensing*, in press
- Roberts, G., M. J. Wooster, G. L. W. Perry, N. Drake, L.-M. Rebelo, and F. Dipotso (2005) Retrieval of biomass combustion rates and totals from fire radiative power observations: Application to southern Africa using geostationary SEVIRI imagery, *J. Geophys. Res.*, 110, D21111, doi:10.1029/2005JD006018.
- Robinson, J. (1991) Fire from space: Global fire evaluation using infrared remote sensing, *Int. J. Remote Sens.*, 12, 3 –24.
- Schmid, J. (1999?), The SEVIRI instrument, EUMETSAT internal report, available at www.eumetsat.int/groups/ops/documents/document/pdf_ten_msg_seviri_instrument.pdf
- Shephard, M. and Kennelly, E. (2003) Effect of Band-to-Band Coregistration on Fire Property Retrievals, *IEEE Transactions on Geoscience and Remote Sensing*, 41, 2648-2661.
- Van der Werf, G. R., J. T. Randerson, G. J. Collatz, L. Giglio, P. S. Kasibhatla, A. Avelino, S. C. Olsen, and E.S. Kasischke (2004) Continental-scale partitioning of fire emissions during the 1997-2001 El Nino / La Nina period. *Science*, 303: 73-76.
- van der Werf, G. R., J. T. Randerson, L. Giglio, G. J. Collatz, P. S. Kasibhatla, and A. F. Arellano (2006) Interannual variability in global biomass burning emissions from 1997 to 2004, *Atmospheric Chemistry and Physics*, 6, 3423-3441.

- Wolfe, R. E., M. Nishihama, A. J. Fleig, J. A. Kuyper, D. P. Roy, J. C. Storey, and F. S. Patt (2002) Achieving sub-pixel geolocation accuracy in support of MODIS land science, *Remote Sens. Environ.*, 83, 31–49.
- Wooster, M. J., B. Zhukov, and D. Oertel (2003) Fire radiative energy for quantitative study of biomass burning from the BIRD experimental satellite and comparison to MODIS fire products, *Remote Sens. Environ.*, 86, 83– 107.
- Wooster, M. J., G. Roberts, G. L. W. Perry, and Y. J. Kaufman (2005) Retrieval of biomass combustion rates and totals from fire radiative power observations: FRP derivation and calibration relationships between biomass consumption and fire radiative energy release, *J. Geophys. Res.*, 110, D24311, doi:10.1029/2005JD006318.
- Zhukov, B., Lorenz, E., Oertel, D., Wooster, M. J., and Roberts, G. (2005) Spaceborne detection and characterization of fires during the Bi-spectral Infrared Detection (BIRD) experimental small satellite mission 2001-2004. *Remote Sensing of Environment* 100: 29-51.

A 3 The project consortium

Description of the consortium

The consortium consisted of six organizations with expertise in the full range of areas that were required to complete the necessary tasks in this project to a high degree of skill and quality, namely satellite remote sensing (KCL, UPMC, MO, ECMWF), satellite-based analysis of biomass burning patterns (KCL, UA, FZK), quantification of pyrogenic emissions (UA, FZK, UPMC, KCL), modeling of atmospheric chemistry and transport (ECMWF, FZK, UPMC, MO) and the generation of operational atmospheric forecasts and reanalyses via data assimilation methods (ECMWF, MO). The team included Prof. Martin Wooster, the main developer of the FRP approach adopted by EUMETSAT in the FRP product, and was coordinated by Dr. Martin Schultz who combines a key expertise in global atmospheric modelling with significant capability in fire emissions modelling and expertise in the co-ordination of complex research programmes. Dr. Schultz is co-ordinating the sub-project on global reactive gases within the GEMS project. The other partners are well-known experts in their field, and several of play an important role in the ongoing developments of earth system monitoring services run by ECMWF and the Met Office. Dr. Guido van der Werf is a key person in the development of the GFED fire emissions product generated with input from MODIS active fire detection. Dr. Claire Granier is leading the Global Emission Inventory Activity and is an expert in the utilisation and assessment of tropospheric satellite data (GOME, SCIAMACHY, MOPITT). Dr. Olivier Boucher is head of the climate chemistry and ecosystems team at the Met Office and is presently co-ordinating the sub-project on aerosols in GEMS. Dr. Anthony Hollingsworth served as director of research at ECMWF and co-ordinated the GEMS project. After his death in July 2007, his role was taken over by Dr. Adrian Simmons.

CVs of the FREEVAL consortium members

The following curricula vitae of the FREEVAL investigators document the key experience of the team members in all aspects relevant to the project.

Curriculum Vitae

MARTIN G. SCHULTZ

(ICG-2, Forschungszentrum Jülich, Germany)

ADDRESS: Forschungszentrum Jülich
ICG-2, D-52425 Jülich

TELEPHONE: (49) 2461 61 2831
FAX: (49) 2461 61 8131
E-MAIL: m.schultz@fz-juelich.de

RELEVANT KEY EXPERTISE

Martin Schultz is leading the modelling department in the institute for chemistry and dynamics of the geosphere, tropospheric research (ICG-2), directed by Prof. Andreas Wahner. Dr. Schultz has a lot of experience in global modelling of atmospheric chemistry and climate and he has also been involved in various activities related to in-situ and remote Earth observations. He has participated and led several European and national research programmes and is currently co-ordinator of the sub-project on global reactive gases within the EU integrated project Global Environmental Monitoring of the Atmosphere Using Satellite Observations (GEMS), which aims at establishing an operational system for predicting and monitoring the atmospheric composition at the European Centre for Medium-range Weather Forecasts (ECMWF). Dr. Schultz has a strong interest in the application of satellite data for improving emission estimates from vegetation fires and has contributed to several discussions on this topic at various international workshops (i.e. at EUMETSAT or ESA and elsewhere). He is author or co-author of almost 40 peer-reviewed publications and several assessment reports. Based on his involvement in GEMS, his experience with the use of satellite data in fire emissions modelling, and his experience with project co-ordination, he was selected to act as co-ordinator of the present project.

EMPLOYMENT

2006-	Head of the dept. of atmospheric chemistry modelling at the ICG-2, research center Jülich
2001-2006	Group leader "Aerosols, Chemistry and Climate" at Max Planck Institute for Meteorology.
1999-2001	Scientist at the Max Planck Institute for Meteorology, Hamburg
1997-1999	Postdoctoral fellow at Harvard University, Cambridge, US
1996	Postdoctoral fellow at the ICG-II, research center Jülich

EDUCATION

- 1992-1996 PhD, University of Wuppertal and ICG-2, research center Jülich, Germany
 1990-1991 Diplom, solid state physics, University of Heidelberg
 1985-1990 University education in Bonn and Heidelberg, Germany

RELEVANT RESEARCH PROJECTS AND COMMITTEE MEMBERSHIPS

- 2005 - Co-ordinator of GEMS sub-project Global reactive gases and member of the GEMS management board
 2003 -2006 Co-ordinator of 5th framework EU programme RETRO with 12 partner institutes
 2003 -2005 BMBF AFO-2000 project ISOTROP on the use of satellite information for modelling
 2003 – 2006 PhD advisor of a student investigating the use of GLOBSCAR and GBA2000 burned area data for fire emission modelling

EXAMPLE KEY PUBLICATIONS

1. B. Mota, J. Pereira, D. Oom, M. Vasconcelos, and **M. G. Schultz**: Screening the ESA ATSR-2 World Fire Atlas (1997-2002), *Atmos. Chem. Phys.*, pp. 1409-1424. SRef-ID: 1680-7324/acp/2006-6-1409, 2006.
2. **Schultz, M.G.**, Heil, A., Hoelzemann, J.J., Spessa, A., Thonicke, K., Goldammer, J., Held, A.C., Pereira, J.M., van het Bolscher, M.: Global Emissions from Wildland Fires 1960 to 2000, *Global Biogeochemical Cycles.*, 22, GB2002, doi:10.1029/2007GB003031, 2008.
3. Laepple, T., **M.G. Schultz**, J.F. Lamarque, et al.: Improved Albedo Formulation for Chemistry-Transport Models based on satellite observations and assimilated snow data and its impact on tropospheric photochemistry, *J. Geophys. Res.*, 110(D11), D11308, doi:10.1029/2004JD005463, 2005.
4. Hoelzemann, J.J., G.P. Brasseur, C. Granier, **M.G. Schultz**, and M. Simon. The Global Wildfire Emission Model GWEM: A new approach with global area burnt satellite data, *J. Geophys. Res.*, 109(D14), doi:10.1029/2003JD003666, 2004.
5. **Schultz, M.G.**: On the use of ATSR fire count data to estimate the seasonal and interannual variability of vegetation fire emissions, *Atmos. Chem. Phys.*, 2, 387-395, 2002.

*Curriculum Vitae***MARTIN WOOSTER**

(King's College London, UK)

ADDRESS: Department of Geography,
 King's College London
 Strand, London,
 WC2R 2LS, UK

TELEPHONE: (44) 207 848 2577
FAX: (44) 207 848 2287
E-MAIL: martin.wooster@kcl.ac.uk

RELEVANT KEY EXPERTISE

Martin Wooster is Professor of Earth Observation Science in the Department of Geography, King's College London. He has particular expertise in the techniques and applications of thermal remote sensing, and in the causes and consequences of biomass burning as a global environmental phenomena. He is the author of more than 40 peer-reviewed papers on these issues and has led a number of UK-funded research projects that have in recent years concentrated on development and application of the Fire Radiative Power technique. Professor Wooster was co-investigator on the European Space Agency 'ECOFIRE' project, assessing current and future capabilities for characterising fire events and associated emissions from spaceborne remote sensing, is a member of the EUMETSAT Mission Team for the Meteosat Third Generation Mission, and is part of the CARBOAFRICA EU Framework 6 where his contribution is to examine carbon fluxes from African biomass burning using terrestrial satellite remote sensing approaches. The FTA algorithm implemented by EUMETSAT is a derivative of that developed by King's College London, and Wooster is co-author of the FTA Algorithm Theoretical Basis Document.

EMPLOYMENT

2005- Chair of Earth Observation Science, Department of Geography, King's College London, UK
 2003-2005 Reader (Physical Geography), King's College London, UK
 1998-2003 NERC Earth Observation Science Initiative Lecturer, Department of Geography, KCL.
 1992-1994 Higher Scientific Officer, Environmental Science Dept., Natural Resources Institute
 1986-1997 IBM UK Ltd., Information Systems Officer

EDUCATION

1994-1998 PhD Department of Earth Sciences, The Open University
 1991-1992 MSc Remote Sensing (Distinction), University of London
 1987-1990 BSc (Hons), Physics (Upper Second), Bristol University

RELEVANT MISSION INVESTIGATORSHIPS AND COMMITTEE MEMBERSHIPS

2004 - EUMETSAT MTG Mission Team (with relevance to fire applications).
 2005 - Steering committee for NERC Airborne Remote Sensing Facility (and Chair designate)
 2003 - Steering committee for NERC Field Spectroscopy Facility
 2002 - Bi-spectral Infrared Detection (BIRD) small experimental 'high temperature events' satellite
 1999–2006 EUMETSAT (MSG SEVIRI instrument) Principal Investigator

RESEARCH AWARDS

2002 Wooster (2002) selected as an AGU highlight paper in Geophysical Research Letters.
 2001 Awarded the Daiwa-Adrian Prize for Excellence in a UK-Japan Collaborative Science Project carried out during 1998-2000 (The Daiwa Foundation)
 2000 Royal Society Travel Award to IAVCEI 2000 Conference, Indonesia.
 1999 Visiting Fellowship at University of Tokyo (Japanese Government Award)

1998 - 2003 One of only four UK academics supported under the 1997-2000 NERC Earth Observation Science Initiative lectureship scheme (awarded 50% of full costs of my KCL academic post for 5 years).

EXAMPLE KEY PUBLICATIONS

1. Smith, A.M.S., Drake, N., **Wooster, M.J.**, Hudak, A. and Holden, Z.A.: Production of Landsat ETM+ reference imagery of burned areas within Southern African savannahs: comparison of methods and application to MODIS, *International Journal of Remote Sensing*, Vol. 28, No. 12, 20 June 2007, 2753–2775, 2007.
2. Roberts, G., **Wooster, M.J.**, Perry, G.L.W., Drake, N., Rebelo, L-M., Dipotso, F.: Retrieval of biomass combustion rates and totals from fire radiative power observations: Application to southern Africa using geostationary SEVIRI Imagery, *Journal of Geophysical Research*, 110, D21111, doi: 10.1029/2005JD006018, 2005.
3. **Wooster, M.J.**, Roberts, G., Perry, G. and Kaufman, Y.J.: Retrieval of biomass combustion rates and totals from fire radiative power observations: Calibration relationships between biomass consumption and fire radiative energy release, *Journal of Geophysical Research*, , 110, D21111, doi: 10.1029/2005JD006318, 2005.
4. Zhukov, B., Lorenz, E., Oertel, D., **Wooster, M.J.** and Roberts, G.: Spaceborne detection and characterization of fires during the Bi-spectral Infrared Detection (BIRD) experimental small satellite mission (2001-2004) *Remote Sensing of Environment*, 100, 29-51, 2005.
5. Smith, A.M.S., **Wooster, M.J.**, Drake, N.D., Perry, G.L.W. and Dipotso, F.: Fire in African savanna: testing the impact of incomplete combustion on pyrogenic emissions estimates, *Ecological Applications*, 15, 1074–1082, 2005.
6. **Wooster, M.J.**, Zhukov, B. and Oertel, D.: Fire radiative energy for quantitative study of biomass burning: Derivation from the BIRD experimental satellite and comparison to MODIS fire products, *Remote Sensing of Environment*, 86, 83-107, 2003.

LARGE RESEARCH GRANTS

- 2006-2009 CarboAfrica (EU FP6, 3 Meuro; 151k euro to KCL (PI Wooster)
- 2006-2008 GEOFIRE - A Global Geostationary Biomass Burning Emissions Estimation System for Use in Forecasting of Atmospheric State (NERC KT Grant, £191k, PI Wooster)
- 2006-2007 European Space Agency, ECOFIRE-2 ‘Scientific Assessment of Space-borne High Temperature Event Observing Mission Concepts’ (80,000 euro, European Space Agency, PI: DLR, with Co-IM Wooster; 36,000€ to KCL)
- 2006-2007 FREEVAL – FRE Evaluation (EUMETSAT; 124keuro (48keuro to KCL)
- 2005-2008 Spatio-temporal characterisation of boreal forest fire intensity dynamics and its impact on carbonflux estimation (£344,000, NERC, PI Wooster with NERC CEH and University of Leicester)
- 2005-2006 Royal society china fellowship: remote sensing of surface kinetic temperature for urban heat island investigations (£20,000, The Royal Society, with Weidong Xu)
- 2005-2006 A geostationary fire product for Africa (£50,913, NERC, PI M Wooster)

- 2003-2005 ECOFIRE – Scientific Assessment of Space-borne High Temperature Event Observing Mission Concepts (200,000 ecu, European Space Agency, PI: DLR, with Co-I M Wooster)
- 2002-2005 Enhancing volcanic hazard avoidance capacity in Central America through local remote sensing and improved risk communication (£415,000, DFID, PI: M. Wooster, with Co-I's D. Demeritt and M. Redclift)
- 2003-2005 Infrared remote sensing of Japanese volcanoes (£20,000, Japan Society for Promotion of Science, with T. Kaneko)
- 2002-2004 Retrieval of fire radiative energy to support biomass-burning emissions inventories; derivation via new spaceborne mid-IR radiometry (£133,000, NERC, PI: M. Wooster, with G. Perry as Co-I)
- 2002-2003 Fire in the Russian boreal zone for CO₂ flux estimation (£10,000, Royal Society)
- 2002-2004 Characterising fire in the Russian boreal zone for quantifying CO₂ fluxes (£44,700, The Leverhulme Trust)
- 2000-2003 Improved N₂O and nitrogenous emissions from savanna burning (£53,640, NERC GANE Thematic Programme PhD studentship and research costs)
- 1998-2003 Earth Observation Science Initiative Lectureship (£79,000, M. Wooster and King's College London Department of Geography, NERC)
- 1998 Visiting fellowship at King's College London for Dr T. Kaneko (£18,750, Japanese Ministry of Education, Science and Culture)
- 1998 Land use and remote sensing component of the Global Environment Fund (GEF) Lake Tanganyika special study on sediment discharge and its consequences (£19,000, with N. Drake, UNEP)

Curriculum Vitae

ANGELIKA HEIL

(ICG-2, Forschungszentrum Jülich, Germany)

ADDRESS: Forschungszentrum Jülich **TELEPHONE:** (49) 2461 61 6864
 ICG-2, D-52425 Jülich **FAX:** (49) 2461 61 5346
E-MAIL: a.heil@fz-juelich.de

RELEVANT KEY EXPERTISE

Angelika Heil works in the modelling department in the institute for chemistry and dynamics of the geosphere, tropospheric research (ICG-2), directed by Prof. Andreas Wahner. Her major research experience and expertise covers the interaction between fire emission, air quality and human health. Her main research interest is on fire emissions from peat fires in Indonesia. Over the last 10 years, she has been addressing this research topic with multidisciplinary approaches, including field and laboratory measurements, the analysis of satellite retrievals, regional atmospheric chemistry modelling and epidemiology.

EMPLOYMENT

- 2007- Post-doctoral fellow at the Research Center Juelich, Institute for Chemistry and Dynamics of the Geosphere, Tropospheric Research (ICG-2);Germany.
- 2002 Research assistant at the Global Fire Monitoring Center (GFMC)/Fire Ecology Group of the Max-Planck-Institute for Chemistry, Freiburg, Germany
- 2001 Research assistant at the Swiss Federal Research Station for Agroecology and Agriculture, Zuerich, Switzerland
- 2000 Research assistant at the Institute of Environmental Technology/Technical University Berlin, Germany
- 1997 Consultant for the German Technical Cooperation (GTZ) the Ministry of Forestry, Jakarta, Indonesia

EDUCATION

- 2003-2007 PhD, earth system modelling, Max-Planck Institute for Meteorology/
Department of Geosciences, University of Hamburg, Germany
- 1992-2000 Master of Engineering, Environmental Engineering,
Technical University Berlin, Germany

EXAMPLE KEY PUBLICATIONS

1. Schultz, M.G., **Heil, A.**, Hoelzemann, J.J., Spessa, A., Thonicke, K., Goldammer, J., Held, A.C., Pereira, J.M., van het Bolscher, M.: Global Emissions from Wildland Fires 1960 to 2000, *Global Biogeochemical Cycles.*, 22, GB2002, doi:10.1029/2007GB003031, 2008.
2. **Heil, A.**, Langmann, B., and Aldrian, E.: Indonesian peat and vegetation fire emissions: Study on factors influencing large-scale smoke haze pollution using a regional atmospheric chemistry model. *Mitigation and Adaptation Strategies for Global Change* 12 (1): 113-133, 2007; doi: 10.1007/s11027-006-9045-6.
3. Langmann, B. and **Heil, A.**:Release and dispersion of vegetation and peat fire emissions in the atmosphere over Indonesia 1997/1998. *Atmospheric Chemistry and Physics* 4: 2145-2160, 2004.
4. **Heil, A.** and Goldammer, J.G. Smoke-haze pollution: A review of the 1997 episode in Southeast Asia. *Regional Environmental Change* 2: 24-37, 2001.

*Curriculum Vitae***GARETH ROBERTS**

(King's College London, UK)

ADDRESS: Department of Geography, **TELEPHONE:** (44) 207 848 2916
King's College London **FAX:** (44) 207 848 2287
Strand, London, **E-MAIL:** gareth.j.roberts@
WC2R 2LS, UK kcl.ac.uk

RELEVANT KEY EXPERTISE

Gareth Roberts is a research associate in the Department of Geography, King's College London. His research interests lie in monitoring land surface dynamics using optical and thermal EO remote sensing. He has expertise in the application of bidirectional reflectance distribution function (BRDF) models for monitoring vegetation dynamics and retrieving biophysical parameters. For the last 5 years he has applied thermal remote sensing techniques to address key questions regarding fire impact and effects. This research has involved the development of thermal EO methods and their use in quantifying the amount of terrestrially-stored carbon released through biomass burning. Part of this research has involved the development of a prototype of the FTA algorithm implemented by EUMETSAT.

EMPLOYMENT

2003-present Research associate at the Department of Geography, Kings College London

EDUCATION

1998-2002 PhD in Remote Sensing, Dept. of Geography, University College London
 1997-1998 MSc Remote Sensing, University of London
 1994-1997 BSc (Hons), GIS (Upper Second), Kingston University

EXAMPLE KEY PUBLICATIONS

1. **Roberts, G.**, Wooster, M.J., Perry, G.L.W., Drake, N., Rebelo, L-M., Dipotso, F.: Retrieval of biomass combustion rates and totals from fire radiative power observations: Application to southern Africa using geostationary SEVIRI Imagery, *Journal of Geophysical Research*, 110, D21111, doi: 10.1029/2005JD006018, 2005.
2. Wooster, M.J., **Roberts, G.**, Perry, G. and Kaufman, Y.J.: Retrieval of biomass combustion rates and totals from fire radiative power observations: Calibration relationships between biomass consumption and fire radiative energy release, *Journal of Geophysical Research*, , 110, D21111, doi: 10.1029/2005JD006318, 2005.
3. Zhukov, B., Lorenz, E., Oertel, D., Wooster, M.J. and **Roberts, G.**: Spaceborne detection and characterization of fires during the Bi-spectral Infrared Detection (BIRD) experimental small satellite mission (2001-2004) *Remote Sensing of Environment*, 100, 29-51, 2005.
4. Privette, J. L., Tian, Y., **Roberts, G.**, Scholes, R., Wang, Y., and Caylor, K., (2004) Structural characteristics and relationships of Kalahari woodlands and savannas. *Global Change Biology*. 10, 281–291, doi: 10.1111/j.1529-8817.2003.00740.x
5. Privette, J., L., Myneni, R., B., Knyazikhin, Y., Mukufute, M., **Roberts, G.**, Tian, Y., Wang, Y., and Leblanc, S., (2002) Early spatial and temporal validation of MODIS LAI product in Africa. *Remote Sensing of Environment*. 83(1-2), 232-243.

*Curriculum Vitae***GUIDO VAN DER WERF**

(Vrije Universiteit, Amsterdam, Netherlands)

ADDRESS:	Faculty of Earth and Life Sciences Vrije Universiteit De Boelelaan 1085 1081HV Amsterdam NL.	TELEPHONE:	(31) 20 598 5687
		FAX:	(31) 20 598 9940
		E-MAIL:	Guido.van.der.werf@ falw.vu.nl

RELEVANT KEY EXPERTISE

Guido van der Werf is a post-doctoral scientist in the department of Hydrology and Geo-environmental Sciences at the Vrije Universiteit in Amsterdam. His past work included the development of models and the processing of input data with the aim to quantify fire emissions on global scales. He was the first to assess these emission on interannual scales using satellite-derived burned area, and showed with key publications in science and nature how fire emissions contribute to interannual variability in the CO₂ and CH₄ growth rates. The resulting emission database is widely used in the atmospheric and biogeochemical communities, and he co-authored several publications using atmospheric measurements of CO that aimed to further constrain these emission estimates. Guido van der Werf was recently awarded the prestigious "VENI" fellowship from the Dutch organization of scientific research to study relations between fire activity, deforestation, and climate.

EMPLOYMENT

2006- Post-doctoral scholar at the Vrije Universiteit, Amsterdam. Funding
2002-2004 Research assistant at NASA Goddard Space Flight Center, MD, USA

EDUCATION

2004-2006 PhD, global biogeochemical cycles, Vrije Universiteit, Amsterdam
1993-2001 MSc, Hydrology, Vrije Universiteit, Amsterdam

KEY PUBLICATIONS

1. **van der Werf, G. R.**, Randerson, J. T., Collatz, G. J., and Giglio, L.: Carbon emissions from fires in tropical and subtropical ecosystems, *Global Change Biology*, 9, 547-562, 2003.
2. **van der Werf, G. R.**, Randerson, J. T., Collatz, G. J., Giglio, L., Kasibhatla, P. S., Arellano, A. F., Olsen, S. C., and Kasischke, E. S.: Continental-scale partitioning of fire emissions during the 1997 to 2001 El Nino/La Nina period, *Science*, 303, 73-76, 2004.
3. **van der Werf, G. R.**, Randerson, J. T., Giglio, L., Collatz, G. J., Kasibhatla, P. S., and Arellano, A. F.: Interannual variability in global biomass burning emissions from 1997 to 2004, *Atmospheric Chemistry and Physics*, 6, 3423-3441, 2006.
4. Giglio, L., **van der Werf, G. R.**, Randerson, J. T., Collatz, G. J., and Kasibhatla, P. S.: Global Estimation of Burned Area using MODIS Active Fire Observations, *Atmospheric Chemistry and Physics*, 6, 957-974, 2006.
5. Randerson, J. T., **van der Werf, G. R.**, Collatz, G. J., Giglio, L., Still, C. J., Kasibhatla, P., Miller, J. B., White, J. W. C., DeFries, R. S., and Kasischke, E. S.: Fire emissions from C-3 and C-4 vegetation and their influence on interannual

variability of atmospheric CO₂ and delta(CO₂)-C-13, *Global Biogeochemical Cycles*, 19, 2005.

6. Arellano, A. F., Kasibhatla, P. S., Giglio, L., **van der Werf, G. R.**, Randerson, J. T., and Collatz, G. J.: Time-dependent inversion estimates of global biomass-burning CO emissions using Measurement of Pollution in the Troposphere (MOPITT) measurements, *Journal of Geophysical Research-Atmospheres*, 111, 2006.
7. Bousquet, P., Ciais, P., Miller, J. B., Dlugokencky, E. J., Hauglustaine, D. A., Prigent, C., **Van der Werf, G. R.**, Peylin, P., Brunke, E. G., Carouge, C., Langenfelds, R. L., Lathiere, J., Papa, F., Ramonet, M., Schmidt, M., Steele, L. P., Tyler, S. C., and White, J.: Contribution of anthropogenic and natural sources to atmospheric methane variability, *Nature*, 443, 439-443, 2006.
8. Gloudemans, A. M. S., Krol, M. C., Meirink, J. F., de Laat, A. T. J., **van der Werf, G. R.**, Schrijver, H., van den Broek, M. M. P., and Aben, I.: Evidence for long-range transport of carbon monoxide in the Southern Hemisphere from SCIAMACHY observations, *Geophysical Research Letters*, 33, 2006.

Curriculum Vitae

CLAIRE GRANIER

(Université Paris, France)

ADDRESS	Université Paris 6 Service d'Aéronomie Boite 102 - T15 - E5 4, Place Jussieu, 75252 Paris Cedex 05 Paris, France	TELEPHONE: (33) 144 27 84 21 FAX: (33) 144 27 37 76 E-MAIL: clg@aero.jussieu.fr
----------------	--	--

RELEVANT KEY EXPERTISE

Claire Granier is "Directeur de Recherche" at the Service d'Aéronomie/IPSL in Paris. She has over 20 years research experience in atmospheric sciences. For the past 15 years, she has worked on the development and evaluation of chemistry-transport models which have been used for the study of the composition of the lower atmosphere and its evolution. Over the past years, her work has focused on the determination of surface emissions of atmospheric compounds and their changes as a result of human activities. She is the co-coordinator of the GEIA (Global Emissions Inventory Activity) project of the IBGP program. She is also the coordinator of the activity on emissions in the ACCENT European Network for Excellence, and the deputy coordinator of the GEMS (Global and regional Earth-system Monitoring using Satellite and in-situ data) European project.

EMPLOYMENT

2001-present	Directrice de Recherches CNRS, Service d'Aéronomie, Paris, France
1996 – 2001	Chargée de Recherches CNRS, Service d'Aéronomie, Paris, France
1990 - 1995	Scientist I and Scientist II, National Center for Atmospheric Research, Boulder
1988 – 1990	Visiting Scientist, National Center for Atmospheric Research, Boulder

1984 – 1986 Chargée de Recherches CNRS, Service d'Aéronomie, Paris
1982 – 1984 Attachée de Recherches CNRS, Service d'Aéronomie, Paris

EDUCATION

1988 Thèse d'Etat (Equivalent to Habilitation), Physics, University Paris 6, France
1982 Thèse 3ème cycle, External Geophysics, University Paris 6, France
1979 Master, Mathematics, University Paris 6, France
1978 Licence, Mathematics, University Paris 6, France

RELEVANT RESEARCH PROJECTS AND COMMITTEE MEMBERSHIPS

2006 – Present: co-Editor-in-Chief, Journal of Atmospheric Chemistry
2005 – Present: Deputy Coordinator of the GEMS (Global and regional Earth-system Monitoring using Satellite and in-situ data) European project
2005 – Present : Member of the Scientific Steering Committee of the AIMES (Analysis, Integration and Modeling of the Earth System) project of the IGBP program
2004 – Present: Member of the Managing Committee of the ACCENT Network of Excellence
2003 - Present: Co-chair of the GEIA (Global Emissions Inventory Activity) project of IGBP

EXAMPLE KEY PUBLICATIONS

1. Richter, A., J. P. Burrows, H. Nüß, **C. Granier**, and U. Niemeier, Changes in Tropospheric NO₂ Levels Observed from Space by GOME and SCIAMACHY, 437, 129, *Nature*, 2005.
2. Niemeier, U., **C. Granier**, L. Kornbluh, S. Walters and G. Brasseur, The global impact of road traffic on atmospheric chemical composition and on climate forcing, *J. Geophys. Res.*, Vol.111, No.D9, D09301, 10.1029/2005JD006407, 2006.
3. **Granier, C.**, U. Niemeier, J. H. Jungclaus, L. Emmons, P. Hess, J.F. Lamarque, S. Walters and G. P. Brasseur, Ozone pollution from future ship traffic in the arctic northern passages, *Geophys. Res. Lett.*, Vol. 33, No 13, doi: 10.1029/2006GL026180, 2006.
4. Brasseur G.P., M. Schultz, **C. Granier**, M. Saunois, T., M. Botzet, E. Roeckner, and S. Walters, Impact of Climate Change on the Future Chemical Composition of the Global Troposphere, *J. Climate*, 19, 3932-3951, 2006.

Curriculum Vitae

OLIVIER BOUCHER

(UK Met Office, Exeter, UK)

ADDRESS: Met Office,
Fitz Roy Road
EX1 3PB Exeter, UK.

TELEPHONE: (44) 1392 886910
FAX: (44)1392 885681
E-MAIL: olivier.boucher@
metoffice.gov.uk

RELEVANT KEY EXPERTISE

Olivier Boucher is Head of the Chemistry, Climate and Ecosystems team in the Hadley Centre for Climate Prediction and Research of the Met Office. He has particular expertise in aerosol modelling and remote sensing. He published 50 articles in the peer-reviewed literature in the field of aerosol, radiation, and climate. He has participated to 3 EU projects. Olivier Boucher coordinated the DAEDALUS FP5 project and is the coordinator of the "aerosol" sub-project of GEMS. GEMS-aerosol has strong requirements for near-real-time estimates of biomass-burning aerosol emissions. The Climate, Chemistry and Ecosystems team is also heavily involved in carbon cycle modelling and monitoring through the GEMS and Carbo-Europe projects. Olivier Boucher is also chair of the management committee of the JULES UK community model under which fire modelling is currently planned. The Met Office has a strong interest in a near-real-time operational fire product for visibility applications, calibrating and validating aerosol and trace gases emissions in climate models, as well as understanding and monitoring of the global carbon cycle.

EMPLOYMENT

2005- Head Climate Chemistry and Ecosystems Team, Met Office, UK
 1996-2005 Junior scientist at CNRS, Laboratoire d'Optique Atmosphérique, France

EDUCATION

1992-1995 Ph.D. student, Laboratoire de Meteorologie Dynamique, Paris, France
 1990-1994 Elève de l'Ecole Normale Supérieure, Paris, France

RELEVANT MISSION INVESTIGATORSHIPS AND COMMITTEE MEMBERSHIPS

2006 - Chair of the Joint UK Land Environment Simulator (JULES) community model committee
 2005 - Coordinator of the GEMS aerosol sub-project and member of the GEMS management board
 2004 - Member of the Commission on Atmospheric Chemistry and Global Pollution (CACGP) of the IAMAS
 2003 - 2005 Coordinator of the GMES-related DAEDALUS European project
 2003 - 2004 Member of the IGACO commission of IGOS (Integrated Global Observing Strategy)

EXAMPLE KEY PUBLICATIONS

1. Bellouin, N., **O. Boucher**, J. Haywood, and M. S. Reddy, Estimate of aerosol direct effects over land and oceans from MODIS, *Nature*, 438, 1138-1141, doi:10.1038/nature04348, 2005.
2. Venkataraman, C., G. Habib, D. Kadamba, M. Shrivastava, J.-F. Leon, B. Crouzille, **O. Boucher**, and D. G. Streets, Emissions from biomass burning in India: Integrating the inventory approach with high-resolution MODIS active-fire and land cover data, *Global Biogeochemical Cycles*, 20, GB2013, doi:10.1029/2005GB002547, 2006.
3. Barrie, L., P. Borrell, **O. Boucher**, J. Burrows, C. Camy-Peyret, J. Fishman, A. Goede, C. Granier, E. Hilsenrath, D. Hinsman, H. Kelder, J. Langen, V. Mohnen, T. Ogawa, T. Peter, P. C. Simon, P.-Y. Whung, and A. Volz-Thomas, *International Global Atmospheric Chemistry Observations System (IGACO) Theme Report*, IGOS, L. Barrie, P. Borrell, and J. Langen (Eds.), ESA SP-1282, Report GAW No. 159 (WMO TD No. 1235), 54 pp., 2004.

4. Kaufman, Y. J., D. Tanré, and **O. Boucher**, A satellite view of aerosols in the climate system, *Nature*, 419, 215-223, 2002.

Curriculum Vitae

MARIE DOUTRIAUX-BOUCHER

(UK Met Office, Exeter, UK)

ADDRESS:	Met Office, Fitz Roy Road EX1 3PB Exeter, UK.	TELEPHONE:	(44) 1392 886041
		FAX:	(44)1392 885681
		E-MAIL:	marie.doutriaux- boucher@@metoffice.gov.uk

RELEVANT KEY EXPERTISE

Marie Doutriaux-Boucher is working as a feedback scientist in the Hadley Center for Climate Prediction and Research of the Met Office. She is on secondment from the University of Lille where she is an assistant professor at the Laboratoire d'Optique Atmosphérique. She also worked as a meteorological product expert for the European Organisation for the Exploitation of Meteorological Satellites (EUMETSAT). Her main research interests are climate and cloud from an observational and a modelling point of view.

EMPLOYMENT

2007-	Climate feedback scientist, Hadley Center, Met Office, UK
2005-2007	Research Scientist, Satellite Application Group, Met Office, UK
2001-2005	Assistant professor, Laboratoire d'Optique Atmosphérique, France
1999-2001	Meteorological product expert, EUMETSAT, Germany
1997-1999	Postdoc student, CNES, France

EDUCATION

1993-1997	Ph.D. student, Laboratoire de Meteorologie Dynamique, Paris, France
-----------	---

KEY PUBLICATIONS

9. W. Yu, **M. Doutriaux**, G. Sèze, H. Le Treut, and M. Desbois, A methodology **M. Doutriaux**, J. Pelon, V. Trouillet, G. Sèze, H. Le Treut, P. Flamant, and M. Desbois, Simulation of satellite lidar and radiometer retrievals of a GCM three-dimensional cloud dataset, *J. Geophys. Res.*, 103, 26025-26039, 1998.
10. **M. Doutriaux** and G. Sèze, Significant changes between the ISCCP C and D cloud climatologies, *Geophys. Res. Lett.*, 22, 4193-4196, 1998.
11. **M. Doutriaux-Boucher**, J-C. Buriez, G. Brogniez, and L. C.-Labonnote, Sensivity of retrieved POLDER directional cloud optical thickness to various ice particle models, *Geophys. Res. Lett.*, 27, 109-112, 2000.
12. J. Riedi, **M. Doutriaux-Boucher**, P. Goloub, and P. Couvert, Global distribution of cloud top phase from POLDER/ADEOS I, *Geophys. Res. Lett.*, 27, 1707-1710, 2000.

13. J.-C. Buriez, **M. Doutriaux-Boucher**, F. Parol, and N. G. Loeb, Angular variability of the liquid water cloud optical thickness retrieved from ADEOS-POLDER, *J. Atmos. Sci.*, 58, 3007-3018, 2001.
14. **M. Doutriaux-Boucher** and J. Quaas, Evaluation of cloud thermodynamic phase parametrisations in the LMDZ GCM by using POLDER satellite data, *Geophys. Res. Lett.*, 31, L06126, doi:10.1029/2003GL019116, 2004.
15. F.-M. Bréon and **M. Doutriaux-Boucher**, A comparison of cloud droplet radii measured from space, *IEEE*, doi:10.1109/TGRS.2005.852838, 2005.
16. M. Doutriaux-Boucher and P. Dubuisson, Volcanic SO₂ detection by satellite using infrared radiometers submitted to "Atmospheric Research", March 2008.

Curriculum Vitae

TOMASZ KASIKOWSKI
(UK Met Office, Exeter, UK)

ADDRESS:	Met Office, FitzRoy Road EX1 3PB Exeter, UK.	TELEPHONE: (44) 1392 884801 FAX: (44)1392 885681 E-MAIL: tomasz.kasikowski@ metoffice.gov.uk
-----------------	--	--

RELEVANT KEY EXPERTISE

Tomasz does his post-dos research in the Climate Impacts team in the Hadley Centre for Climate Prediction and Research of the Met Office. Tomasz is involved in developing the fire model coupled with Hadley Centre General Circulation Models. Within his EU funded post (GREENCYCLES MC RTN) Tomasz is studying impacts of fires on the environment. The developed fire model will reflect changes in surface albedo, vegetation disturbance and CO₂ emissions. Optimisation and further validation of the fire model (in terms of burnt area) has been performed basing on space-borne products.

EMPLOYMENT

2007- Post-doc in Climate Impacts Team, Met Office, UK

EDUCATION

1998-2004 Poland	PhD study; Nicolas Copernicus University, Faculty of Chemistry, Torun,
1993-1998 Poland	MSc study; Nicolas Copernicus University, Faculty of Chemistry, Torun,

*Curriculum Vitae***ANTHONY HOLLINGSWORTH**

(European Centre for Medium Range Weather Forecast, Reading, UK)

† deceased 29 July 2007

Expertise		Research and operational assimilation of satellite data in Numerical Weather Prediction systems
Place & Date of birth		Dublin, 6 July 1943
Education	1961-64	B.Sc. with first class honours in pure and applied mathematics University College, Cork, Ireland
	1967-70	Ph.D in Meteorology, with a minor in Applied Mathematics Supervisors: Prof. E N Lorenz, then Prof. N A Phillips Massachusetts Institute of Technology, Cambridge, MA, USA
Distinctions	1999	Jule G. Charney Award of the American Meteorological Society 'for penetrating research on four-dimensional data assimilation systems and numerical models'
	1993	D.Sc, National University of Ireland for work in Numerical Weather Prediction
Employment	1975-date	EUROPEAN CENTRE FOR MEDIUM-RANGE WEATHER FORECASTS Shinfield Park ,Reading, RG2 9AX, UK
	2003-date	ECMWF Coordinator, Global Earth System Monitoring project funded by EU
	1994-2003	Deputy Director, ECMWF
	1991-2003	Head, Research Department, ECMWF
	1978-1990	Head Data Division, ECMWF
	1976-1978	Head, Physical Aspects Section, ECMWF
	1975-1976	Senior Scientist, ECMWF
	1971-75	UK UNIVERSITIES ATMOSPHERIC MODELLING GROUP, Dept of Meteorology, Univ. of Reading, READING, UK
	1970-71	Assistant Professor , Dept of Atmospheric Sciences OREGON STATE UNIVERSITY , Corvallis, Oregon, U.S.A (Chairman Prof. E Wendell Hewson)
	1967-70	Dept of Meteorology MASSACHUSETTS INSTITUTE OF TECHNOLOGY, Cambridge MA 02139 USA 1969-70 Research Assistant, to Prof N A Phillips 1968-69 Research Assistant, to Prof E N Lorenz 1967-68 Jonathan Whitney Fellow
	1964-67	Meteorologist ,IRISH METEOROLOGICAL SERVICE Shannon Airport, Ireland

EXAMPLE KEY PUBLICATIONS

1. **Hollingsworth, A.**, S. Uppala, E. Klinker, D. Burridge, F. Vitart, J.R.A. Onville, J.W. de Vries, A. de Roo and C. Pfrang, The transformation of earth-system observations into information of socio-economic value in GEOSS Quart. *J. Royal Meteor. Soc.*, 131, 613, 3493-3512, 2006. doi:10.1256/qj.05.181.
2. **Hollingsworth, A.**, P. Viterbo, A.J. Simmons: The relevance of numerical weather prediction for forecasting natural hazards and for monitoring the global environment,

AmerMeteorSoc Met Monograph, A Half Century of Progress in Meteorology: A Tribute to Richard Reed; ed. Richard H. Johnson and Robert A. Houze Jr. 2004.

3. Chédin, A., S. Serrar, R. Armante, N. A. Scott, and **A. Hollingsworth**: Signatures of annual and seasonal variations of CO₂ and other greenhouse gases from NOAA/TOVS observations and model simulations. *J. Climate* 15, 95-116, 2002.
4. **Hollingsworth, A.**: Prospects for Development of Medium-Range and Extended-Range Forecasts: Ch 11, pp327-354 of "General Circulation Model Development Past, present and future" ed. D Randall pub Academic Press, *International Geophysics Series* 2001. ISBN 0-12-578010-9.

Curriculum Vitae

ADRIAN SIMMONS, M.A., Ph.D.

(European Centre for Medium-range Weather Forecasts, Reading, UK)

ADDRESS: ECMWF	TELEPHONE: (44) 118 949 9700
Reading RG2 9AX	FAX: (44) 118 949 9450
United Kingdom	E-MAIL: a.simmons@ecmwf.int

RELEVANT KEY EXPERTISE

Head of Model Division and later Head of Data Division at ECMWF. Currently Coordinator of the GEMS FP6 Integrated Project. Extensive research and management experience in numerical modelling, data assimilation, reanalysis, predictability, dynamical meteorology and the use of high-performance computing. Awarded L.F. Richardson and Buchan Prizes of Royal Meteorological Society. Publications include about seventy papers as author or co-author in the peer-reviewed scientific literature. Currently Chair of the GCOS/WCRP Atmospheric Observations Panel for Climate, an ex officio member of the Steering Committee of GCOS, a member of the WCRP/GCOS Observations and Assimilation Panel, and Visiting Professor, University of Reading.

EMPLOYMENT

1972-1978 University of Reading
1978-present ECMWF

*Curriculum Vitae***JEAN-JACQUES MORCRETTE**

(European Centre for Medium-Range Weather Forecasts, Reading, UK)

ADDRESS:	ECMWF	TELEPHONE:	(44) 118 949 9733
	Reading RG2 9AX	FAX:	(44) 118 949 9450
	United Kingdom	E-MAIL:	morcrette@ecmwf.int

RELEVANT KEY EXPERTISE

Since 2005, he has been in charge of the forward modelling of prognostic aerosols in the ECMWF IFS. His main interest is in cloud-aerosol-radiation interactions. Publications include more than 20 papers as first author in the open peer-reviewed scientific literature. Previous member of the Working Group on Radiation Fluxes (now GEWEX GRP).

EMPLOYMENT

Visiting fellow, Atmospheric Environment Service, Canada
Post-doctoral fellow, Advanced Study Program, NCAR
Principal Scientist at ECMWF, where he is in charge of the radiation transfer parameterisations in the forecasting model.

EDUCATION

Doctorat d'Etat en Sciences Physiques from Universite de Ille, France

RELEVANT EXAMPLE PUBLICATIONS

1. **J.-J. Morcrette**, L. Jones, J. Kaiser, A. Benedetti, O. Boucher, Toward a forecast of aerosols with the ECMWF Integrated Forecast System, *ECMWF Newsletter* No. 114, ECMWF, Reading, 2008.
2. A. Hollingsworth, R.J. Engelen, C. Textor, A. Benedetti, O. Boucher, F. Chevallier, A. Dethof, H. Elbern, H. Eskes, J. Flemming, C. Granier, J.W. Kaiser, **J.-J. Morcrette**, P. Rayner, V.-H. Peuch, L. Rouil, M.G. Schultz, A.J. Simmons, The Global Earth-system Monitoring using Satellite and in-situ (GEMS) Projects: Towards a monitoring and forecasting system for atmospheric composition, *BAMS*, 2008, in press.

*Curriculum Vitae***JOHANNES W. KAISER**

(European Centre for Medium-Range Weather Forecasts, Reading, UK)

ADDRESS: ECMWF
Reading RG2 9AX
UK

TELEPHONE: (44) 118 949 9475
FAX: (44) 118 949 9450
E-MAIL: j.kaiser@ecmwf.int

RELEVANT KEY EXPERTISE

Johannes Kaiser developed radiative transfer and instrument models along with retrieval algorithms for his PhD on measurements of atmospheric limb scattering in the UV-visible-NIR from SCIAMACHY aboard the Envisat satellite. He then worked as a Project Scientist at University of Zurich for close to three years, developing operational processing and archiving of data from the air-borne APEX spectrometer. He joined ECMWF in 2005, working first on the GMES HALO project and recently becoming a member of the GEMS project team, in which he works on fire emissions and aerosol modelling and assimilation.

EMPLOYMENT

2001-2002 University of Bremen
2002-2005 University of Zurich
2005 ECMWF

EDUCATION

1997 Diploma in Astrophysics from the Technical University of Berlin
2001 Ph.D. in Atmospheric Physics from the University of Bremen

RELEVANT EXAMPLE PUBLICATIONS

1. **J.W. Kaiser**, M.G. Schultz, J.-M. Gregoire, C. Textor, M. Sofiev, E. Bartholome, M. Leroy, R.J. Engelen, A. Hollingsworth, Observation Requirements for Global Biomass Burning Emission Monitoring, Proc. 2006 EUMETSAT Met. Sat. Conf., 2006.
2. J.-J. Morcrette, L. Jones, **J.W. Kaiser**, A. Benedetti, O. Boucher, Toward a forecast of aerosols wit the ECMWF Integrated Forecast System, *ECMWF Newsletter* No. 114, ECMWF, Reading, 2008.
3. A. Hollingsworth, R.J. Engelen, C. Textor, A. Benedetti, O. Boucher, F. Chevallier, A. Dethof, H. Elbern, H. Eskes, J. Flemming, C. Granier, **J.W. Kaiser**, J.J. Morcrette, P. Rayner, V.-H. Peuch, L. Rouil, M.G. Schultz, A.J. Simmons, The Global Earth-system Monitoring using Satellite and in-situ (GEMS) Projects: Towards a monitoring and forecasting system for atmospheric composition, *BAMS*, 2008, in press.

Global Real-time Fire Emission Estimates Based on Space-borne Fire Radiative Power Observations

J.W. Kaiser*, M. Suttie*, J. Flemming*, J.-J. Morcrette*, O. Boucher[†] and M.G. Schultz**

**European Centre for Medium-Range Weather Forecasts (ECMWF), UK*

[†]Hadley Centre for Climate Change, Met Office, UK

***Forschungszentrum Jülich (FZJ), Germany*

Abstract. We present the first real-time system for the estimation of global biomass burning emissions from several different satellite-based fire radiative power (FRP) observations. The FRP products from the MODIS and SEVIRI instruments on Aqua, Terra, and Meteosat-9 are combined by averaging all pixels with fire detection or just the potential of fire detection on a global grid with ~ 125 km resolution. The total observed area per grid cell is used as a proxy for the accuracy of the estimation. Thus the different observations can be merged consistently and the advantage the high temporal sampling frequency of the geostationary observation is maintained while almost global coverage is achieved with the polar orbiting platforms. The system is being tested and validation is ongoing. As a first trial application, daily pyrogenic carbon monoxide emissions are used in the European GEMS project to produce 3-day forecasts of the carbon monoxide plumes emitted by biomass burning. Some potential improvements of the method are discussed.

Keywords: biomass burning emission, smoke plume, global air quality forecast, fire radiative power observation, fire assimilation system

PACS: 92.60.hn Geochemical cycles

INTRODUCTION

Modelling of the atmospheric composition requires accurate knowledge of surface fluxes as lower boundary condition. The smoke emission by biomass burning needs to be described based on actual fire observations because it is highly variable on all time scales from hours to decades. Only real time satellite-based observations of active fires, as opposed to burnt area, can yield the information required for global-scale smoke plume forecasts. Fire Radiative Power (FRP) is a quantitative product that is derived from observations of the thermal emission near $4\text{ }\mu\text{m}$ wavelength. FRP promises superior accuracy to traditional hot-spot products since it is directly proportional to the combustion rate so that assumptions on available fuel load and combustion completeness are not required. [1]

Two satellite-based FRP products are currently available in real time: The MOD14 product [2, 3] is generated from MODIS observations with 1 km spatial resolution at the sub-satellite point. The MOD03 product provides the complete geolocation information for the MOD14 product. Two MODIS instruments operate aboard the polar orbiting Terra and Aqua satellites. Whenever MODIS is mentioned below it shall refer to the observation system comprising both instruments. MODIS has the advantage of global coverage. The observation frequency can, however, be as low as one per several days due to cloud cover.

The FRPPIXEL product [1, 4, 5] is generated from SEVIRI observations aboard the geostationary satellite Meteosat-9 by the EUMETSAT LandSAF (<http://landsaf.meteo.pt>). The spatial resolution at sub-satellite point is 3 km. Observations are recorded every 15 minutes. This allows for the observation of the diurnal cycle of fires and provides redundancy to compensate for temporary cloud cover.

We acquire both FRP products to produce global FRP and associated accuracy maps. Subsequently, daily emission rate maps are derived for several species. In a test application, carbon monoxide emissions are used to produce atmospheric fire plume forecasts for the next 3 days.

METHOD

In order to derive FRP maps, the observational FRP products are first transformed from MW/pixel to W/m^2 . Next, the observations in each grid cell and within each 1-hour slot are averaged with weights proportional to their respective

pixel sizes. All pixels with actual fire detections, i.e. $FRP > 0$, and potential fire detections, i.e. $FRP = 0$, are combined into a single map of the global FRP distribution. This roughly comprises all cloud-, snow-, and ice-free land pixels. The procedure accounts for partial cloud cover in a grid cell by implicitly assuming the same distribution of fires in the cloud-obscured and cloud-free parts. It also allows to ingest multiple observations of an individual fire. Multiple observations within one hour are caused by the high observation frequency of SEVIRI and the “bow-tie” effect of the MODIS scan and they carry additional information. The observation pixel sizes are aggregated in a separate map, which represents the observed area per grid cell.

In the third step, the FRP maps from MODIS and SEVIRI are averaged with weights proportional to their respective observed area maps. The two observed area maps are added to yield the total observed area.

A global daily FRP map is obtained by averaging the 24 hourly FRP maps, again with weights proportional to their respective observed areas. The sum of the 24 observed area maps yields a measure for the accuracy of the daily FRP map.

The biomass combustion rate [kg/s/m^2] is calculated by scaling FRP [W/m^2] with a factor 0.368×10^{-6} [1]. Individual species emission rates are subsequently derived by geographically dependent scaling with the emission factors used in GFEDv2 [6].

For the pyrogenic carbon monoxide plume forecast, the global GEMS reactive gas model [7] is run for 72 hours into the future. The CO field is initialised from the previous day’s 24 hour forecast, the meteorology is initialised from the operational ECMWF analysis, and the fire CO emission rate is derived from the observed average FRP of the previous 24 hours. Atmospheric CO is assumed to decay with a time constant of 50 days.

All calculations are based on an irregular grid with ~ 125 km resolution, i.e. reduced Gaussian T159.

RESULTS

The exemplary MODIS observed area during one hour, which is shown in Fig. 1a, exhibits one satellite track passing over South America and the US east coast and another over Mexico, the US, Russia and southward to the Himalaya. Larger values for off-nadir areas are due to the “bow tie” effect of the MODIS scan. The SEVIRI observations are obviously geographically limited to Africa, eastern South America, southern and middle Europe, and the Arabian peninsula and a bit eastwards (Fig. 1b). They exhibit larger observed area values than the MODIS ones since four measurements are recorded every hour. Both products are limited to cloud-, snow- and ice-free land areas on which a large enough fire can be detected.

The observed area accumulated from all instruments during one day (Fig. 1c) reflects both the high observation frequency of SEVIRI and the almost global coverage of the MODIS instruments. Only a few small regions remain unobserved. The SEVIRI disk is mostly well covered except for Central Africa, where persistent cloud cover inhibits accurate fire observations in a small area.

The FRP observed by MODIS and SEVIRI during the exemplary hour slot (Fig. 1d/e) seems to exhibit similar patterns in the overlap region in South America. Generally, the product complementarity is evident. The daily average FRP map (Fig. 1f) captures boreal forest fires in Canada and Eastern Siberia, fires in California and Southern Europe, and tropical fires in Southern Africa and South America. The daily accumulated observations (Fig. 1c) typically amount to an observed area per grid cell of $\sim 10^{12} \text{ m}^2$ in Africa, while MODIS alone achieves values of $\sim 10^{11} \text{ m}^2$ in other tropical regions. Therefore, where SEVIRI observations are available, the combined FRP estimate (Fig. 1f) is dominated by the SEVIRI observations with a weight ratio of typically 10/1.

Preliminary forecasts of atmospheric carbon monoxide plumes from biomass burning are published on the GEMS web site <http://gems.ecmwf.int>. A forecast for the 700 hPa pressure level with 48 hours lead time is reproduced in Fig. 2. The plumes from the African and Canadian fires are dominating and those of the Californian and South American fires are also well visible. The plume structure in the Arctic originates from transport of carbon monoxide that had been emitted during the preceding weeks, mostly in Siberia.

DISCUSSION

We are running the first real-time system for the global estimation of biomass burning emissions from FRP measurements by several different satellite-based instruments. In each grid cell, the observed area is interpreted as a measure for the accuracy of the FRP product. Thus FRP products with different measurement characteristics can be merged in a consistent way.




FIGURE 1. Observed Area [$\text{m}^2/\text{grid cell}$] (top) and average FRP [W/m^2] (bottom) for MODIS (left) and SEVIRI (middle) observations during 1700–1800 UTC and for the combination of all observations during 0000–2359 UTC (right), on 27 July 2008. The plots show the logarithm base 10 of the actual values.




FIGURE 2. 48-hour atmospheric fire plume forecast, valid on 30 July 2008, 0000 UTC: CO [ppb] on 700 hPa pressure level.

By including observations of no fire being present, i.e. $FRP = 0$, in the algorithm, ad hoc assumptions on the lifetime of the detected fires can be avoided. If the fire distribution within a grid cell is homogeneous, including $FRP = 0$ observations also avoids a bias being introduced by the incomplete observation of partially cloudy grid cells.

Only a small fraction of the grid cells remains unobserved during one day when FRP products from SEVIRI and the two MODIS instruments are combined. This may lead to a small underestimation of the global FRP. Additional bias may be introduced because of the diurnal cycle in regions that are not covered by the frequent SEVIRI observations. If the FRPPIXEL approach can be extended to other geostationary instruments this uncertainty could be reduced.

The new system still needs extended validation. Ongoing work also aims at the implementation of a fire assimilation system based on the hourly averaged FRP observations presented here. The assimilation system shall produce estimates for the fire emission with a temporal resolution of one hour by bridging observation gaps with a numerical model of the fire's diurnal cycle.

ACKNOWLEDGMENTS

We acknowledge the vital vision and leadership provided by Tony Hollingsworth[†] and Adrian Simmons in the GEMS project. Martin Wooster from King's College London has kindly introduced us to the SEVIRI FRP product, which is now being supplied by the very supportive staff at the EUMETSAT LandSAF in Lisbon, Portugal. NOAA is making the MODIS products available. Guido van der Werf (Free University Amsterdam, The Netherlands) has kindly provide the emission factors used in GFEDv2. This work has been carried out in the GEMS project, which is funded by the European Commission under the EU Sixth Research Framework Programme, contract number SIP4-CT-2004-516099.

REFERENCES

1. M. Wooster, G. Roberts, G. Perry, and Y. Kaufman, *JGR* **110** (2005).
2. C. Justice, L. Giglio, S. Korontzi, J. Owens, J. Morisette, D. Roy, J. Descloitres, S. Alleaume, F. Petitcolin, and Y. Kaufman, *Remote Sensing of Environment* **83**, 244–262 (2002).
3. L. Giglio, MODIS Collection 4 Active Fire Product User's Guide Version 2.2 (2005).
4. G. Roberts, M. Wooster, G. Perry, N. Drake, L. Rebelo, and F. Dipotso, *Journal of Geophysical Research* **110** (2005).
5. M. Schultz, M. Wooster, O. Boucher, M. Doutriaux-Boucher, C. Granier, A. Heil, A. Hollingsworth, J. Kaiser, T. Kasikowski, J.-J. Morcrette, G. Roberts, A. Simmons, and G. van der Werf, Evaluation of a fire radiative power product derived from meteosat 8/9 and identification of operational user needs, Tech. rep., EUMETSAT, Darmstadt, Germany (2008).
6. G. van der Werf, J. Randerson, L. Giglio, G. Collatz, P. Kasibhatla, and A. Arellano Jr, *Atmos. Chem. Phys.* **6**, 3423–3441 (2006).
7. A. Hollingsworth, R. Engelen, C. Textor, O. B. A. Benedetti, F. Chevallier, A. Dethof, H. Elbern, J. F. H. Eskes, C. Granier, J. Kaiser, J.-J. Morcrette, V.-H. P. P. Rayner, L. Rouil, M. Schultz, A. Simmons, and the GEMS consortium, *BAMS* (2008), in press.

SUBMITTED TO THE PROCEEDINGS OF THE INTERNATIONAL RADIATION SYMPOSIUM 2008

1. **Einsatz von multispektralen Satellitenbilddaten in der Wasserhaushalts- und Stoffstrommodellierung – dargestellt am Beispiel des Rureinzugsgebietes**
von C. Montzka (2008), XX, 238 Seiten
ISBN: 978-3-89336-508-1
2. **Ozone Production in the Atmosphere Simulation Chamber SAPHIR**
by C. A. Richter (2008), XIV, 147 pages
ISBN: 978-3-89336-513-5
3. **Entwicklung neuer Schutz- und Kontaktierungsschichten für Hochtemperatur-Brennstoffzellen**
von T. Kiefer (2008), 138 Seiten
ISBN: 978-3-89336-514-2
4. **Optimierung der Reflektivität keramischer Wärmedämmschichten aus Yttrium-teilstabilisiertem Zirkoniumdioxid für den Einsatz auf metallischen Komponenten in Gasturbinen**
von A. Stuke (2008), X, 201 Seiten
ISBN: 978-3-89336-515-9
5. **Lichtstreuende Oberflächen, Schichten und Schichtsysteme zur Verbesserung der Lichteinkopplung in Silizium-Dünnschichtsolarzellen**
von M. Berginski (2008), XV, 171 Seiten
ISBN: 978-3-89336-516-6
6. **Politiksznarien für den Klimaschutz IV – Szenarien bis 2030**
hrsg.von P. Markewitz, F. Chr. Matthes (2008), 376 Seiten
ISBN 978-3-89336-518-0
7. **Untersuchungen zum Verschmutzungsverhalten rheinischer Braunkohlen in Kohledampferzeugern**
von A. Schlüter (2008), 164 Seiten
ISBN 978-3-89336-524-1
8. **Inorganic Microporous Membranes for Gas Separation in Fossil Fuel Power Plants**
by G. van der Donk (2008), VI, 120 pages
ISBN: 978-3-89336-525-8
9. **Sinterung von Zirkoniumdioxid-Elektrolyten im Mehrlagenverbund der oxidkeramischen Brennstoffzelle (SOFC)**
von R. Mücke (2008), VI, 165 Seiten
ISBN: 978-3-89336-529-6
10. **Safety Considerations on Liquid Hydrogen**
by K. Verfondern (2008), VIII, 167 pages
ISBN: 978-3-89336-530-2

11. **Kerosinreformierung für Luftfahrtanwendungen**
von R. C. Samsun (2008), VII, 218 Seiten
ISBN: 978-3-89336-531-9
12. **Der 4. Deutsche Wasserstoff Congress 2008 – Tagungsband**
hrsg. von D. Stolten, B. Emonts, Th. Grube (2008), 269 Seiten
ISBN: 978-3-89336-533-3
13. **Organic matter in Late Devonian sediments as an indicator for environmental changes**
by M. Kloppisch (2008), XII, 188 pages
ISBN: 978-3-89336-534-0
14. **Entschwefelung von Mitteldestillaten für die Anwendung in mobilen Brennstoffzellen-Systemen**
von J. Latz (2008), XII, 215 Seiten
ISBN: 978-3-89336-535-7
15. **RED-IMPACT
Impact of Partitioning, Transmutation and Waste Reduction Technologies on the Final Nuclear Waste Disposal
SYNTHESIS REPORT**
ed. by W. von Lensa, R. Nabbi, M. Rossbach (2008), 178 pages
ISBN 978-3-89336-538-8
16. **Ferritic Steel Interconnectors and their Interactions with Ni Base Anodes in Solid Oxide Fuel Cells (SOFC)**
by J. H. Froitzheim (2008), 169 pages
ISBN: 978-3-89336-540-1
17. **Integrated Modelling of Nutrients in Selected River Basins of Turkey**
Results of a bilateral German-Turkish Research Project
project coord. M. Karpuzcu, F. Wendland (2008), XVI, 183 pages
ISBN: 978-3-89336-541-8
18. **Isotopengeochemische Studien zur klimatischen Ausprägung der Jüngerer Dryas in terrestrischen Archiven Eurasiens**
von J. Parplies (2008), XI, 155 Seiten, Anh.
ISBN: 978-3-89336-542-5
19. **Untersuchungen zur Klimavariabilität auf dem Tibetischen Plateau - Ein Beitrag auf der Basis stabiler Kohlenstoff- und Sauerstoffisotope in Jahrringen von Bäumen waldgrenznaher Standorte**
von J. Griessinger (2008), XIII, 172 Seiten
ISBN: 978-3-89336-544-9

20. **Neutron-Irradiation + Helium Hardening & Embrittlement Modeling of 9%Cr-Steels in an Engineering Perspective (HELENA)**
by R. Chaouadi (2008), VIII, 139 pages
ISBN: 978-3-89336-545-6
21. **Messung und Bewertung von Verkehrsemissionen**
von D. Klemp, B. Mittermaier (2008), ca. 230 Seiten
ISBN: 978-3-89336-546-3
22. **Verbundvorhaben APAWAGS (AOEV und Wassergenerierung) – Teilprojekt: Brennstoffreformierung – Schlussbericht**
von R. Peters, R. C. Samsun, J. Pasel, Z. Porš, D. Stolten (2008), VI, 106 Seiten
ISBN: 978-3-89336-547-0
23. **FREEVAL**
Evaluation of a Fire Radiative Power Product derived from Meteosat 8/9 and Identification of Operational User Needs
Final Report
project coord. M. Schultz, M. Wooster (2008), 139 pages
ISBN: 978-3-89336-549-4



FREEVAL

Evaluation of a Fire Radiative Power Product derived from
Meteosat 8/9 and Identification of Operational User Needs

Final Report

Martin G. Schultz, Project Coordinator
Martin Wooster, Project Co-coordinator